



DFE-528TX

“
This adapter plugs into a desktop computer's PCI expansion bus slot to run in 10BASE-T or 100BASE-TX mode, half- or full-duplex.

10/100Mbps PCI Card

The DFE-528TX is a high-performance auto-sensing 10/100Mbps dual-speed adapter for the PCI bus. Installable in a PC equipped with PCI expansion slots, this card turns a desktop computer into a high-bandwidth graphic/multimedia workstation running at full-duplex speed.

High Performance

With 32-bit Bus Master operation, the card guarantees the highest performance for power workstations and servers. Bus Master transfers data directly between the card and the host, bypassing the host CPU to alleviate its workload. This allows the host to concentrate on the application at hand.

10/100Mbps Flexible Connection

The card's single connector connects to either 10BASE-T Ethernet or 100BASE-TX Fast Ethernet. 10/100Mbps speeds are auto-negotiated, completely without users' need to intervene.

Full Duplex Support

Full/half duplex operations are auto-negotiated in both 10BASE-T and 100BASE-TX modes. When connected to a switch in full duplex, the network speed can be increased to 200Mbps, making the card an ideal NIC for high-speed workstation deployment.

Key Features

- 10/100Mbps auto-sensing with single shielded RJ-45 connector
- 32-bit PCI Bus Master operation
- Full/half duplex support
- Low network command processing overhead
- Runs Win95, 98, NT, ME, 2000, NetWare, Unix
- Easy-to-view diagnostic LEDs

DFE-528TX

Technical Specifications

10/100Mbps PCI Card

General

Standards

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- ANSI/IEEE 802.3 NWay auto-negotiation
- PCI local bus 2.1, 2.2 specifications

Topology

Star

Protocol

CSMA/CD

Network Data Transfer Rates

- 10BASE-T:
 - 10Mbps (half-duplex)
 - 20Mbps (full-duplex)
- 100BASE-TX:
 - 100Mbps (half-duplex)
 - 200Mbps (full-duplex)

Network Cables

- 10BASE-T:
 - UTP Cat. 3 (100 m)
 - UTP Cat. 4, 5 (100 m)
 - EIA/TIA-568 STP (100 m)
- 100BASE-TX:
 - UTP Cat. 5 (100 m)
 - EIA/TIA-568B STP (100 m)

System

IRQ

Allocated by system

I/O Address

Allocated by system

Diagnostic LED Report

- Link
- Activity

Physical & Environmental

Power Consumption

0.32 watts (96mA @ 3.3V) max.

Dimensions

120 x 58 mm

Weight

25 grams

Operating Temperature

0° - 55°C

Storage Temperature

-25° - 55°C

Humidity

10% - 90% non-condensing

Emission

- FCC Class B
- CE Class B
- VCCI Class B

LAN O.S. & Drivers Support

- Microsoft Windows 95, 98, NT 4.0, 2000, ME, XP
- Novell NetWare 3.12, 4.1x, 5.x ODI driver
- Microsoft LAN Manager

- Packet driver
- NDIS 2.0 driver
- SCO Open 5.x



Ordering Information

DFE-528TX 10/100Mbps PCI Card

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A.	TEL: 1-949-788-0805	FAX: 1-949-753-7033
Canada	TEL: 1-905-829-5033	FAX: 1-905-829-5095
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
U.K.	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-61-96779900	FAX: 49-61-967799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Benelux	TEL: 31-10-204-5740	FAX: 31-10-204-5880
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8-564-61900	FAX: 46-(0)8-564-61901
Norway	TEL: 47-22-991890	FAX: 47-22-205700
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
China	TEL: 86-010-8518-2533	FAX: 86-010-8518-2250
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914
Middle East	TEL: 202-6356176	FAX: 202-6356192
South America	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
South Africa	TEL: 27(0)126652165	FAX: 27(0)126652186
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE
Rev. 01 (Nov. 2002)
Printed in Taiwan