



DP-G321

## 3-Port Wireless Print Server

*With 2 USB Ports, 1 Parallel Port & 802.11g WLAN*

The DP-G321 multi-port wireless print server provides 2 high-speed USB 2.0 printer ports for connection to 2 USB-supported printers, and 1 parallel printer port for connection to a parallel printer. Equipped with a 10/100BASE-TX Ethernet and high-speed 802.11g wireless LAN interface, this device lets you conveniently share your printer with a group of users, with or without the network wires. Supporting multiple network operating systems, this print server brings a high level of flexibility and performance to your printing needs.

### Multiple Ports Save Cost

With 3 printer ports available from a single device, you don't need to purchase and install a separate print server for each printer. This multi-port print server is only slightly more expensive than a single-port print server. Where your printers are closely placed together, it makes sense to buy 1 single print server instead of 3.

### Simultaneous Printing on All Printers

Equipped with a powerful CPU, large memory and high-speed printer ports, this print server makes printing of your network files fast. All printers attached to this device can print their print jobs at the same time, giving your multi-port print server a similar performance as 3 separate single-port print servers.

### Ethernet and Wireless Interfaces

Two LAN interfaces are provided on this print server: (1) a 10/100BASE-TX Ethernet port and (2) a high-speed 802.11g wireless LAN interface supporting up to 54Mbps network data transfer. This built-in flexibility allows both Ethernet users and wireless users to print files through the print server.

### Wireless Network Security

The DP-G321 provides the necessary security for wireless users, using the user-selectable 64/128-bit industry-standard WEP (Wired Equivalent Privacy) encryption protocol. Data privacy mechanism is based on a shared key algorithm, as described in the wireless LAN standard.

### Remote Printing Support

The DP-G321 supports IPP (Internet Printing Protocol), so you can set an IP address in the print server for remote users to output print files to the printers from remote places.

### Setup & Access Control

Setting up the print server can be done from any workstation running a web browser. In addition, Windows-based menu-driven program allows you to do administration jobs and set access control. Access to your network printer can be control by setting up a list of MAC addresses of user computers allow to print files. SNMP and latest MIB-II MIBs are built into the print server, allowing you to manage this device on an SNMP standard-based network.

### Key Features

- 2 high-speed USB 2.0 printer ports, 1 parallel printer port
- Built-in high-speed 802.11g wireless interface
- 10/100BASE-TX Ethernet port
- Prints files from Windows, Unix, NetWare, Macintosh
- Remote printing support
- User access & print job control
- Easy web-based administration
- Windows-based program for easy setup/management of print jobs
- SNMP and MIB-II (RFC 1213) support for platform-independent management

# DP-G321

## Technical Specifications

## Print Server

### Printer Ports

- 2 high-speed USB 2.0 port
- 1 parallel DB-36 male Centronics port
- Bi-directional communication support

### LAN Interfaces

- 802.11g wireless LAN
- 10/100BASE-TX port

### Network Protocol Support

- TCP/IP
- NetBEUI
- AppleTalk
- LPR
- SMB (over IP)
- IPX
- IPP (Internet Printing Protocol)

### Management and Diagnostics

- Standard: SNMP
- MIBs: MIB-II (RFC 1213)
- Mac OS RendezVous
- Windows-based GUI & web-based administration
- Configuration reset button

### IP Assignment

- Manual
- Automatic through DHCP, BOOTP or RARP server

### Diagnostic LED Indicators

- Power
- Ethernet (Link/Act)
- WLAN
- USB
- LPT

### Built-in Wireless LAN

#### Wireless LAN Standards

- 802.11g
- 802.11b

#### Data Rates

- 802.11g: up to 54Mbps (6/9/12/18/24/36/48/54Mbps)
- 802.11b: up to 11Mbps (1/2/5.5/11Mbps)

#### Transmission Technology

DSSS

#### RF Frequency Range

2.4 to 2.4835GHz

#### Operating Channels

- 1 to 11 channels (FCC)
- 1 to 13 channels (ETSI)

#### Data Modulation Type

DBPSK, DQPSK, CCK, OFDM

#### Antenna

2dBi Gain external dipole detachable (reserve SMA connector) antenna

#### Transmit Output Power

16dBm (typical)

#### Receive Sensitivity (for 802.11b)

- (typically @PER < 8% packet size 1024 @ 25 C +/- 5 C)
- 11Mbps (CCK): -82 dBm
- 5.5Mbps (CCK): -86 dBm
- 2Mbps (QPSK): -90 dBm
- 1Mbps (BPSK): -90 dBm

#### Receive Sensitivity (for 802.11g)

- (typically @PER < 8% packet size 1024 @ 25 C +/- 5 C)
- 54Mbps (OFDM): -66 dBm
- 48Mbps (OFDM): -64 dBm
- 36Mbps (OFDM): -70 dBm
- 24Mbps (OFDM): -72 dBm
- 18Mbps (OFDM): -80 dBm
- 12Mbps (OFDM): -84 dBm
- 9Mbps (OFDM): -86 dBm
- 6Mbps (OFDM): -88 dBm

#### Operating Range \*

- Indoors: 100 meters
- Outdoors: 400 meters

\* Environmental factors may adversely affect range.

### Security

WEP 64/128-bit data encryption (user-selectable)

### O.S. Support

- Windows 98, ME, 2000, XP
- MacOS EtherTalk
- Unix
- NetWare 5.0 or above (Native NDS)
- Ipd

### Environmental & Physical

#### Input Power

- 5V DC 2.5A
- Through external power adapter

#### Dimensions

142 mm (W) x 109 mm (D) x 31 mm (H) (device only)

#### Weight

325 grams

#### Operating Temperature

0° to 50 °C

#### Storage Temperature

-25° to 55 °C

#### Humidity

5% to 95% non-condensing

#### Emissions

- FCC Class B
- CE Class B
- C-Tick

#### Box Includes

- DP-G321 print server
- CD-ROM with Manual and Print Server Administration program
- Quick Installation Guide
- External power adapter



## Ordering Information

### 802.11g Wireless Multi-Port Print Server

#### DP-G321

With 2 USB 2.0 printer ports,  
1 parallel printer port, 10/100BASE-TX port

Please specify your order as follows:

<b>DP-G321/ANA</b>	US standard power adapter, North America frequency
<b>DP-G321/BEU</b>	UK standard power adapter, EU frequency
<b>DP-G321/EEU</b>	EU standard power adapter, EU frequency
<b>DP-G321/NEU</b>	Australia standard power adapter, EU frequency
<b>DP-G3210/CN</b>	China standard power adapter, China frequency
<b>DP-G3210/ENA</b>	EU standard power adapter, North America frequency

# D-Link®

Specifications subject to change without prior notice.  
D-Link is a registered trademark and AirPlusG is a trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

<b>U.S.A</b>	TEL: 1-714-885-6000	FAX: 1-866-743-4905
<b>Canada</b>	TEL: 1-905-8295033	FAX: 1-905-8295223
<b>Europe</b>	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
<b>Germany</b>	TEL: 49-6196-77990	FAX: 49-6196-7799300
<b>France</b>	TEL: 33-1-30238688	FAX: 33-1-30238689
<b>Netherlands</b>	TEL: 31-10-282-1445	FAX: 31-10-282-1331
<b>Belgium</b>	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500
<b>Italy</b>	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
<b>Iberia</b>	TEL: 34-93-4090770	FAX: 34-93-4910795
<b>Sweden</b>	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
<b>Norway</b>	TEL: 47-22-309075	FAX: 47-22-309085
<b>Denmark</b>	TEL: 45-43-969040	FAX: 45-43-424347
<b>Finland</b>	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
<b>Singapore</b>	TEL: 65-6774-6233	FAX: 65-6774-6322
<b>Australia</b>	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
<b>Japan</b>	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
<b>China</b>	TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
<b>India</b>	TEL: 91-022-652-6696	FAX: 91-022-652-8914
<b>Middle East (Dubai)</b>	TEL: 9714-8834234	FAX: 9714-8834394
<b>Turkey</b>	TEL: 90-212-335-2553	FAX: 90-212-335-2500
<b>Egypt</b>	TEL: 202-414-4295	FAX: 202-415-6704
<b>Israel</b>	TEL: 972-9-9715700	FAX: 972-9-9715601
<b>Latinamerica</b>	TEL: 56-2-232-3185	FAX: 56-2-232-0923
<b>Brazil</b>	TEL: 55-11-55039320	FAX: 55-11-55039321
<b>South Africa</b>	TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
<b>Russia</b>	TEL: 7-095-744-0099	FAX: 7-095-744-0099#350
<b>Taiwan</b>	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
<b>D-Link Corp.</b>	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299

  
RECYCLABLE  
Rev. 01 (Jun. 2004)