

Product announcement



Product:	DSL-504T
Product name:	ADSL Ethernet Router (Annex A), 4 Ports Switch
Key features:	<ul style="list-style-type: none"> • Meets T-DSL (U-R2) performance requirements • Downstream rate of up to 8 MBit • Upstream rate of up to 1MBit • Rate adaptive ADSL technology • DMZ and Virtual Server Mapping support • Virtual Private Network (VPN) pass-through support • Ethernet über ATM, IP über ATM, PPPoE • PAP/CHAP Authentication • Supports up to 8 virtual circuits simultaneously (PVC) • LAN port supports 10/100 MBit Fast Ethernet connection
Bid text:	DSL-504T D-Link ADSL Ethernet Router (Annex A), 4 Port Switch 10/100 TX, 8 MBit Down- and 1 MBit Upstream, T-DSL (UR2), 10/100 MBit LAN Port, Web based management
Why to Buy D-Link	<ul style="list-style-type: none"> • Easy to connect • Web based management • No driver for installation needed • Fast 8 MBit download speed • Works with all ISP's (AOL, Telekom, Arcor, etc.) • For ISDN Telephone lines • DSL Gateway ready
Technical Details:	<p>STANDARDS: ITU G.992.1 (G.dmt) ITU G.992.2 (G.lite) ITU G.994.1 (G.hs) ANSI T1.413 Issue # 2</p> <p>DATA TRANSFER RATE: G.dmt full rate: Downstream up to 8 MBit Upstream up to 1Mbit G.lite: Downstream up to 1.5 MBit Upstream up to 512 KBit</p> <p>MEDIA INTERFACE EXCHANGE: RJ-11 port ADSL telephone line connection RJ-45 port for 10/100 BASE-T Ethernet connection</p> <p>DC Inputs: 9 VAC 1A external power adapter</p> <p>Power Adapter: 12 V DC 1.2A</p> <p>Safety: TÜV/GS</p> <p>Power Consumption: 9 Watts Max.</p> <p>Operating Temperature: 5 ° to 40 °</p> <p>Humidity: 5 to 95% (non-condensing)</p> <p>Dimensions: 180 mm x 114 mm x 30 mm</p> <p>Weight: 332 g</p> <p>EMI: CE</p>
Package Contents:	QIG, Manual CD, RJ-45 Cable, Telephone Cable, Power Supply
Retail:	Yes
UPC Code:	790069-265174
Units per Carton:	10
Dimensions and Weight:	250 x 290 x 65 mm, 1.36Kg (Box) 530 x 365 x 385 mm, 15,55 Kg (carton)
Revision:	DSL-504T H/W: A1
Available:	Now
End User Price (Gross):	€