



DWL-520+

Wireless LAN PCI Card with 22Mbps enhanced network speed and detachable antenna.

2.4GHz Enhanced Performance Wireless LAN PCI Card

The D-Link AirPlus DWL-520+ is an enhanced speed wireless network PCI card desktop PCs. This card connects you to a 2.4GHz wireless LAN, giving you fast, secured mobile access to the network. It provides enhanced transmission speeds at up to 22Mbps, industry standard interoperability, strong 256-bit data security and ease of use for desktop PC users requiring fast, secure wireless network connection.

Enhanced Speed Transmission

At 22 Megabits per second, the DWL-520+ delivers high data transfer rate within the industry standard. This speed is double the 11Mbps normally found among IEEE 802.11b 2.4GHz wireless LAN devices.

Industry-standard Interoperability

With both WiFi™ certification compatibility and IEEE 802.11b wireless LAN industry standard compliance, the DWL-520+ adapter provides you with excellent network interoperability.

Network Security

Security is an issue when data is transmitted without the wires. In the air, transmitted data can be easily intercepted if not well protected by a security scheme. The DWL-520+ provides the necessary security, using the enhanced 64/128/256-bit industry-standard WEP (Wired Equivalent

Privacy) encryption protocol. Data privacy mechanism is based on a shared key algorithm, as described in the wireless LAN standard.

Easy Installation

With PCI plug-and-play installation, the DWL-520+ can be easily installed into a desktop PC to provide connectivity directly to another 802.11b wireless enabled device (ad-hoc mode) or through an 802.11b Access Point (infra-structure mode).

Detachable Antenna

The DWL-520+ is equipped with an SMA reverse detachable dipole antenna with an effective range of 100 meters indoors, or 400 meters outdoors. Where a longer range is required, you can easily remove this antenna and replace it with a higher Gain antenna.

Features

- IEEE 802.11b industry standard compliance
- 2.4GHz frequency band Direct Sequence Spread Spectrum (DSSS)
- Up to 22Mbps enhanced data transfer rate
- 32-bit Bus Master data transfer with PC host
- Detachable SMA reverse dipole antenna
- Enterprise-level security with 64/128/256-bit WEP data encryption
- Supports Windows 98, 2000, ME, XP
- Wi-Fi™ compatibility certified

DWL-520+

Technical Specifications

2.4 GHz Wireless LAN PCI Card

Standards & Hardware Specifications

LAN Standard

- IEEE 802.11b wireless LAN

Bus Type

- PCI 2.2 specifications
- 32-bit Bus Master data transfer mode

Media Access Control Protocol

CSMA/CA

Network Architecture Types

- Supports Ad-Hoc and Infrastructure Modes
- Cell to cell roaming (IEEE 802.11b compliant)

Data Rates

- 22 Mbps
- 11 Mbps
- 5.5 Mbps
- 2 Mbps
- 1 Mbps
- Auto fallback

Data Rate & Modulation

- 22Mbps/8.5db: PBCC
- 11Mbps/4.5db: PBCC
- 11Mbps/8.5db: CCK
- 5.5Mbps/1.5db: PBCC
- 5.5Mbps/5.5db: CCK
- 2Mbps/3db: Barker

Operating Channels

- North America (FCC): 11
- Canada (DOC): 11
- Europe (ETSI): 13 (Except Spain and France)
- Japan (MKG): 14

Sensitivity @ PER<0.08

- 22Mbps < -80dBm (PBCC)
- 11Mbps < -84dBm (PBCC)
- 5.5Mbps < -86dBm
- 2 Mbps < -89dBm
- 1 Mbps < -91dBm

Frequency Range

2.4 - 2.462 GHz

Modulation Techniques

- Direct Sequence Spread Spectrum (DSSS)
- Packet Binary Convolutional Coding (PBCC)
- 11-chip Barker Sequence

Key Management

Automatic Dynamic Key Allocation (ADKA) through public key

Data Security

64, 128, 152-bit WEP (Wired Equivalent Privacy) encryption

Antenna

Detachable 2dBi Gain dipole diversity antenna (reverse SMA connector)

Mobility

Seamless roaming across cell boundaries within access point range

Transmitter Output Power

15dBm ±2dB

Over-Driving Levels

Tolerates up to +17dBm at the Antenna

Range Coverage (Open Environment)

- Indoors: Up to 100 meters (328 feet)
- Outdoors: Up to 400 meters (1,312 feet)

Physical & Environmental

Diagnostic LEDs

- Power
- Link/Activity

Operating Voltage

3.3V +/- 10%

Power Consumption

- Transmission: 650 mA (max.)
- Reception: 350 mA (max.)

Dimensions

133 (L) x 121 (W) x 18 (H) mm
(5.24 x 4.76 x 0.71 inches)

Weight

77 grams (0.17 lb.)

Operating Temperature

0° - 55°C (32° - 131°F)

Storage Temperature

-30° - 70°C (-22° - 158°F)

Humidity

Up to 95%, non-condensing

Emission Certification

- FCC Class B
- CE Class B

Compatibility Certification

Wi-Fi™

MTBF (Mean Time Between Failure)

> 30,000 hours

Software

O.S. Support

Windows 98, 2000, ME, XP



Ordering Information

DWL-520+

IEEE 802.11b Wireless LAN PCI Card

Please specify your order as follows:

DWL-520+/NA
DWL-520+/EU
DWL-520+/CN

For North America frequency channels (worldwide type packaging)
For EU frequency channels (worldwide type packaging)
For EU frequency channels (packaging for China)

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A.	TEL: 1-949-788-0805	FAX: 1-949-753-7033
Canada	TEL: 1-905-829-5033	FAX: 1-905-829-5095
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511
U.K.	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511
Germany	TEL: 49-61-96779900	FAX: 49-61-967799300
France	TEL: 33-1-30.23.86.88	FAX: 33-1-30.23.86.89
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723
Iberia	TEL: 34-93-4965751	FAX: 34-93-4965701
Sweden	TEL: 46-(0)8-564-61900	FAX: 46-(0)8-564-61901
Norway	TEL: 47-22-991890	FAX: 47-22-207039
Denmark	TEL: 45-43-96.90.40	FAX: 45-43-42.43.47
Finland	TEL: 358-9-622-91660	FAX: 358-9-622-91661
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-9417-7100	FAX: 61-2-9417-1077
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
China	TEL: 86-10-88097777	FAX: 86-10-88096789
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914
Middle East	TEL: 202-2456176	FAX: 202-2456192
South America	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brazil	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
South Africa	TEL: 27(0)126652165	FAX: 27(0)126652186
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE
Rev. 01 (Jun 2002)
Printed in Taiwan

