

AirPremier AG



Dualband



— DWL-7100AP

802.11a/g Tri-Mode Dualband Wireless Access Point

The D-Link AirPremier AG DWL-7100AP is a tri-mode, dualband wireless Access Point that provides the most expanded user bandwidth available in an AP. Hundreds of wireless clients can connect to this AP using any one of its 11 non-overlapping channels to transfer data at speeds never before achievable in a wireless device.

Dualband Operation

The DWL-7100AP operates seamlessly and simultaneously in both the 2.4GHz and 5GHz frequency spectrums supporting the 802.11b and the newer, faster 802.11a and 802.11g wireless standards. For offices, schools or public hotspots that already use 802.11b devices, the DWL-7100AP is a great way to expand an existing network. It enables more users to communicate with one another, access data and the Internet. Now, you can have an AP that will compliment your existing network and protect the investment you made when you provided the convenience of wireless networking.

Fast, Unobstructed Data Transfer

The DWL-7100AP offers transfer rates up to 108Mbps Turbo mode* in either the 2.4GHz or 5GHz bands, large data packets travel from the router to a remote desktop or roaming laptop PC at up to five times the speed of previous wireless devices. Everyone can work faster and more efficiently or watch a streaming video smoothly. The additional (802.11a) 5GHz band also offers a way to quickly transfer data without the interference produced by other devices operating in the 2.4GHz frequency.

Network Segmentation by Frequency Channels

Network administrators can partition the usage of the dualband DWL-7100AP by segmenting the users on the wireless network by frequency band. Users who require special networking privileges access to sensitive information, specific departments or video conferencing may use just the 802.11a channels; while other employees may just use the 802.11b and 802.11g channels. This type of user segmentation optimizes the AP's performance and delivers the best network experience to each set of users.

Enhanced Network Security

The DWL-7100AP is ideal for network administrators who require additional network security features. All of the AP's settings are easily accessible in the web-based software user interface that features a step-by-step Setup Wizard to get your AP up and running in just a matter of minutes. The DWL-7100AP incorporates the 802.1x standard for wireless user authentication and WPA (Wi-Fi™ Protected Access) which dynamically encrypts data as it's being sent.

Key Features

- 802.11a/g industry standard
- Dual 5GHz and 2.4GHz frequency bands
- Up to 108Mbps Turbo mode network data transfer rate on both frequency bands
- Compatible with existing 802.11b wireless devices
- Strong 64/128/152-bit WEP data encryption
- WPA security
- Enhanced security: AES (*), 802.1x authentication, RADIUS client, and Cipher negotiation
- DFS/TPC support for European operation
- 10/100Mbps Fast Ethernet port to bridge wireless LAN with Ethernet-based network & servers
- Web-based configuration/management

*AES feature available as a driver/firmware upgrade in the near future. Turbo mode operation on 5GHz is not allowed in the EC(European Community).

DWL-7100AP

Technical Specifications

Standards

- IEEE 802.11g
- IEEE 802.11b
- IEEE 802.11a
- IEEE 802.3
- IEEE 802.3u

Media Access Control

CSMA/CA with ACK

Ethernet Port

10/100BASE-TX Ethernet port

Wireless Frequency Range *

- 802.11b/g: 2.4 to 2.4835GHz
- 802.11a: 5.150 to 5.8750GHz

* Software configurable as allowable frequency will vary among different countries in the European region.

Wireless Data Rates

(With automatic fallback)

54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps

Modulation Technology

- 802.11a/g: BPSK, QPSK, 16QAM, 64QAM, OFDM
- 802.11b: DQPSK, DBPSK, DSSS, CCK

Security

- 64/128/152-bit WEP
- 802.1x
- WPA: Wi-Fi Protected Access (64/128/152-bit WEP with TKIP, MIC, IV Expansion, Shared Key Authentication)
- Advanced Encryption Standard (AES) support

* WPA features available as a driver/firmware upgrade download in the near future

Antennas

Dual non-detachable dipole external antennas:

- For 2.4GHz: 2dBi Gain antenna
- For 5GHz: 2dBi Gain antenna

Dual PIFA internal antennas:

- For 2.4GHz: 2dBi Gain antenna
- For 5GHz: 2dBi Gain antenna

Wireless Operating Range *

- Indoors: up to 100 m (328 feet)
- Outdoors: up to 400 m (1,312 feet)

* Environmental conditions may adversely affect wireless signal range

Receive Sensitivity

- 802.11a (1000-byte PDUs @ 10% PER):
 - 87dBm for 6Mbps
 - 86dBm for 9Mbps
 - 85dBm for 12Mbps
 - 83dBm for 18Mbps
 - 80dBm for 24Mbps
 - 76dBm for 36Mbps
 - 71dBm for 48Mbps
 - 66dBm for 54Mbps
 - 73dBm for 108Mbps (Turbo Mode)
- 802.11b (@ 8% PER):
 - 83dBm for 11Mbps
 - 89dBm for 2Mbps
- 802.11g (1000-byte PDUs @ 10% PER):
 - 87dBm for 6Mbps
 - 86dBm for 9Mbps
 - 85dBm for 12Mbps
 - 83dBm for 18Mbps
 - 80dBm for 24Mbps
 - 76dBm for 36Mbps
 - 71dBm for 48Mbps
 - 66dBm for 54Mbps

Transmit Output Power

- 802.11a:
 - +14 to 15dBm @ 54Mbps, 108Mbps
 - +14 to 16dBm @t 48Mbps
 - +16 to 18dBm @t 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps, 6Mbps
- 802.11b:
 - +18dBm @ 11Mbps, 5.5Mbps, 2Mbps, 1Mbps
- 802.11g:
 - +14 to 15dBm @ 54Mbps, 108Mbps
 - +14 to 16dBm @ 48Mbps
 - +16 to 18dBm @ 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps, 6Mbps

Diagnostic LEDs

- Power
- 10Mbps (Link/Act)
- 100Mbps (Link/Act)
- WLAN 802.11b/g
- WLAN 802.11a

Device Management

- Web-based: Internet Explorer v6 or later; Netscape Navigator v6 or later; or other Java-enabled browsers
- DHCP client
- Factory reset button

Physical & Environmental

Power Input

DC 5V, 2A

Through external power adapter

Dimensions

192 mm (W) x 118 mm (D) x 31 mm (H) (device only)

Weight

280 grams (device only)

Operating Temperature

0° to 55 °C (32° to 149 °F)

Storage Temperature

-20° to 75 °C (4° to 167 °F)

Humidity

95% maximum (non-condensing)

Emission (EMI)

- FCC Class B
- CE Class B
- C-Tick

Safety

CSA International



Ordering Information

DWL-7100AP 802.11a/g Wireless LAN Access Point

Please specify your model number as follows:

DWL-7100AP/BEU	For UK, Ireland
DWL-7100AP/EEU	For Denmark, Germany, Iceland, Finland, Netherlands, Norway, Sweden, Poland, Slovenia, Luxembourg, South Africa
DWL-7100AP/EFR	For France
DWL-7100AP/ALA	For Latin America (with US standard power adapter)
DWL-7100AP/ELA	For Latin America (with EU standard power adapter)
DWL-7100AP/NAU	For Australia
BDWL-7100AP	For USA (US packaging)
NDWL-7100AP	For China
DWL-7100AP/ESG	For Singapore
TDWL-7100AP	For Taiwan

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark and AirPremierAG is a trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A	TEL: 1-714-885-6000	FAX: 1-866-743-4905
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Benelux	TEL: 31-10-282-1445	FAX: 31-10-282-1331
Italy	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Norway	TEL: 47-22-309075	FAX: 47-22-309085
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
China	TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
India	TEL: 91-022-652-6696	FAX: 91-022-652-8914
Middle East (Dubai)	TEL: 9714-8834234	FAX: 9714-8834394
Turkey	TEL: 90-212-335-2553	FAX: 90-212-335-2500
Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
LatinAmerica	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-55039320	FAX: 55-11-55039321
South Africa	TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
Russia	TEL: 7-095-744-0099	FAX: 7-095-744-0099#350
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE
Rev. 01 (Mar. 2004)