



— DWL-900AP+

Wireless LAN Access Point with 22Mbps enhanced network speed and detachable antenna.

2.4GHz Enhanced Performance Wireless LAN Access Point

The D-Link AirPlus DWL-900AP+ is an Access Point that gives 2.4GHz wireless LAN users fast, secure access to an IEEE 802.11b wireless Local Area Network (LAN). With data transfer rates at up to 22Mbps, this Access Point provides twice the speed of other IEEE 802.11b Access Points, while adding a strong 256-bit security scheme for your data traveling on the wireless LAN. Strictly complying to industry standards, the DWL-900AP+ gives you the speed, security and other enhanced features without compromising interoperability with all 802.11b wireless LAN equipment and Ethernet-based networks.

Range Extension

The DWL-900AP+ Access Point connects the wireless LAN nodes (workstations, print servers, etc.) together via a 2.4GHz IEEE 802.11b wireless interface. It listens to all data traffic on all its interface and maintains a MAC address database. MAC address information is updated dynamically. When necessary, the DWL-900AP+ the Address Resolution Protocol (ARP) to match IP addresses to MAC addresses and stores ARP information in its database as well.

Access Control

Through an Access Control List that contains the MAC address of every wireless device, you can set up filters to prevent unauthorized access to network resources.

Efficiency Improvement

The DWL-900AP+ can discriminate based on the destination address of packets it handles by maintaining a list of disallowed destinations. This helps improve efficiency by eliminating unnecessary transmission of data packets.

Enhanced Speed Transmission

At 22Mbps, the DWL-900AP+ delivers high data transfer rate within the industry standard. This speed is double the 11Mbps normally found in other 2.4GHz wireless LAN Access Points.

Industry-standard Interoperability

The DWL-900AP+ delivers speeds without compromising compatibility. With both WiFi™ certification and IEEE 802.11b wireless LAN industry standard compliance, the DWL-900AP+ provides you with excellent network interoperability.

Network Security

Security is an issue when data is transmitted without the wires. In the air, transmitted data can be easily intercepted if not well protected by a security scheme. The DWL-900AP+ provides the necessary security, using the enhanced 64/128/256-bit industry-standard WEP (Wired Equivalent Privacy) encryption protocol. Data privacy mechanism is based on a shared key algorithm, as described in the wireless LAN standard.

Built-in DHCP Server

DHCP server function is built into this Access Point that automatically assign IP addresses to connected wireless nodes. This eliminates for you the need to install a separate DHCP server on the network.

Detachable Antenna

The DWL-900AP+ is equipped with an SMA reverse detachable dipole antenna with an effective range of 100 meters indoors, or 400 meters outdoors. Where a longer range is required, you can easily remove this antenna and replace it with a higher Gain antenna.

Features

- IEEE 802.11b DSSS 2.4GHz standard
- Up to 22Mbps enhanced data transfer rates
- 10/100Mbps auto-sensing Fast Ethernet port to bridge wireless LAN to Ethernet-based network
- Seamless roaming from cell to cell and Access Points
- 256-bit WEP data encryption
- Access control
- Built-in DHCP server
- Built-in AP-to-AP bridge, AP-to-multi-point bridge, wireless client bridge
- Detachable SMA reverse dipole antenna
- Web-based configuration & management with JavaScript

DWL-900AP+

Technical Specifications

2.4 GHz Wireless LAN Access Point

General

Standards

- IEEE 802.11b wireless LAN
- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet

Reception Sensitivity Nominal Temp Range

- 22Mbps: 10-5 BER @ -80 dBm minimum
- 11Mbps: 10-5 BER @ -79 dBm minimum
- 5.5Mbps: 10-5 BER @ -83 dBm minimum
- 1Mbps: 10-5 BER @ -89 dBm minimum

Frequency Range

- 2.4 - 2.4835 GHz

Modulation Techniques

- Direct Sequence Spread Spectrum (DSSS)
- Packet Binary Convolutional Coding (PBCC)

Data Rates

- 22 Mbps
- 11 Mbps
- 5.5 Mbps
- 2 Mbps
- 1 Mbps
- Auto fall-back

Data Rate & Modulation

- 22Mbps/8.5db: PBCC
- 11Mbps/4.5db: PBCC
- 11Mbps/8.5db: CCK
- 5.5Mbps/1.5db: PBCC
- 5.5Mbps/5.5db: CCK
- 2Mbps/3db: Barker

Operating Channels

- North America (FCC): 11
- Canada (DOC): 11
- Europe (ETSI): 13 (Except Spain and France)
- Japan (MKK): 14

Hardware

Wireless LAN to Ethernet Interface

Through RJ-45 10/100Mbps Fast Ethernet port

Antenna

Detachable 2dBi Gain antenna (reverse SMA connector)

Operating Range

- Up to 100 m (328 feet) indoors
- Up to 400 m (1,312 feet) outdoors

Diagnostic LEDs

- Power
- Link
- Tx/Rx

Software

Operating Modes

- Access Point
- Access Point to Access Point bridging
- Access Point to multi-point bridging
- Wireless client

Roaming

Among Access Points on the same subnet

Network Protocols Supported

- TCP/IP
- IPX/SPX
- NetBEUI
- ARP
- SNMP
- DHCP
- NDIS3
- NDIS4

IP Number Assignment

Automatic through built-in DHCP server

Security

- Data encryption: 64-bit, 128-bit, 256-bit WEP (Wired Equivalent Privacy)
- Connected node access control list

Configuration & Management

- Manage wireless LAN, network connection and client access control through web browser (Java Script supported)
- TFTP client for firmware upgrade
- Set IP session (ARP/ping)
- DHCP client (IP number self-assignment)

Physical & Environmental

Power Input

- DC 5V, 2.5A
- Uses external AC power adapter

Dimensions

142 x 145 x 32 mm
(5.59 x 5.71 x 1.26 inches)

Weight

288 grams (0.636 lb.)

Operating Temperature

0° - 55°C (32° - 131°F)

Storing Temperature

-20° - 65°C (-4° - 149°F)

Humidity

5% - 95%, non-condensing

EMI Certification

- FCC Class B
- CE Class B

Safety Certification

- UL 1950-3

Compatibility

Wi-Fi™

MBTF (Mean Time Between Failure)

> 30,000 hours



Ordering Information

IEEE 802.11b Wireless LAN Access Point DWL-900AP+ Wireless LAN Access Point

Please specify your model number as follows:

DWL-900AP+/ANA	Includes USA standard AC power adapter, North America frequency
DWL-900AP+/BEU	Includes U.K. standard AC power adapter, EU frequency
DWL-900AP+/EEU	Includes EU standard AC power adapter, EU frequency
DWL-900AP+/EFR	Includes EU standard AC power adapter, France frequency
DWL-900AP+/CN	Includes China standard AC power adapter, EU frequency
DWL-900AP+/NEU	Includes Australia standard AC power adapter, EU frequency
DWL-900AP+/UNA	Includes no AC power adapter, North America frequency

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A.	TEL: 1-949-788-0805	FAX: 1-949-753-7033
Canada	TEL: 1-905-829-5033	FAX: 1-905-829-5095
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511
U.K.	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511
Germany	TEL: 49-61-96779900	FAX: 49-61-967799300
France	TEL: 33-1-30.23.86.88	FAX: 33-1-30.23.86.89
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723
Iberia	TEL: 34-93-4965751	FAX: 34-93-4965701
Sweden	TEL: 46-(0)8-564-61900	FAX: 46-(0)8-564-61901
Norway	TEL: 47-22-991890	FAX: 47-22-207039
Denmark	TEL: 45-43-96.90.40	FAX: 45-43-42.43.47
Finland	TEL: 358-9-622-91660	FAX: 358-9-622-91661
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-9417-7100	FAX: 61-2-9417-1077
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
China	TEL: 86-10-88097777	FAX: 86-10-88096789
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914
Middle East	TEL: 202-2456176	FAX: 202-2456192
South America	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
South Africa	TEL: 27(0)126652165	FAX: 27(0)126652186
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE
Rev. 01 (Jun 2002)
Printed in Taiwan

