



— DSL-502T

ADSL Router for Home/SOHO

With Additional USB Port

The DSL-502T is an ADSL Router designed for home and the small office. This router lets you quickly and easily connect to high-speed broadband Internet and share your ADSL line. With a built-in ADSL interface supporting download speeds of up to 24Mbps, an additional USB port and advanced router functions, this device gives your home and business a convenient and cost-effective way to install a secure, fast network with bottleneck-free link to the outside world.

High-Speed Broadband Internet Connection

With this router, you can easily connect to your ADSL broadband line for Internet access in your office or at home. This device automatically creates an IP number and assigns for each user, simplifying everyone's logon operation.

Network Security

The router provides NAT protection for your office and home users from any Internet intruders and hackers, plus VPN pass-through for extra security. It also blocks and redirects certain ports to limit the services that outside users can access your network. Virtual server mapping is used to re-task services to multiple servers. This router can be set to

allow separate FTP, Web, and Multiplayer game servers to share the same Internet-visible IP address while still protecting your servers and workstations from hackers.

DMZ Host to Open Public Domain

The router supports constricted DMZ to redirect unknown packets to a dedicated server/PC behind the router, enabling a client (such as a Web server) to fully expose it to the Internet and ensure complete Internet application compatibility. This allows you to set up web sites and e-commerce business from your office while maintaining protection for the rest of your office LAN.

Standards & Features

- High-speed Internet access
- ADSL line Internet sharing
- Built-in ADSL interface with widest range of DSLAM interoperability
- ADSL: G.992.1 G.dmt, G.992.2 G.lite, ANSI T1.413 issue 2 (full rate DMT over analog POTS) Annex A
- ADSL2: G.992.3 (G.dmt.bis) Annex A
- ADSL2+: G.992.5 Annex A
- G.994.1 G.hs auto-negotiation of different ADSL flavors
- 1 10/100BASE-TX LAN port, 1 USB 1.1 port for connection to a workstation
- Virtual Private Network (VPN) pass-through support
- DMZ and Virtual Server Mapping support
- Firewall with Stateful Packet Inspection (SPI) function
- Web-based configuration

DSL-502T

Technical Specifications

ADSL Router

Router

LAN/Computer Interface

- RJ-45 10/100BASE-TX Fast Ethernet LAN port
- USB 1.1 port

Routed Packet Type

IP packets

Routing Protocols & Methods

- RIP v1/v2 and static routing
- Dynamic routing

DHCP Support

- DHCP server (for automatic IP assignment)
- DHCP Client

Security

- VPN support: PPTP/L2TP/IPSec pass-through
- Network Address/Port translation (NAPT)
- Authentication: PAP and CHAP
- DoS (UDP/TCP), detection of known attacks
- SPI firewall
- Web login password authentication

Configuration & Network Management

- HTTP server for web-based management
- Remote management through Telnet or HTTP
- System logs
- Support UPnP 1.0
- Configuration backup and restore
- Factory reset

Statistics Monitoring

Ethernet, ATM and ADSL statistics

Diagnostic LEDs

- Power
- Status
- ADSL Link/Act
- Ethernet Link/Act
- USB Link/Act

Built-in ADSL Modem

Standards

- ADSL standards: ANSI T1.413 Issue 2, ITU G.992.1 (G.dmt) Annex A, ITU G.992.2 (G.lite) Annex A
- ADSL2 standards: ITU G.992.3 (G.dmt.bis) Annex A, ITU G.992.4 (G.lite.bis) Annex A
- ADSL2+ standards: ITU G.992.5 Annex A
- Auto-handshake: ITU G.994.1 (G.hs)

Data Rates

- G.dmt: 8Mbps downstream, 832Kbps upstream
- G.lite: 1.5Mbps downstream, 512Kbps upstream
- ADSL2: 12Mbps downstream, 1Mbps upstream
- ADSL2+: 24Mbps downstream, 1Mbps upstream

ATM/ADSL

- ATM signaling ATM Forum UNI3.1/4.0
- OAM support F4/F5 Loopback
- ATM traffic Shaping: UBR, CBR, VBR

Bridged/PPP Support

- Bridged Ethernet over ATM
- Classical IP over ATM
- PPP over ATM
- PPP over Ethernet

Physical & Environmental

Power Input

Through 9VAC 1A external power adapter

Dimensions

142 x 117 x 31 mm

Weight

202 grams

Operating Temperature

0° to 40 °C

Storage Temperature

-20° to 70 °C

Operating Humidity

5% to 95% non-condensing

Emission (EMC/EMI)

- FCC Part 15 Class B
- CE Class B (EN55022)

Safety

CSA International (CSA950, EN60950, IEC60950, UL1950)



Ordering Information

ADSL Router DSL-502T

1 RJ-11 ADSL port
1 RJ-45 10/100BASE-TX LAN port
1 USB 1.1 port

To select the router with built-in ADSL modem that works best with your service provider, please consult your nearest D-Link representative or distributor/reseller.



Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A.	TEL: 1-800-326-1688	FAX: 1-866-743-4905
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223
Europe (U. K.)	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Norway	TEL: 47-99-300-100	FAX: 47-22-309580
Finland	TEL: 358-9-2707 5080	FAX: 358-9-2707-5081
Spain	TEL: 34-93-4090770	FAX: 34-93-4910795
Portugal	TEL: 351-21-8688493	
Czech Republic	TEL: 420-(603)-276-589	
Switzerland	TEL: 41-(0)-1-832-11-000	FAX: 41(0)-1-832-11-01
Greece	TEL: 30-210-9914 512	FAX: 30-210-9916902
Luxemburg	TEL: 32-(0)2-517-7111	FAX: 32-(0)2-517-6500
Poland	TEL: 48-(0)-22-583-92-75	FAX: 48-(0)-22-583-92-76
Hungary	TEL: 36-(0)-1-461-30-00	FAX: 36-(0)-1-461-30-09
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
India	TEL: 91-022-26526696	FAX: 91-022-26528914
Middle East (Dubai)	TEL: 971-4-3916480	FAX: 971-4-3908881
Turkey	TEL: 90-212-289-56-59	FAX: 90-212-289-76-06
Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
LatinAmerica	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brazil	TEL: 55-11-218-59300	FAX: 55-11-218-59322
South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Russia	TEL: 7-095-744-0099	FAX: 7-095-744-0099 #350
China	TEL: 86-10-58635800	FAX: 86-10-58635799
Taiwan	TEL: 886-2-6600-0123	FAX: 886-2-6600-1188
Headquarters	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299