## **D-Link**®

# AX3000 Wi-Fi 6 Travel Router

# **DBR-330**

### **Key Features**

- Compact, lightweight, and designed for easy portability wherever you go
- Built-in Wi-Fi 6 AX3000 mobile hotspot delivers high-speed, highperformance Wi-Fi to all your connected devices
- Supports multiple methods for sharing Internet connectivity, including routing, Wireless Internet Service Provider (WISP), and 4G/5G hotspot
- USB Type-A port connects to cellular adapters and storage devices
- · VPN for convenient, secure remote access
- · Support web-based file sharing
- USB Type-C connector for fast charging with USB PD





### **User Benefits**



#### **Versatility for Stable Connection**

Supports multiple Internet connection methods to achieve high availability of connectivity



#### Secure Remote Access

Access resources at a remote corporate or branch office conveniently and securely over the Internet using VPN



#### **Storage Capacity Expansion**

Support microSD/TF Card Slot to expand the storage capacity flexibly



#### Join N' Share File Sharing

Share files on the USB drive and microSD card across multiple operating systems for collaborative projects



#### Auto LAN/WAN Port

High-speed wired local and Internet connectivity with the ability to switch automatically between the two depending on the configured mode



#### **Best Partner for Smart Life**

Enjoy the convenience of mobile Internet and the power of Wi-Fi 6 on all your connected devices at home or on the go

## **Technical Specifications**

General	
Device Interfaces	1 x Gigabit Ethernet LAN/WAN port (auto-switch between LAN and WAN) 1 x USB Type-C with Power Delivery (PD) for power input 1 x USB Type-A 1 x microSD/TF card slot (CLASS 6 / CLASS 10 / UHS- I) 1 x Reset button
LEDs	Power, Status
IEEE Standards <sup>1</sup>	IEEE 802.11ax/ac/n/g/b IEEE 802.3u/ab
Wi-Fi Data Rates¹	3000 Mbps (5 GHz up to 2403 Mbps / 2.4 GHz up to 574 Mbps)
Internet Connectivity	Cellular WAN (compatible with D-Link DWM-222W & D501 only) Ethernet WAN: Static IP, Dynamic IP, PPPoE, PPTP, L2TP, DS-Lite, 802.1p & 802.1q VLAN Tagging and Priority Bit Wireless Internet Service Provider (WISP)
Antenna Type	2 x Wi-Fi 2.4 GHz internal antennas 3 x Wi-Fi 5 GHz internal antennas
Functionality	
Security Protocol	• WPA/WPA2 – Personal • WPA2 – Personal • WPA2/WPA3 - Personal • WPA3 - Personal
File Sharing	Join N' Share (Web-based file sharing function)
Firewall	Stateful Packet Inspection (SPI), Anti-spoofing checking, IP Address Filtering, 1 x DMZ
Software	
Device Management	Web UI
Physical	
Dimensions	120 x 82 x 23.5 mm
Weight	122 g
Power Input <sup>2</sup>	USB Type-C 12 V / 3 A
Operating Temperature	0 to 40 °C
Storage Temperature	-20 to 65° C
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Certifications	CE FCC IC
Package Contents	
DBR-330	AX3000 Wi-Fi 6 Travel Router USB-C to USB-C Charging Cable RJ45 Ethernet Cable

 $<sup>1.</sup> Maximum \ wireless \ signal \ rate \ derived from \ IEEE \ standard \ 802.11ax/ac/n/g/b \ specifications. \ Actual \ data \ throughput \ will \ vary. \ Network \ conditions \ and \ environmental \ factors,$ including volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate. Environmental factors may adversely affect



<sup>2.</sup> We recommend using D-Link DPP series power bank (DPP-201) and DCP series GaN charger (DCP-101 & DCP-651) to supply power to the device.