

# 5-in-1 USB-C Hub

**DUP-501**

## Key Features

- All-in-one USB-C Hub to satisfy your every need of on-the-go connectivity: storage, peripherals, and display
- File transfers without waiting – USB 3.0 offers speeds up to 5 Gbps<sup>1</sup>
- Vivid display for presentation and entertainment – HDMI output supports wired HDMI with 3840x2160@60 Hz and wireless HDMI with 1920x1080@60 Hz
- The front button switches between wired and wireless HDMI display modes
- Up to PD 100W power pass-through to charge your laptop and power the connected peripherals when used with a USB-C power adapter
- Plug & Play - no driver installation required. Simply plug in and you are ready to go
- Wireless HDMI operates on the 5 GHz band with less congestion



## User Benefits



### Integrated Connectivity

Versatile connectors combined with wireless HDMI provide both wired and wireless connectivity to achieve seamless flexibility



### Improved Work Efficiency

The hub connects to a variety of peripherals and gadgets to optimize your workspace



### Pass-through Charging

The PD port supports rapid charging with a capacity of up to 100W, ensuring the connected devices always stay powered



### Backwards Compatible

The USB and HDMI ports are fully compatible with any legacy devices that support older generations



### Keep Your Desk Organized

The all-in-one hub can be connected at the front and rear to accommodate any PC or laptop design to keep your desk uncluttered



### Easy yet Powerful

No driver installation is required with plug and play – USB 3.0 offers high-speed data transfer while HDMI 2.0 delivers lifelike images



### Reliable & Stable

Wireless transmission of HDMI signals on the 5 GHz band with much lower interference than the 2.4 GHz band for clearer visuals wherever you need it



### Best On-the-Go Partner

Simplify your workspace while enhancing communication with superior connection speed and transmission quality, whether you're in the office, at home, or on the go

# Technical Specifications

## General

<b>USB-C Hub Interfaces<sup>1,3</sup></b>	<b>Video Port:</b> <ul style="list-style-type: none"> <li>1 x wired HDMI 2.0 (3840x2160@60 Hz)</li> </ul>
	<b>USB Ports:</b> <ul style="list-style-type: none"> <li>2 x USB 3.0 Type-C: 5 Gbps</li> <li>1 x USB 3.0 Type-A: 5 Gbps</li> </ul>
	<b>PD-in Port:</b> <ul style="list-style-type: none"> <li>USB Type-C: supports USB Power Delivery (PD 3.0) 100W power pass-through for fast charge</li> </ul>
	<b>Button:</b> <ul style="list-style-type: none"> <li>Switch between wired and wireless HDMI mode</li> </ul>
	<b>Host Connector:</b> <ul style="list-style-type: none"> <li>USB 3.1 Type-C with cable: 10 Gbps with USB Power Delivery (PD 3.0) 85W for fast charge</li> </ul>
	<b>Wireless HDMI Receiver Interfaces</b> <ul style="list-style-type: none"> <li>1 x HDMI 1.2 (1920x1080@60 Hz)</li> <li>Transmission distance limit: 30 m</li> <li>1 x USB-A: requires power of 5V@1A</li> </ul>
Display Resolution <sup>2</sup>	<ul style="list-style-type: none"> <li>HDMI 2.0: 4K (3840x2160@60 Hz) for wired HDMI and 1920x1080@60 Hz for wireless HDMI</li> </ul>
LED	<ul style="list-style-type: none"> <li>Green: Power on, Hub Mode</li> <li>Green: Power on, Wired HDMI Mode</li> <li>White: Power on, Wireless HDMI Mode</li> </ul>
<b>Compatibility<sup>4</sup></b>	
Supported Devices/Systems	PCs and tablets equipped with a USB Type-C port that supports DisplayPort Alt Mode and Power Delivery and installed with the following operating systems: macOS, Windows 11, Windows 10, ChromeOS, and iPadOS
<b>Physical</b>	
Dimensions	<b>USB-C Hub:</b> 90 x 55 x 15 mm (3.54 x 2.17 x 0.59 in) <b>Wireless HDMI Receiver:</b> 27.5 x 18.5 x 10 mm (1.08 x 0.73 x 0.39 in)
Weight	<b>USB-C Hub:</b> 61.5 g (2.17 oz) <b>Wireless HDMI Receiver:</b> 22.3 g (0.79 oz)
Operating Temperature	0 to 40 °C (32 to 104 °F)
Storage Temperature	-20 to 65 °C (-4 to 149 °F)
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Certifications	FCC CE HDMI
<b>Package Contents</b>	
DUP-501	5-in-1 USB-C Hub Quick Installation Guide Warranty Card

1. Backward compatible with previous USB versions.
2. Resolutions based on DP 1.4 of the input signal of the connected device. If the input signal of the connected device is compatible with DP 1.2 graphics on Windows, only 4K (3840x2160@30 Hz) can be supported as the max resolution.
3. Incompatible with TEAMGROUP MP44 M.2 PCIe 4.0 SSD (TM8FPW008TC101)
4. The compatibility list is based on laboratory test results. Actual performance is not guaranteed and may vary by use, configuration, device conditions and other related environmental factors.
5. Actual performance may vary due to settings, cabling, temperature, network configuration, interface, device compatibility, environmental and on-site conditions, and other similar factors. References to power capability, signal or processing speed, signal range or distance, data encryption, storage capacity, display properties, or other performance metrics are based on optimal conditions derived from industry standards and provided for informational purposes only.
6. Specifications may be subject to change without prior notice.