



— DWL-G520

Wireless 108 G PCI Card

The D-Link AirPlusXtremeG™ DWL-G520 Wireless 108 G PCI card is an enhanced 802.11g high-performance, wireless card for desktop computers. This card supports high-speed wireless networking of up to 108Mbps Turbo mode, while providing seamless interoperability with all existing 802.11b wireless equipment. Together with better security, this card is the ideal wireless solution that offers an upgrade to a fast, new technology while protecting your past investments through interoperability with your current network equipment.

Up to 108Mbps Transmission Speed

Unlike most wireless cards, the DWL-G520 provides speeds of up to 108Mbps Turbo mode when used with other D-Link AirPlusXtremeG and other 802.11g products. This compares favorably with 802.11b adapters that offer 11Mbps speed.

This enhanced speed and adoption of 2.4GHz frequency, now available for public use in most countries, plus the mobility and convenience inherent in a wireless LAN, make this card an ideal solution for bandwidth intensive WLAN applications.

Compatible With 802.11b

Like the 802.11b adapters, the DWL-G520 uses a single 2.4GHz wireless frequency, eliminating the complexity of dualband networking. 802.11g's compatibility with existing wireless LAN standards means that you do not need to change your entire network to maintain connectivity.

Easy Migration to Higher Bandwidth

By maintaining compatibility with your existing wireless network equipment, this adapter lets you upgrade to a higher speed at the pace you want. The DWL-G520 and other 802.11g standard devices can be gradually added to your network, while the rest of your older network remains perfectly connected.

Wi-Fi™ Protected Access

Wi-Fi™ Protected Access is provided to authorize and identify users based on a secret key that changes automatically at a regular interval. Used in conjunction with a RADIUS server, WPA uses TKIP (Temporal Key Integrity Protocol) to change the temporal key every 10,000 packets. This insures much greater security than the standard WEP security, which requires the keys to be changed manually.

802.1x Authentication

The DWL-G520 supports 802.1x authentication for protection against network intrusion. Used in conjunction with a RADIUS server, this function provides a means to verify the identity of the client before an access to the network is granted.

Pre-Shared Key

This function brings a lot of convenience (when used in conjunction with other 802.11g products) for users that do not incorporate a RADIUS server in their networks. Utilizing the Pre Shared Key mode of WPA, the DWL-G520 will obtain a new security key every time it connects to the 802.11g network. You only need to input your encryption information once in the configuration menu. With the DWL-G520, you will automatically receive a new key every time you connect, doing away with the inconvenience of manual WEP key input.

Features

- 802.11g industry standard
- Uses popular 2.4GHz frequency band
- Up to 108Mbps Turbo mode network throughput 15 times faster than 802.11b
- Strong 64/128/152-bit WEP data encryption security
- Compatible with existing 802.11b wireless devices
- Advanced security with WPA EAP/PSK, WPA2 EAP/PSK, TKIP, AES Support
- Powerful integrated antenna provides 100-meter indoors, 400-meter operation range *
- Easy configuration, plug-and-play installation
- Runs Windows 98SE, 2000, ME, XP

* Environmental factor may adversely affect operation range.

DWL-G520

Technical Specifications

2.4 GHz Wireless LAN

Standards

- 802.11g wireless LAN
- PCI 2.3

Media Access Control Protocol

CSMA/CA with ACK

Network Architecture Types

- Ad-Hoc mode
- Infrastructure mode

Frequency Range

2.4 - 2.4835 GHz

Operating Channels

- US (FCC): 11
- Europe (ETSI): 13
- Canada (DOC): 11

Network Transfer Rate/Modulation Technique

- 802.11b:
 - 11Mbps, 5.5Mbps: CCK
 - 2Mbps: DQPSK
 - 1Mbps: DBPSK
- 802.11g:
 - 54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps, 6Mbps: OFDM (Orthogonal Frequency Division Multiplexing)

Receive Sensitivity (for 802.11b)

- 1Mbps: -92dBm
- 2Mbps: -88dBm
- 5.5Mbps: -86dBm
- 11Mbps: -84dBm

Receive Sensitivity (for 802.11g)

- 6Mbps: -88dBm
- 9Mbps: -85dBm
- 12Mbps: -85dBm
- 18Mbps: -81dBm
- 24Mbps: -77dBm
- 36Mbps: -73dBm
- 48Mbps: -71dBm
- 54Mbps: -70dBm

Transmit Output Power (for 802.11b)

1Mbps, 2Mbps, 5.5Mbps, 11Mbps: 16dBm to 18dBm

Transmit Output Power (for 802.11g)

- 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps: 16dBm to 18dBm
- 36Mbps: 15dBm to 17dBm
- 48Mbps: 14dBm to 16dBm
- 54Mbps, 108Mbps: 13dBm to 15dBm

Antenna

External dipole antenna with detachable reverse SMA connector

Operation Range

- Indoors: up to 100 meters (328 feet)*
- Outdoors: up to 400 meters (1,312 feet)*

* Environmental factors may adversely affect range

Security

- 64/128/152-bit WEP data encryption
- WPA EAP/PSK, WPA2 EAP/PSK
- TKIP, AES support

Physical & Environmental

Diagnostic LEDs

- Link
- Activity

Operating Voltage

3.3V

Power Consumption

- Transmit mode: 248 mA
- Power save mode: 28 mA
- Standby mode: 4.66 mA

Dimensions

114 (L) x 54 (W) x 8.7 (H) mm
(4.64 x 2.13 x 0.34 inches)

Weight

55 grams (0.12 lb.)

Operating Temperature

0° - 55°C (32° - 149°F)

Storage Temperature

-20° - 65°C (-4° - 149°F)

Humidity

Up to 95% non-condensing

Emission (EMI)

- FCC Class B
- CE Class B
- R&TTE

OS Support

- Windows 98SE, ME, 2000, XP
- Linux



Ordering Information

DWL-G520 802.11g Wireless LAN PCI Card

Please specify your order as follows:

DWL-G520/NA	North America frequency
DWL-G520/EU	EU frequency
DWL-G520/CN	EU frequency (packaging for China)

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademarks and AirPlus Xtreme G is a trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A	TEL: 1-714-885-6000	FAX: 1-866-743-4905
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500
Italy	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Norway	TEL: 47-23-897189	FAX: 47-22-309085
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
China	TEL: 86-10-5863-5800	FAX: 86-10-5863-5799
India	TEL: 91-022-2652-6696	FAX: 91-022-2652-8914
Middle East (Dubai)	TEL: 9714-3916480	FAX: 9714-3908881
Turkey	TEL: 90-212-335-2553	FAX: 90-212-335-2500
Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Latin America	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-55039320	FAX: 55-11-55039322
South Africa	TEL: 27-1266-52165	FAX: 27-1266-52186
Russia	TEL: 7-095-744-0099	FAX: 7-095-744-0099#350
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299