



Internet Camera Outdoor Enclosures

Outdoor Protection for Surveillance Cameras

- Water Resistance/Dust-Proof Protection
- Heater/Blower for Protection Against Heat/Cold Temperature
- Built-in Power Supply for Easy Cable Management
- Angle-Adjustable Mounting Brackets
- Vertical or Horizontal Installation

The D-Link SecuriCam Internet camera outdoor enclosures provide a cost-effective solution for protecting your D-Link Internet Camera from the rigors of outdoor use. The fixed-type enclosures include heavy-duty, angle-adjustable mounting brackets that can be used to secure the camera on a vertical or horizontal surface. These enclosures maximize the full potential of your D-Link Internet cameras to secure and protect your home and business.

DCS-45 Thermal Barrier Design With Flip Open Top

The DCS-45 includes a thermal barrier design to withstand temperature fluctuations and a flip open top for easy installation.



Supported Devices

- DCS-2000
- DCS-3220

Dimensions

360 (L) x 140 (D) mm (14.2 x 5.5 inches)

Weight

1.48 kg (3.26 lb)

Material

Aluminum Housing with Steel Bracket

Color

Light Gray Powder Coating

DCS-50 IP66 Certified With Built-In Power Supply

The DCS-50 features IP66 certification for water resistance and dust-proof operation. This model includes a built-in power supply for easy cable management.



Supported Devices

- DCS-2000
- DCS-3220

Power Supply

90 to 264V AC Input, 12V DC, 3A Output

Dimensions

390 (L) x 127 (W) x 124 (H) mm (15.4 x 5 x 4.9 inches)

Weight

3.05 kg (6.72 lb)

Material

Aluminum Housing

Color

White

DCS-60 IP44 Certified With Built-In Power Supply, Heater and Blower

The DCS-60 features IP44 certification for water resistance and dust-proof operation. This model includes a heater and blower for camera operation in a wider range of temperature-sensitive environments. The built-in power supply simplifies the installation procedure.



Supported Devices

- DCS-2000
- DCS-3220

Power Supply

90 to 264V AC Input, 12V DC, 3A Output

Heater

On at 18°C (64°F), Off at 28°C (82° F)

Blower

On at 35°C (95°F), Off at 25°C (77°F)

Dimensions

450 (L) x 135 (W) x 140 mm (H) (17.7 x 5.3 x 5.5 inches)

Weight

4.3 kg (9.47 lb)

Material

Aluminum Housing

Color

White

DCS-70 Dome Type, IP66 Certified With Built-In Power Supply, Heater and Blower

The DCS-70 is a dome-type enclosure and is designed for use with D-Link's motorized pan and tilt cameras. This IP66 certified enclosure protects your camera against dust and heavy jets of water. Camera installation is simplified with the built-in power supply, while the heater and blower keeps your camera in proper operating temperatures.



Supported Devices

- DCS-5300
- DCS-6620

Power Supply

100 to 240V AC Input, 12V DC, 5A Output

Heater

On at 0°C (32°F), Off at 10°C (50°F)

Blower

On at 40°C (104°F), Off at 30°C (86°F)

Dimensions

225 (H) x 218 (D) mm (8.86 x 8.58 inches)

Weight

3.4 kg (7.27 lb)

Material

Aluminum Housing with Smoked Acrylic Cover

Color

Beige

D-Link Worldwide Offices

U.S.A.	TEL: 1-800-326-1688	FAX: 1-866-743-4905	Luxemburg	TEL: 32-(0)2-517-7111	FAX: 32-(0)2-517-6500
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223	Poland	TEL: 48-(0)-22-583-92-75	FAX: 48-(0)-22-583-92-76
Europe (U. K.)	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511	Hungary	TEL: 36-(0)-1-461-30-00	FAX: 36-(0)-1-461-30-09
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300	Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
France	TEL: 33-1-30238688	FAX: 33-1-30238689	Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331	India	TEL: 91-022-26526696	FAX: 91-022-26528914
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500	Middle East (Dubai)	TEL: 971-4-3916480	FAX: 971-4-3908881
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	Turkey	TEL: 90-212-289-56-59	FAX: 90-212-289-76-06
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901	Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Norway	TEL: 47-99-300-100	FAX: 47-22-309580	LatinAmerica	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Finland	TEL: 358-9-2707 5080	FAX: 358-9-2707-5081	Brazil	TEL: 55-11-218-59300	FAX: 55-11-218-59322
Spain	TEL: 34-93-4090770	FAX: 34-93-4910795	South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Portugal	TEL: 351-21-8688493		Russia	TEL: 7-095-744-0099	FAX: 7-095-744-0099 #350
Czech Republic	TEL: 420-(603)-276-589	FAX: 41(0)-1-832-11-01	China	TEL: 86-10-58635800	FAX: 86-10-58635799
Switzerland	TEL: 41-(0)-1-832-11-00	FAX: 30-210-9916902	Taiwan	TEL: 886-2-6600-0123	FAX: 886-2-6600-1188
Greece	TEL: 30-210-9914 512		Headquarters	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299