

# 65W GaN Charger

**DCP-651**

## Key Features

- Ensure your devices stay charged while you're on the go with a reliable and efficient charging block
- The 65W charging capability includes one USB Type-C port that delivers up to 65W of charging power
- GaN technology facilitates powerful, efficient, and safe charging with comprehensive safety protection
- A compact and convenient multi-port charging block designed to power a variety of devices while minimising heat buildup
- The USB connectors support a wide range of power outputs, with various maximum capacities
- Designed with advanced protection features: overcurrent, overvoltage, overtemperature, overcharge, and short circuit protection
- USB Power Delivery (PD) 3.0 and Quick Charge (QC) 4.0 for fast charging
- Interchangeable power plugs for AU, EU, UK, and US to ensure smooth charging experience when you travel



## User Benefits



### Supercharged Productivity

GaN technology enables efficient and reliable charging for up to 3 devices simultaneously, ensuring you stay productive and connected wherever you are



### Fast Charging

Power your personal devices and gadgets with fast charging capabilities, thanks to standardized charging technologies



### Ultra-compact & Portable

With its sleek, rounded edge design, you can easily toss it into your bag without worrying about scratching other items



### Power Efficiency with Safety Protection

GaN technology and multifold protection enhance safety and energy efficiency, reducing electricity costs and extending product lifespan



### Universal Support

The interchangeable power plugs make it ideal for travel and remote work, capable of charging devices ranging from laptops to phones and tablets



### Best On-the-Go Partner

Satisfy your portable charging needs by charging smart and portable accessories safely and efficiently – all at the same time

# Technical Specifications

General	
Power Input	100AC-240 V AC (MIN: 90 V, MAX: 264 V) Rated frequency: 50/60Hz Rated Input Current: Max 1.5A@100-240 V input & Full load
Output Interfaces	<ul style="list-style-type: none"><li>When only one charging port is used<ul style="list-style-type: none"><li>USB Type-C1 or C2<ul style="list-style-type: none"><li>Output: 5.0V@3.0A, 9.0V@3.0A, 12.0V@3.0A, 15.0V@3.0A, 20.0V@3.25A   MAX 65W</li></ul></li><li>USB Type-A<ul style="list-style-type: none"><li>Output: 4.5V@5.0A, 5.0V@4.5A, 5.0V@3A   MAX 22.5W</li></ul></li></ul></li><li>When more than one charging port is used<ul style="list-style-type: none"><li>USB Type-C1 &amp; C2: 45.0W &amp; 20.0W</li><li>USB Type-C1 &amp; USB Type-A: 45.0W &amp; 18.0W</li><li>USB Type-C2 &amp; USB Type-A: Total 15.0W</li><li>USB Type-C1 &amp; (USB Type-C2 &amp; USB Type-A): 45.0W &amp; Total 15.0W</li></ul></li><li>Maximum Total Output: 65W</li></ul>
Protection	<ul style="list-style-type: none"><li>Overcurrent protection</li><li>Overvoltage protection</li><li>Overcharge protection</li><li>Overtemperature protection</li><li>Short circuit protection</li></ul>
Physical	
Dimensions	44.4 x 29.4 x 63 mm
Power Input	MAX 1.5A@100-240 V
Weight	194 g
Operating Temperature	0 to 40 °C
Storage Temperature	-20 to 80 °C
Operating Humidity	10% to 100% non-condensing
Storage Humidity	30% to 100% non-condensing
Certifications	CE, FCC
Package Contents	
DCP-651	65W GaN Charger Interchangeable AC Plug (US, UK, EU and AU) Quick Installation Guide Warranty Card

