

2K Pan & Tilt Wi-Fi Camera

DCS-6501LH

Smarter Camera, Safer Home

- 2K resolution
- Supports 802.11ax Wi-Fi connectivity
- Built-in Bluetooth Low Energy 5.2 technology for faster setup
- WPA3™ and TLS encryption for enhanced protection
- IR night vision lets you see up to 8M (26 ft.) in total darkness
- Two-way audio with built-in microphone and speaker
- Sound and motion detection
- Continuous recording¹ to local microSD²
- Access anytime, anywhere with the free mydlink app³
- Voice control works with Amazon Alexa or Google Assistant




2K Quality

True 2K 1296p resolution for superior live video clarity



Wi-Fi 6 Connectivity

Wi-Fi 6 delivers stable, reliable connectivity for prompt access to live feeds and alerts



Panorama View Angle Selection

See the camera's range of view and tap to jump to a specific area



Sound & Motion Detect icon

Receive instant notifications via app when triggered



Auto Motion Tracking

Automatic pan/tilt to follow an object as it moves



Two-Way Audio

Transmit and receive audio with built-in microphone and speaker



Day & Night

See clearly up to 8 meters, even in complete darkness



Cloud Recording

Conveniently record to the cloud and view from anywhere

| Camera | | |
|------------------------|--|--|
| Hardware Profile | <ul style="list-style-type: none"> • 1/2.7" Progressive CMOS sensor • 8 m (26 ft) IR illumination distance • Infrared-Cut Removable (ICR) Filter module • Focal length 3.6 mm • Aperture F2.4 | <ul style="list-style-type: none"> • Angle of view (16:9): <ul style="list-style-type: none"> • Horizontal: 89° • Vertical: 48° • Diagonal: 107° • Built-in microphone and speaker |
| Video Resolution | Max. resolution: 1296p (2304 x 1296) | |
| Video Compression | H.264 | |
| Audio Codec | MPEG-2 AAC LC | |
| Image Features | Configurable image size | |
| Pan/Tilt | | |
| Pan Range | -175° to +180° (total 355°) | |
| Tilt Range | -90° to +90° (total 180°) | |
| Network | | |
| Connectivity | <ul style="list-style-type: none"> • 802.11b/g/n/ax (1T1R) • Wi-Fi operates on 2.4 GHz band | <ul style="list-style-type: none"> • Bluetooth Low Energy 5.2 |
| Network Protocols | IPv4 | |
| Security Protocol | WPA3 | |
| System Management | | |
| Event Management | <ul style="list-style-type: none"> • Push notifications • Motion detection • Sound detection | <ul style="list-style-type: none"> • microSD card recording (up to 128 GB capacity) • mydlink Cloud recording⁴ |
| Device Management | <ul style="list-style-type: none"> • mydlink app (iOS and Android) | <ul style="list-style-type: none"> • mydlink portal |
| Physical | | |
| Environment | For indoor use only | |
| Weight | 138 g (6.7 oz) | |
| Power Adapter | <ul style="list-style-type: none"> • Input: 100 to 240 V AC, 50/60 Hz | <ul style="list-style-type: none"> • Output: 5 V DC 1.0 A |
| Temperature | <ul style="list-style-type: none"> • Operating: 0 to 40 °C (32 to 104 °F) | <ul style="list-style-type: none"> • Storage: -20 to 70 °C (-4 to 158 °F) |
| Humidity | <ul style="list-style-type: none"> • Operating: Max. 90% non-condensing | <ul style="list-style-type: none"> • Storage: Mas. 90% non-condensing |
| Dimensions (L x W x H) | 85.96 x 85.96 x 114.3 mm (3.38 x 3.38 x 4.5 in) | |
| Certifications | <ul style="list-style-type: none"> • FCC | <ul style="list-style-type: none"> • CE |
| Hardware Version | C1 | |

¹ Use of audio or video equipment for recording the image or audio of a person without their knowledge and consent is prohibited in certain states or jurisdictions. The end-user assumes all liability for compliance with applicable state, local and federal laws.

² microSD card not included. Camera is compatible with microSD/SDHC/SDXC cards up to v3.01 with up to 128 GB of capacity.

³ Please refer to the app's store page to check whether your device is compatible.

⁴ Subscription required. Subscription and One Year Free Plan offer subject to Terms and Conditions, please visit the D-Link website for more details. D-Link reserves the right to amend Terms and Conditions without prior notice. Minimum recommended upload bandwidth of 2.5 Mbps for live viewing or 5 Mbps for cloud recording.

