# DCS-2802KT-EU Wire-Free Camera Kit





# **Product Highlights**



100% Wire-Free Battery-operated with onboard Wi-Fi



Advanced Motion Detection Receive notifications and record video clips when motion is detected



IP65 Indoor/Outdoor Weatherproof housing allows placement anywhere



The mydlink™ Pro DCS-2802KT-EU is a bundle consisting of two DCS-2800LH-EU Wire-Free Cameras and a DCS-H100 Hub which are ideal for Small Office/Home Office (SOHO) surveillance applications. The DCS-2800LH-EU is a compact wireless network battery camera suitable for day-time and night-time outdoor environments. It features built-in night vision, motion detection, and a free mobile app — so you can feel at ease when you're away from home.

### Compact Design, Simple Setup

The DCS-2802KT-EU is designed to be compact and unobstrusive, so it can fit in with any decor, no matter where you put it. You can stick it anywhere, indoors or out. It's water resistant so it can withstand outdoor weather. Setting up the cameras and hub are also a breeze with the free mydlinkTM app. To get started, simply install the app on your mobile device and with a few taps the app will guide you through the entire setup process.

### **Versatile Feature Set**

Despite its small size, the DCS-2802KT-EU has all the features you need for monitoring your home. Onboard Wi-Fi provides extended range and higher bandwidth for smooth 1080p Full HD video streams on any device. The DCS-H100 Hub together with the mydlink™ app supports two-way audio, simultaneous live viewing, recording, and playback¹ for up to four DCS-2800LH-EU cameras. The Hub has ports that allow you to record snapshots and video clips to a microSD² card or external HDD, and cloud storage5 is possible with mydlink™ app.

The DCS-2802KT-EU camera's built-in motion detection will automatically send motion alert notifications to your mobile device. Night-time monitoring is possible with the built-in infrared LED that allows for night-time viewing of up to 7.5 meters (25 feet), so you can relax knowing you have 24/7 monitoring of your home or small office. Each camera is powered by two powerful lithium batteries allowing its use for a long period of time without the need to charge it.

### Access Anywhere Using the Mobile App

With the mydlink<sup>™</sup> app, you have an easy and convenient way for you to look after your family or to monitor your home or office. Stay up-to-date with notifications and check in on those you love at any time. Access your camera using the mydlink<sup>™</sup> mobile app and you can view and manage your camera using your mobile device. You can interact with what you're watching with two-way audio. Enjoy instant control over your home surveillance with the ability to manually trigger video recording, no matter where you are.

### **Features**

**IFTTT** 

- High-quality 1080p Full HD resolution provides detailed snapshots and crisp video
- ♦ 135-degree viewing angle
- ♦ Stick it anywhere (indoor/outdoor)
- ♦ Weatherproof
- Long-lasting lithium batteries
- Built-in IR LEDs to capture video up to 7.5 meters (25 feet) away in complete darkness
- ♦ PIR Motion detection
- ♦ Pinch to zoom
- H.264 support for the best video streaming performance
- Receive notifications, and save snapshots and video clips to your mobile device
- View and manage your camera remotely through the mydlink<sup>™</sup> app<sup>3</sup>
- ◆ Save video clips to a microSD<sup>2</sup> card, external HDD, or cloud storage<sup>5</sup>
- ♦ Two-way audio
- ♦ AES128-encrypted video and audio streaming




### Automated Video Clip Storage Through mydlink™ Cloud Recording

recordings in the cloud or download video clips to your mobile device from anywhere, anytime through the Internet. Access real-time live views of your cameras using the mydlink mobile app and set automated schedules via your tablet or mobile phone, no matter where you are.

With a mydlink™ cloud recording subscription, you can have peace of mind with automated storage of your video recordings to a cloud server. Play back

Product Images DCS-2800LH-EU



## **Technical Specifications**

DCS-2800LH-EU

Camera		
Hardware Profile	<ul> <li>1/4" 2 megapixel progressive CMOS sensor</li> <li>Minimum illumination: <ul> <li>B/W (Night Mode), IR LEDs on: 0 lux</li> </ul> </li> <li>Lens focal length: 1.9 mm</li> <li>Aperture: F2.2</li> <li>Digital zoom</li> <li>7.5 m (25 ft) IR illumination distance</li> </ul>	<ul> <li>Angle of view (16:9):</li> <li>Horizontal: 115°</li> <li>Vertical: 64°</li> <li>Diagonal: 135°</li> <li>Built-in light sensor</li> <li>Built-in microphone</li> <li>Built-in speaker</li> </ul>
Video Compression	H.264 format compression	JPEG for still images
Video Resolution	• 1080p (1920 x 1080)	• Up to 24 fps
Audio Support	• MPEG-2 AAC LC	Two-way audio
Network		
Connectivity	• 2.4 GHz: 802.11n/g/b wireless with WPA2 encryption	• 866 MHz for signalling
General		
Buttons	Sync Button	
LED	• Status LED	
System Integration		
Event Management	<ul><li>PIR motion detection</li><li>Cloud recording</li><li>Push notifications</li></ul>	Manually taken snapshots & video clips are saved to mobile device
Mobile Support	<ul> <li>mydlink™ apps for iPhone, iPad, iPod touch, and Android devices⁴</li> </ul>	



Physical			
Environment	For Indoor/Outdoor Use		
IP Rating	• IP65		
Weight	• 240 grams (8.47 ounces) ± 5%		
Battery	• 23.5 Wh, 3.6 V total power	Lithium-ion	
Power Adapter	• Input: 100 to 240 V AC, 50/60 Hz	Output: 5 V DC 2 A (Micro-USB)	
Power Consumption	Standby state:     < 0.28 mW	Active state:     < 1,200 mW (Day mode)     < 1,880 mW (Night mode)	
Temperature	• Operating: -20 to 45 °C (-4 to 113 °F)	• Storage: -20 to 70 °C (-4 to 158 °F)	
Humidity	Operating: 10% to 95% non-condensing	Storage: 5% to 95% non-condensing	
Certifications	• CE	• CE LVD	
Dimensions (HxWxD)	• 85 x 66 x 85 mm (3.37 x 2.6 x 3.37 inches)		
Diagram	65.02	84.45	



### **Product Images**

DCS-H100

# Back View Sync Button Power/Network/Camera LEDs Internal Siren USB 2.0 Port Power Button Power Input

### **Technical Specifications** DCS-H100 Wireless Connectivity • 2.4 GHz: 802.11n/g/b wireless • 2x2 300 Mbps • 866 MHz for signalling **Network Protocols** • IPv4, ARP, TCP, UDP, ICMP • DNS client • IPv6 • DHCP Client Security • WPA2 encryption • 1 x USB 2.0 port<sup>2</sup> Ports • 1 x 10/100 Base-T LAN port • 1 x microSD slot<sup>2</sup> • Reset Button Buttons • Sync Button • Power Button LED • Power LED · Camera LED Network LED System Integration mydlink<sup>™</sup> apps for iPhone, iPad, iPod touch, and Mobile Support Android devices<sup>4</sup>



Physical		
Environment	For Indoor Use Only	
Weight	• 195 grams (6.88 ounces) ± 5%	
Power Adapter	• Input: 100 to 240 V AC, 50/60 Hz	Output: 12 V DC 1.5 A
Power Consumption	• 18 W maximum	
Temperature	• Operating: 0 to 40 °C (32 to 104 °F)	• Storage: -20 to 70 °C (-4 to 158 °F)
Humidity	Operating: 20% to 80% non-condensing	Storage: 5% to 95% non-condensing
Certifications	• CE	• CE LVD
Dimensions (LxWxH)	• 65 x 134 x 150 mm (2.56 x 5.28 x 5.91 inches)	
Diagram	134.00	64.05
Order Information		
Part Number	Description	
DCS-2802KT-EU	Wire-Free Camera Kit	

<sup>1</sup> Use of audio or video equipment for recording the image or audio of a person without their knowledge and consent is prohibited in certain states or jurisdictions. The end-user assumes all liability for compliance with applicable state, local and federal laws.
2 The DCS-H100 is compatible with microSD/SDHC/SDXC cards (not included) up to v3.01 and is not compatible with v4.x cards. Supports up to 128GB cards. Also supports one USB 2.0 HDD up to 2TB in capacity.
3 The DCS-2800LH-EU is not supported by the mydlink Home app and is not compatible with D-Link's Connected Home Series.
4 Check device app store for OS requirements.
5 Subscription required. 1 day of recordings for up to three cameras is free.

Updated 2019/5/9