



CLI Reference Guide

Product Model : DIS-700G-28XS
Industrial Layer 2+ Gigabit Managed Switch
with 10G SFP+ slots
Release 1.01

CONTENTS

1	SCOPE	10
1.1	SCOPE	10
1.2	AUDIENCE	10
1.3	PRE-REQUIRED KNOWLEDGE	10
1.4	ACCESS TO HARDWARE INTERFACE	10
1.5	RELATED DOCUMENTS	10
2	OPERATOR INTERFACE	12
2.1	INTRODUCTION	12
2.2	CONNECT INTERFACE	12
2.3	AUTHORIZATION LEVEL	12
2.4	LOGIN EXAMPLE	13
2.5	EXECUTION MODES	13
2.6	GETTING HELP	13
2.7	TERMINAL KEY FUNCTION	14
2.8	NOTATION CONVENTIONS	14
3	COMMANDS DESCRIPTIONS.....	16
3.1	INITIALIZE MODE COMMANDS	16
3.1.1	<i>bye</i>	16
3.1.2	<i>!</i>	16
3.1.3	<i>configure</i>	16
3.1.4	<i>enable</i>	16
3.1.5	<i>exit</i>	16
3.1.6	<i>list command-tree</i>	16
3.1.7	<i>list timezone</i>	16
3.1.8	<i>show env</i>	16
3.1.9	<i>show history</i>	17
3.1.10	<i>show time</i>	17
3.1.11	<i>show uptime</i>	17
3.1.12	<i>sleep</i>	17
3.2	ENABLE MODE COMMANDS	18
3.2.1	<i>bye</i>	18
3.2.2	<i>!</i>	18
3.2.3	<i>exit</i>	18
3.2.4	<i>configure</i>	18
3.2.5	<i>disable</i>	18
3.2.6	<i>kick</i>	18
3.2.7	<i>list alarm</i>	18
3.2.8	<i>list command-tree</i>	18
3.2.9	<i>list event</i>	18
3.2.10	<i>list execution-modes</i>	19
3.2.11	<i>list timezone</i>	19
3.2.12	<i>ping</i>	19
3.2.13	<i>show snmp</i>	19
3.2.14	<i>show account</i>	19
3.2.15	<i>show login-users</i>	19
3.2.16	<i>show syslog</i>	19
3.2.17	<i>show clisettings</i>	20
3.2.18	<i>show runningcfg</i>	20
3.2.19	<i>show runningcfg default</i>	20
3.2.20	<i>show firmware status</i>	20
3.2.21	<i>show firmware partition</i>	20
3.2.22	<i>show management</i>	20
3.2.23	<i>show route static</i>	20

3.2.24	<i>show runningcfg backup</i>	20
3.2.25	<i>show bootloader</i>	20
3.2.26	<i>show system information</i>	20
3.2.27	<i>show http</i>	20
3.2.28	<i>show temperature</i>	21
3.2.29	<i>show time</i>	21
3.2.30	<i>show version</i>	21
3.2.31	<i>show system inventory</i>	21
3.2.32	<i>show aging</i>	21
3.2.33	<i>show fdb</i>	21
3.2.34	<i>show fdb interface gigabit <portNo></i>	22
3.2.35	<i>show fdb vlan <vlanid></i>	22
3.2.36	<i>show fdbstatic</i>	22
3.2.37	<i>show fdbstatic interface gigabit <portNo></i>	22
3.2.38	<i>show fdbstatic vlan <vlanid></i>	22
3.2.39	<i>show interface gigabit <portNo></i>	22
3.2.40	<i>show interface gigabit <portNo> counter</i>	23
3.2.41	<i>show interface gigabit <portNo> stp</i>	23
3.2.42	<i>show interface gigabit <portNo> vlan</i>	23
3.2.43	<i>show jumboframe</i>	23
3.2.44	<i>show stp</i>	23
3.2.45	<i>show vlan</i>	23
3.2.46	<i>show vlan <vlanid></i>	23
3.2.47	<i>show cos-queue-mapping</i>	24
3.2.48	<i>show interface gigabit <portNo> qos</i>	24
3.2.49	<i>show policer</i>	24
3.2.50	<i>show profile acl {<number> all}</i>	24
3.2.51	<i>show interface gigabit <portNo> acl</i>	24
3.2.52	<i>show queue-scheduler profile</i>	24
3.2.53	<i>show queue-shaper</i>	24
3.2.54	<i>show port-shaper</i>	24
3.2.55	<i>show port-isolation</i>	25
3.2.56	<i>show interface gigabit <portNo> port-isolation</i>	25
3.2.57	<i>show interface gigabit <portNo> storm-control</i>	25
3.2.58	<i>show vlan {unknown-uc unknown-mc broadcast}</i>	25
3.2.59	<i>show port-mirror</i>	25
3.2.60	<i>show interface gigabit <portNo> rmon-counter</i>	25
3.2.61	<i>show interface vlan igmp</i>	26
3.2.62	<i>show multicast-fdb</i>	26
3.2.63	<i>show multicast-fdb static</i>	26
3.2.64	<i>show ring</i>	26
3.2.65	<i>show ssl decrypted</i>	26
3.2.66	<i>show ssl encrypted</i>	26
3.2.67	<i>show interface gigabit <portNo></i>	26
3.2.68	<i>show ext-tpid</i>	27
3.2.69	<i>show interface vlan</i>	27
3.2.70	<i>show interface vlan <vlanid></i>	27
3.2.71	<i>show protocol-vlan</i>	27
3.2.72	<i>show interface gigabit <portNo> vlan</i>	27
3.2.73	<i>show vlan-trans</i>	27
3.2.74	<i>show igmp-mvr-profile {<number> all}</i>	28
3.2.75	<i>show igmp-acl-profile {<number> all}</i>	28
3.2.76	<i>show interface gigabit <portNo> igmp</i>	28
3.2.77	<i>show interface vlan igmp</i>	28
3.2.78	<i>show interface vlan <vlanid> igmp</i>	28
3.2.79	<i>show multicast-fdb srclist</i>	28
3.2.80	<i>show multicast-fdb</i>	28
3.2.81	<i>show dot1x</i>	29
3.2.82	<i>show dot1x pae-info-status {<portNo> all}</i>	29
3.2.83	<i>show dot1x eapol-stats {<portNo> all}</i>	29
3.2.84	<i>show dot1x radius-stats</i>	29

3.2.85	<i>show http</i>	29
3.2.86	<i>show interface trunk-group</i>	29
3.2.87	<i>show fdb interface trunk-group <number></i>	29
3.2.88	<i>show fdb</i>	29
3.2.89	<i>show fdb vlan <vlanid></i>	30
3.2.90	<i>sleep</i>	30
3.2.91	<i>system restart</i>	30
3.2.92	<i>system stop</i>	30
3.2.93	<i>telnet <ip></i>	30
3.2.94	<i>traceroute <ip></i>	30
3.3	CONFIGURE MODE COMMANDS.....	31
3.3.1	<i>bye</i>	31
3.3.2	<i>disable</i>	31
3.3.3	<i>!</i>	31
3.3.4	<i>interface gigabit <portNo></i>	31
3.3.5	<i>interface trunk-group <number></i>	31
3.3.6	<i>interface vlan <vlanid></i>	31
3.3.7	<i>profile acl</i>	31
3.3.8	<i>profile alarm</i>	32
3.3.9	<i>profile igmp-acl</i>	32
3.3.10	<i>profile igmp-mvr</i>	32
3.3.11	<i>profile sch</i>	32
3.3.12	<i>promote <prompt></i>	32
3.3.13	<i>promote default</i>	32
3.3.14	<i>sntp polling-interval <interval></i>	32
3.3.15	<i>sntp server address <ip></i>	32
3.3.16	<i>sntp sync</i>	32
3.3.17	<i>time set timezone</i>	33
3.3.18	<i>time set {date/time}</i>	33
3.3.19	<i>account add <username></i>	33
3.3.20	<i>account delete <username></i>	34
3.3.21	<i>account modify <username></i>	34
3.3.22	<i>kick <index> {cli/console/web}</i>	34
3.3.23	<i>syslog server <ip></i>	34
3.3.24	<i>syslog {enable/disable}</i>	35
3.3.25	<i>setenv pagefilter <enabled></i>	35
3.3.26	<i>setenv script-delay <delay></i>	35
3.3.27	<i>setenv show-date-time-in-prompt <enabled></i>	35
3.3.28	<i>clisettings <timeout></i>	35
3.3.29	<i>runningcfg clear</i>	35
3.3.30	<i>runningcfg get <ip> <username> <password> {binary/cli} <string></i>	37
3.3.31	<i>runningcfg import download</i>	37
3.3.32	<i>runningcfg put <ip> <username> <password> {binary/cli} <string></i>	38
3.3.33	<i>runningcfg replace-save <inbandBackupIndex></i>	38
3.3.34	<i>runningcfg restore index <inbandBackupIndex></i>	39
3.3.35	<i>runningcfg restore name <inbandBackupName></i>	39
3.3.36	<i>runningcfg save</i>	39
3.3.37	<i>firmware partition <partition></i>	40
3.3.38	<i>firmware write</i>	40
3.3.39	<i>system restart</i>	40
3.3.40	<i>system restart cancel</i>	41
3.3.41	<i>system dump <ip> <username> <password> <string></i>	41
3.3.42	<i>system stop ftp</i>	41
3.3.43	<i>route add <network> netmask <netmask> gateway <gateway></i>	41
3.3.44	<i>route delete <network> netmask <netmask></i>	41
3.3.45	<i>default-gateway <default_gateway></i>	41
3.3.46	<i>ip-address <ip></i>	42
3.3.47	<i>default all</i>	42
3.3.48	<i>list timezone</i>	42
3.3.49	<i>system-info contact <string></i>	42
3.3.50	<i>system-info location <string></i>	42

3.3.51	<i>system-info name <string></i>	42
3.3.52	<i>http port {<portNo>/default}</i>	43
3.3.53	<i>temperature shift down <time></i>	43
3.3.54	<i>temperature shift up <time></i>	43
3.3.55	<i>temperature threshold down <threshold></i>	43
3.3.56	<i>temperature threshold up <threshold></i>	43
3.3.57	<i>vlan <vlanid></i>	43
3.3.58	<i>vlan <vlanid> {<name> broadcast disable unknown-mc unknown-uc} {block forward}</i>	44
3.3.59	<i>vlan disable <vlanid></i>	44
3.3.60	<i>aging <time></i>	44
3.3.61	<i>fdb-delete all</i>	44
3.3.62	<i>fdb-delete interface gigabit <portNo></i>	44
3.3.63	<i>fdb-delete vlan <vlanid></i>	45
3.3.64	<i>fdbstatic <number> interface gigabit <portNo> <vlanid><mac></i>	45
3.3.65	<i>fdbstatic delete <number></i>	46
3.3.66	<i>fdbstatic delete all</i>	46
3.3.67	<i>fdbstatic delete interface gigabit <portNo></i>	46
3.3.68	<i>fdbstatic delete vlan <vlanid></i>	46
3.3.69	<i>stp {disable/enable}</i>	46
3.3.70	<i>stp bpdu {deny/flooding}</i>	46
3.3.71	<i>stp forward-delay <number></i>	46
3.3.72	<i>stp hello-time <number></i>	47
3.3.73	<i>stp max-age <number></i>	47
3.3.74	<i>stp msti <index> { add create delete set} { <vlan> range}</i>	47
3.3.75	<i>stp priority <number></i>	47
3.3.76	<i>stp region-name <name></i>	47
3.3.77	<i>stp revision <value></i>	47
3.3.78	<i>stp version {stp/rstp/mstp}</i>	48
3.3.79	<i>jumboframe {enable/disable}</i>	48
3.3.80	<i>jumboframe mtu <value></i>	48
3.3.81	<i>cos-queue-mapping cos <priority> queue <number></i>	49
3.3.82	<i>policer cos-mark green <green-number> yellow <yellow-number> red <red-number></i>	49
3.3.83	<i>policer dscp-mark green <green-number> yellow <yellow-number> red <red-number></i>	49
3.3.84	<i>policer ingress-color {aware/blind}</i>	49
3.3.85	<i>policer ingress-color cos <number> {red/yellow/green}</i>	50
3.3.86	<i>mirror analyzer-port {enable/disable}</i>	50
3.3.87	<i>mirror analyzer-port <portNo></i>	50
3.3.88	<i>vlan <vlanid> unknown-uc {block/forward}</i>	50
3.3.89	<i>vlan <vlanid> unknown-mc {block/forward}</i>	50
3.3.90	<i>vlan <vlanid> broadcast {block/forward}</i>	50
3.3.91	<i>port-mirror monitor-port <portNo></i>	51
3.3.92	<i>port-mirror {enable/disable}</i>	51
3.3.93	<i>port-mirror {tx-analyzer-port/rx-analyzer-port} <portNo></i>	51
3.3.94	<i>counter interface-counter clear <portNo></i>	51
3.3.95	<i>counter rmon-counter clear <portNo></i>	51
3.3.96	<i>multicast-fdb delete all</i>	51
3.3.97	<i>multicast-fdb static delete</i>	52
3.3.98	<i>multicast-fdb static <number> interface gigabit <portNo> <vlan> <ipaddr></i>	52
3.3.99	<i>ring-group <number></i>	52
3.3.100	<i>ext-tpid <number></i>	52
3.3.101	<i>profile igmp-mvr</i>	53
3.3.102	<i>profile igmp-acl</i>	53
3.3.103	<i>dot1x {enable/disable}</i>	53
3.3.104	<i>dot1x radius set <ip> <auth_port> <secret></i>	54
3.3.105	<i>dot1x clear eapol-stats {<portNo>/all}</i>	54
3.3.106	<i>dot1x clear dot1x-radius-stats</i>	54
3.3.107	<i>https {enable/disable}</i>	54
3.3.108	<i>https port {<portNo>/default}</i>	54
3.3.109	<i>interface trunk-group <number></i>	55
3.3.110	<i>fdb-delete interface trunk-group <number></i>	55
3.3.111	<i>ssl default-certificate</i>	55

3.3.112	<i>ssl upload</i>	55
3.4	INTERFACE GIGABIT MODE COMMANDS	56
3.4.1	<i>accfrm</i>	56
3.4.2	<i>priority</i> <priority>	56
3.4.3	<i>vlan</i> <vlanid>.....	56
3.4.4	<i>vlan</i> <vlanid> <i>disable</i>	56
3.4.5	<i>vlan</i> <vlanid> <i>tag</i>	56
3.4.6	<i>vlan</i> <vlanid> <i>untag</i>	56
3.4.7	<i>stpport</i> { <i>disable/enable</i> }.....	57
3.4.8	<i>stpport cost</i> <number>.....	57
3.4.9	<i>stpport edge-port</i> { <i>enable/disable</i> }.....	57
3.4.10	<i>stpport priority</i> <number>.....	57
3.4.11	<i>flow-control</i> { <i>enable/disable</i> }.....	58
3.4.12	<i>speed</i>	58
3.4.13	<i>sfp-speed</i> (for 10G ports)	58
3.4.14	<i>sfp-speed</i> (for 1G ports)	58
3.4.15	<i>port</i> { <i>enable/disable</i> }.....	58
3.4.16	<i>default vlan</i>	59
3.4.17	<i>policer pir</i> <pir-rate> <i>pbs</i> <pbs-size> <i>cir</i> <cir-rate> <i>cbs</i> <cbs-size> { <i>drop/cos/dscp</i> }	60
3.4.18	<i>policer disable</i>	60
3.4.19	<i>acl-profile-bind</i> <number>	60
3.4.20	<i>def-acl</i> { <i>permit/deny</i> }	60
3.4.21	<i>queue-scheduler bind</i> <number>.....	60
3.4.22	<i>port-shaper</i> { <i>enable/disable</i> }.....	60
3.4.23	<i>port-shaper</i> <rate>	61
3.4.24	<i>queue-shaper</i> { <i>enable/disable</i> }.....	61
3.4.25	<i>queue-shaper queue</i> <number> <rate>	61
3.4.26	<i>port-isolation</i> <portNo>	61
3.4.27	<i>unknown-uc rate</i> <rate>	61
3.4.28	<i>unknown-uc</i> { <i>block/forward</i> }.....	61
3.4.29	<i>unknown-mc rate</i> <rate>	62
3.4.30	<i>unknown-mc</i> { <i>block/forward</i> }.....	62
3.4.31	<i>broadcast rate</i> <rate>.....	62
3.4.32	<i>broadcast</i> { <i>block/forward</i> }	62
3.4.33	<i>vlan-stack</i> { <i>enable/disable</i> }.....	62
3.4.34	<i>protocol-vlan</i> <number> <i>create</i> <ether-type> <svlan> <s-prio>	62
3.4.35	<i>protocol-vlan</i> <number> <i>delete</i>	63
3.4.36	<i>vlan-trans</i> <number> <i>create</i> <cvlan> <c-prio> <svlan> <s-prio> <i>many-to</i> -	63
3.4.37	<i>vlan-trans</i> <number> <i>delete</i>	63
3.4.38	<i>igmp mvrprofile</i> <index>	64
3.4.39	<i>igmp aclprofile</i> <index>	64
3.4.40	<i>igmp max-channel</i> <number>.....	64
3.4.41	<i>dot1x</i> { <i>force-reinitialize/force-reauthenticate</i> }.....	64
3.4.42	<i>dot1x auth-port-control</i> { <i>auto/force-authorized/force-unauthorized</i> }	64
3.4.43	<i>dot1x auth-quiet-period</i> <period>	64
3.4.44	<i>dot1x auth-tx-period</i> <period>	65
3.4.45	<i>dot1x max-req</i> <number>	65
3.4.46	<i>dot1x auth-supp-timeout</i> <timeout>	65
3.4.47	<i>dot1x auth-server-timeout</i> <timeout>	65
3.4.48	<i>dot1x reauth</i> { <i>enable/disable</i> }	65
3.4.49	<i>dot1x reauth-period</i> <period>	66
3.5	ACL-PROFILE CONFIGURE MODE COMMANDS.....	67
3.5.1	<i>acl-profile</i> <number> { <i>create/delete</i> }.....	67
3.5.2	<i>acl-profile</i> <prof-number> { <i>create/delete</i> } <i>entry</i> <entry-number>	67
3.5.3	<i>acl-profile</i> <prof-number> <i>set name</i> <name>.....	67
3.5.4	<i>acl-profile</i> <prof-number> <i>set entry</i> <entry-number> <i>mac-type set vlan</i> <vlanid>	67
3.5.5	<i>acl-profile</i> <prof-number> <i>set entry</i> <entry-number> <i>mac-type set vlan any</i>	68
3.5.6	<i>acl-profile</i> <prof-number> <i>set entry</i> <entry-number> <i>mac-type set</i> { <i>srcmac/dstmac</i> } <mac> <mask> ..	68
3.5.7	<i>acl-profile</i> <prof-number> <i>set entry</i> <entry-number> <i>mac-type set ethertype</i> <ethertype>	68
3.5.8	<i>acl-profile</i> <prof-number> <i>set entry</i> <entry-number> <i>mac-type set ethertype any</i>	69
3.5.9	<i>acl-profile</i> <prof-number> <i>set entry</i> <entry-number> <i>ipv4-type set</i> { <i>srcip/dstip</i> } <ipaddr> <mask>....	69

3.5.10	<i>acl-profile <prof-number> set entry <entry-number> ipv4-type set ip-protocol <protocol-id></i>	69
3.5.11	<i>acl-profile <prof-number> set entry <entry-number> ipv4-type set ip-protocol any</i>	70
3.5.12	<i>acl-profile <prof-number> set entry <entry-number> l4port-type set protocol {tcp udp}</i>	70
3.5.13	<i>acl-profile <prof-number> set entry <entry-number> l4port-type set {srcip dstip} <ipaddr> <mask></i> .	70
3.5.14	<i>acl-profile <prof-number> set entry <entry-number> l4port-type set {srcport dstport} <number></i>	71
3.5.15	<i>acl-profile <prof-number> set entry <entry-number> l4port-type set {srcport dstport} any</i>	71
3.5.16	<i>acl-profile <prof-number> set entry <entry-number> tos-type set {srcip dstip} <ipaddr> <mask></i>	71
3.5.17	<i>acl-profile <prof-number> set entry <entry-number> tos-type set type {precedence/tos/dscp } <number></i>	72
3.5.18	<i>acl-profile <prof-number> set entry <entry-number> tos-type set type any</i>	72
3.5.19	<i>acl-profile <prof-number> set entry <entry-number> action forwarding {deny permit}</i>	72
3.5.20	<i>acl-profile <prof-number> set entry <entry-number> action queue <number></i>	73
3.5.21	<i>acl-profile <prof-number> set entry <entry-number> action cos <number></i>	73
3.5.22	<i>acl-profile <prof-number> set entry <entry-number> action copyframe</i>	73
3.6	SCH-PROFILE CONFIGURE MODE COMMANDS.....	74
3.6.1	<i>scheduler-profile <number> method {spq spq-wrr wrr}</i>	74
3.6.2	<i>scheduler-profile <prof-number> queue <queue-number> weight <number></i>	74
3.7	SNMP CONFIGURE MODE COMMANDS	75
3.7.1	<i>snmp <index> notify <name></i>	75
3.7.2	<i>snmp <index> notify delete</i>	75
3.7.3	<i>snmp <index> target <ip></i>	75
3.7.4	<i>snmp <index> target delete</i>	75
3.7.5	<i>snmp community <name> group <name></i>	76
3.7.6	<i>snmp community <name> ro</i>	76
3.7.7	<i>snmp community <name> rw</i>	76
3.7.8	<i>snmp community <name> view <name></i>	76
3.7.9	<i>snmp create-community {ro rw} <name> {view group} <name></i>	77
3.7.10	<i>snmp create-group <name> model {v1 v2 v3sum} level {auth noauth priv} read <name> write <name></i> 77	77
3.7.11	<i>snmp create-user {access group} {ro rw} {md5 sha} <passPhrase> des <passPhrase></i>	77
3.7.12	<i>snmp create-view <name> type { exclude include} subtree <subtree></i>	78
3.7.13	<i>snmp delete-community <name></i>	78
3.7.14	<i>snmp delete-group <name></i>	78
3.7.15	<i>snmp delete-user name</i>	79
3.7.16	<i>snmp delete-view { index name }</i>	79
3.7.17	<i>snmp version { v2c v3 }</i>	79
3.8	INTERFACE VLAN MODE COMMANDS.....	80
3.8.1	<i>igmp vlan {create/delete}</i>	80
3.8.2	<i>igmp router-port <portNo></i>	80
3.8.3	<i>igmp access-mode {snooping/proxy}</i>	80
3.8.4	<i>igmp leave-mode {normal/fast}</i>	80
3.8.5	<i>igmp version {v2 v3 v3compatible}</i>	80
3.8.6	<i>igmp robustness <number></i>	80
3.8.7	<i>igmp query-interval <number></i>	80
3.8.8	<i>igmp max-response-time <number></i>	81
3.8.9	<i>igmp last-member-query-count <number></i>	81
3.8.10	<i>igmp last-member-query-interval <number></i>	81
3.8.11	<i>igmp vlan interface address <ipaddr></i>	81
3.8.12	<i>ip-address <ip></i>	81
3.8.13	<i>ip-address <ip> netmask <netmask></i>	81
3.8.14	<i>igmp version {v2 v3 v3compatible}</i>	82
3.9	RING GROUP MODE COMMANDS.....	83
3.9.1	<i>ringv2-group <number></i>	83
3.9.2	<i>guardtimer <time></i>	83
3.9.3	<i>mode enable</i>	83
3.9.4	<i>mode disable</i>	83
3.9.5	<i>node1 <portNo></i>	83
3.9.6	<i>node2 <portNo></i>	83
3.9.7	<i>role ring-master</i>	83
3.9.8	<i>role ring-slave</i>	84
3.9.9	<i>role coupling-primary</i>	84

3.9.10	<i>role coupling-backup</i>	84
3.9.11	<i>role dual-homing</i>	84
3.9.12	<i>role chain-head</i>	84
3.9.13	<i>role chain-tail</i>	84
3.9.14	<i>role chain-member</i>	84
3.9.15	<i>role balancing-chain-terminal-1</i>	84
3.9.16	<i>role balancing-chain-terminal-2</i>	84
3.9.17	<i>role balancing-chain-member</i>	84
3.9.18	<i>role balancing-chain-central-block</i>	85
3.10	IGMP MVR MODE COMMANDS.....	86
3.10.1	<i>igmp-mvr</i> <number,2..15> {create/delete}.....	86
3.10.2	<i>igmp-mvr</i> <p-number> entry <e-number> <startIP> <endIP> <vid>.....	86
3.10.3	<i>igmp-mvr</i> <p-number> entry <e-number> delete.....	86
3.11	IGMP ACL MODE COMMANDS.....	87
3.11.1	<i>igmp-acl</i> <number> {create/delete}.....	87
3.11.2	<i>igmp-acl</i> <number> {default-deny default-permit}.....	87
3.11.3	<i>igmp-acl</i> <p-number> entry <e-number> <startIP> <endIP> {<vid> all} {permit	87
3.11.4	<i>igmp-acl</i> <p-number> entry <e-number> delete.....	87
3.12	TRUNK GROUP MODE COMMANDS.....	88
3.12.1	<i>trunk enable static</i>	88
3.12.2	<i>trunk disable</i>	88
3.12.3	<i>port-trunk add</i> <portNo>.....	88
3.12.4	<i>port-trunk remove</i> {<portNo> all}.....	88
3.13	ALARM RELATED COMMANDS.....	89
3.13.1	<i>show profile alarm</i>	89
3.13.2	<i>show alarm current</i>	89
3.13.3	<i>show event</i>	89
3.13.4	<i>show alarm history</i>	89
3.13.5	<i>event clear</i>	89
3.13.6	<i>alarm history clear</i>	89
3.13.7	<i>profile alarm</i>	89
3.13.8	<i>alarm</i> <alarmid> {mask/unmask major minor}.....	90

[LIST OF TABLES]

Table 2-1	List of Execution Modes.....	13
Table 2-2	List of Terminal Keys.....	14

[LIST OF FIGURES]

Figure 2-1	Screen Description.....	13
------------	-------------------------	----

1. Scope

1.1 Scope

1.2 Audience

1.3 Pre-required Knowledge

1.4 Access to Hardware Interface

1.5 Related Documents

1 Scope

1.1 Scope

This user guide describes the commands and parameters of the Command Line Interface (CLI) as implemented in the current version of DIS-700G-28XS software. These commands are used to set-up, administer and maintain the system.

1.2 Audience

The guide is intended for Operating personnel (sometimes called craft persons).

1.3 Pre-required Knowledge

The reader must be familiar with the:

- Basic operations of DIS-700G-28XS switch (see the Quick Installation Guide).
- Security and activity monitoring constraints that limit how a command is implemented.

1.4 Access to Hardware Interface

Access to the hardware interface is by a terminal (or computer with terminal emulation software). Requirements for the terminal are:

- RS-232 ASCII port
- Selectable transmission baud rate
- Full alphanumeric capability
- Selectable odd/even or no parity check

1.5 Related Documents

You may want to refer to the following related documents:

- DIS-700G-28XS Quick Installation Guide
- DIS-700G-28XS WebGUI User Manual

2. Operator Interface

2.1 Introduction

2.2 Connect Interface

2.3 Authorization Level

2.4 Screen Description

2.5 Execution Modes

2.6 Getting Help

2.7 Terminal Key Function

2.8 Notation Conventions

2 Operator Interface

2.1 Introduction

Access to the Operations System (OS) /Network Element (NE) system is protected by a logon security system. You can log on to the NE with the user name and password. After three failed logon attempts, the system refuses further attempts.

After you log on, the system monitors the interface for periods of inactivity. If the interface is inactive for too long, you are automatically logged off.

All the NEs have the same initial user name (admin) and password (admin). You should change the password as soon as possible, because the initial password is known to anyone who reads this manual. You can also change the user name or add additional user names. Use the “account add” command to enter a new user identification, password and authorization level. The system can handle one local logon session and at least four remote/OS sessions.

2.2 Connect Interface

Interface	Parameter
Console	Baud rate: 115200bps, Data bit: 8, Parity: None, Stop bit: 1
Telnet	Port 23
SSH	Port 22 (In Windows, you can run terminal emulator such as PuTTY)

2.3 Authorization Level

Level	Description
Superuser	Superuser can access all management features.
Engineer	Engineer can access all management features except user account management.
Guest (default)	Read-only mode (Guest can only change his own password). Users of this level can query pages like PM and FM.

2.4 Login Example

```

Localhost login: admin
Password: *****

DIS-700G-28XS 1.00.001

Localhost:>enable
Localhost:%show version

DIS-700G-28XS v1.00.001

```

Figure 2-1 login example

2.5 Execution Modes

The CLI contains several execution modes. Users will see different set of commands under different execution modes. Table 2-1 lists all the execution modes and their purposes. When users enter a certain execution mode, the corresponding mode prompt will be displayed automatically on the screen. The mode prompts of all the execution modes are also listed in Table 2-1.

Table 2-1 List of Execution Modes

Mode	Access Level	Prompt
Init Mode	Guest	>
Enable Mode	Guest	%
Config Mode	Guest	(conf)#
Alarm Profile Config Mode	Engineer	(alarm-profile-conf)#
Gigabit Interface Config Mode	Engineer	(gigabit-intf-conf)#
ACL Profile Config Mode	Engineer	(acl-profile-conf)#
scheduler Profile Config Mode	Engineer	(sch-profile-conf)#
Vlan Interface Config Mode	Engineer	(vlan-intf-conf)#
IGMP MVR Profile Config Mode	Engineer	(igmp-mvr-profile-conf)#
IGMP ACL Profile Config Mode	Engineer	(igmp-acl-profile-conf)#
Ring Group Config Mode	Engineer	(ring-group-conf)#
Trunk Group Config Mode	Engineer	(trunk-group-conf)#
Router Rip Config Mode	Engineer	(router-rip-conf)#
Router Ospf Config Mode	Engineer	(router-ospf-conf)#

2.6 Getting help

The user can get help by entering a question mark '?' at each position in the command. The displayed result depends on the execution mode and previous input.

2.7 Terminal Key Function

Following is the list of all the terminal keys and their function.

Table 2-2 List of Terminal Keys

ENTER	Run a CLI config script
CTRL-M	
TAB	Tab completion. If tab is pressed after a non-whitespace character, complete the word before the Tab. If tab is pressed after a whitespace character, complete the next word.
CTRL-I	
?	Display available commands If ? is pressed after a non-whitespace character, show possible choices for this word. If ? is pressed after a whitespace character, show possible choices for the next word.
<Up Arrow>	Up history
CTRL-P	
<Down Arrow>	Down history
CTRL-N	
Home	Move the cursor to the beginning of the input line
CTRL-A	
End	Move the cursor to the end of the input line
CTRL-E	
<Left Arrow>	Move the cursor backward
CTRL-B	
<Right Arrow>	Move the cursor forward
CTRL-F	
BACKSPACE	Erase the character before the cursor
CTRL-H	

2.8 Notation Conventions

The notation conventions for the parameter syntax of each CLI command are as follows:

- Parameters enclosed in [] are optional.
- Parameter values are separated by a vertical bar “|” only when one of the specified values can be used.
- Parameter values are enclosed in { } when you must use one of the values specified.

3. Commands Descriptions

3.1 Initialize Mode Commands

3.2 Enable Mode Commands

3.3 Configure Mode Commands

3.4 Interface Gigabit Mode Commands

3.5 Acl-profile Configure Mode Commands

3.6 Sch-profile Configure Mode Commands

3.7 Interface VLAN Mode Commands

3.8 Router RIP Configure Mode Commands

3.9 Router OSPF Configure Mode Commands

3 Commands Descriptions

3.1 Initialize Mode Commands

The commands in this section (except 'enable' command) can be executed under all command modes. These commands are global commands.

3.1.1 bye

Description	Quit CLI.
Syntax	bye
Parameter	None

3.1.2 !

Description	Execute the specific number of command in history	
Syntax	! <number>	
Parameter		
	Name	Description
	<number>	Valid values: 1 ~ 32 Type: Mandatory

3.1.3 configure

Description	Enter configuration mode.
Syntax	configure
Parameter	None

3.1.4 enable

Description	Enter enable mode.
Syntax	enable
Parameter	None

3.1.5 exit

Description	Exit current mode.
Syntax	exit
Parameter	None

3.1.6 list command-tree

Description	List tree of all available CLI commands
Syntax	list command-tree
Parameter	None

3.1.7 list timezone

Description	List time zones
Syntax	list timezone
Parameter	None

3.1.8 show env

Description	Show CLI environment variables
Syntax	show env
Parameter	None

3.1.9 show history

Description	Show command history (Note: commands issued in one execution mode only appear in history of that execution mode)
Syntax	show history
Parameter	None

3.1.10 show time

Description	Show current time
Syntax	show time
Parameter	None

3.1.11 show uptime

Description	Show uptime
Syntax	show uptime
Parameter	None

3.1.12 sleep

Description	Sleep for the specified number of milli-seconds	
Syntax	sleep <time>	
Parameter		
	Name	Description
	<time>	Valid values: 1 ~ 0xFFFFFFFF ms Type: Mandatory

3.2 Enable Mode Commands

All the “show - -” commands in this section can also be executed under any other command mode except Initialize Mode.

3.2.1 bye

Description	Quit CLI.
Syntax	bye
Parameter	None

3.2.2 !

Description	Execute the specific number of command in history	
Syntax	! <number>	
Parameter		
	Name	Description
	<number>	Valid values: 1 ~ 32 Type: Mandatory

3.2.3 exit

Description	Exit current mode.
Syntax	exit
Parameter	None

3.2.4 configure

Description	Enter configuration mode.
Syntax	configure
Parameter	None

3.2.5 disable

Description	Enter init mode.
Syntax	disable
Parameter	None

3.2.6 kick

Description	Kick off a logged-in user (only superuser can execute this command)	
Syntax	kick <index> {console cli web}	
Parameter		
	Name	Description
	<index>	Valid values: 1 ~ 10 Type: Mandatory

3.2.7 list alarm

Description	List valid alarm ID
Syntax	list alarm
Parameter	None

3.2.8 list command-tree

Description	List tree of all available CLI commands
Syntax	list command-tree
Parameter	None

3.2.9 list event

Description	List valid event ID
--------------------	---------------------

Syntax	list event
Parameter	None

3.2.10 list execution-modes

Description	List all available execution modes
Syntax	list execution-modes
Parameter	None

3.2.11 list timezone

Description	List timezones
Syntax	list timezone
Parameter	None

3.2.12 ping

Description	send ICMP ECHO_REQUEST to network hosts	
Syntax	ping <ip> ping <ip> count <count> ping <ip> count <count> size <size> ping <ip> size <size>	
Parameter		
	Name	Description
	<ip>	Valid values: - Type: Mandatory
	<count>	Packet count Valid values: 1 ~ 4294967295 Default value: 0 Type: Mandatory
	<size>	The number of data bytes to be sent Valid values: 1 ~ 65500 Default value: 0 Type: Mandatory

3.2.13 show snmp

Description	Show SNMP information.
Syntax	show snmp
Parameter	None

3.2.14 show account

Description	Show account list.
Syntax	show account
Parameter	None

3.2.15 show login-users

Description	Show logged-in users.
Syntax	show login-users
Parameter	None

3.2.16 show syslog

Description	Show syslog configuration.
Syntax	show syslog
Parameter	None

3.2.17 show clisettings

Description	Show CLI settings.
Syntax	show clisettings
Parameter	None

3.2.18 show runningcfg

Description	Show running configuration.
Syntax	show runningcfg
Parameter	None

3.2.19 show runningcfg default

Description	Show default running configuration.
Syntax	show runningcfg default
Parameter	None

3.2.20 show firmware status

Description	Show firmware update status.
Syntax	show firmware status
Parameter	None

3.2.21 show firmware partition

Description	Show firmware partition information.
Syntax	show firmware partition
Parameter	None

3.2.22 show management

Description	Show management channel settings.
Syntax	show management
Parameter	None

3.2.23 show route static

Description	Show routing static table.
Syntax	show route static
Parameter	None

3.2.24 show runningcfg backup

Description	Show running configuration backup.
Syntax	show runningcfg backup
Parameter	None

3.2.25 show bootloader

Description	Show boot loader information.
Syntax	show bootloader
Parameter	None

3.2.26 show system information

Description	Show system information.
Syntax	show system information
Parameter	None

3.2.27 show http

Description	Show HTTP configuration.
--------------------	--------------------------

Syntax	show http
Parameter	None

3.2.28 show temperature

Description	Show temperature information.
Syntax	show temperature
Parameter	None

3.2.29 show time

Description	Show current time.
Syntax	Show time
Parameter	None

3.2.30 show version

Description	Show version information.
Syntax	show version
Parameter	None

3.2.31 show system inventory

Description	Show system inventory.
Syntax	show system inventory
Parameter	None

3.2.32 show aging

Description	Show aging time for MAC learning table (system-wide).
Syntax	show aging
Parameter	None

3.2.33 show fdb

Description	Show MAC learning table.
Syntax	show fdb
Parameter	None

3.2.34 show fdb interface gigabit <portNo>

Description	Show MAC learning table per gigabit port.	
Syntax	show fdb interface gigabit <portNo>	
Parameter		
	Name	Description
	<portNo>	Valid values: 1 ~ 28 Type: Mandatory

3.2.35 show fdb vlan <vlanid>

Description	Show MAC learning table per VLAN index.	
Syntax	show fdb vlan <vlanid>	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094 Type: Mandatory

3.2.36 show fdbstatic

Description	Show static MAC forwarding table.	
Syntax	show fdbstatic	
Parameter	None	

3.2.37 show fdbstatic interface gigabit <portNo>

Description	Show static MAC forwarding table per gigabit port.	
Syntax	show fdbstatic interface gigabit <portNo>	
Parameter		
	Name	Description
	<portNo>	Valid values: 1 ~ 28 Type: Mandatory

3.2.38 show fdbstatic vlan <vlanid>

Description	Show static MAC forwarding table per VLAN index.	
Syntax	show fdbstatic vlan <vlanid>	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094 Type: Mandatory

3.2.39 show interface gigabit <portNo>

Description	Show interface information per gigabit port.	
Syntax	show interface gigabit <portNo>	
Parameter		
	Name	Description
	<portNo>	Valid values: 1 ~ 28 Type: Mandatory

3.2.40 show interface gigabit <portNo> counter

Description	Show Ethernet counter per gigabit port.	
Syntax	show interface gigabit <portNo> counter	
Parameter		
	Name	Description
	<portNo>	Valid values: 1 ~ 28 Type: Mandatory
	counter	Show Gigabit Ethernet counter.

3.2.41 show interface gigabit <portNo> stp

Description	Show STP information per gigabit port.	
Syntax	show interface gigabit <portNo> stp	
Parameter		
	Name	Description
	<portNo>	Valid values: 1 ~ 28 Type: Mandatory
	stp	Show STP port information.

3.2.42 show interface gigabit <portNo> vlan

Description	Show VLAN information per gigabit port.	
Syntax	show interface gigabit <portNo> vlan	
Parameter		
	Name	Description
	<portNo>	Valid values: 1 ~ 28 Type: Mandatory
	vlan	Show VLAN information.

3.2.43 show jumboframe

Description	Show jumbo frame settings.
Syntax	show jumboframe
Parameter	None

3.2.44 show stp

Description	System Wide Spanning Tree Setting/Status.
Syntax	show stp
Parameter	None

3.2.45 show vlan

Description	Show bridge port memberset/status.
Syntax	show vlan
Parameter	None

3.2.46 show vlan <vlanid>

Description	Show bridge port member set/status per VLAN index (1~4094).	
Syntax	show vlan <vlanid>	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094 Type: Mandatory.

3.2.47 show cos-queue-mapping

Description	Show CoS queue mapping table.
Syntax	show cos-queue-mapping
Parameter	None

3.2.48 show interface gigabit <portNo> qos

Description	Show QoS per gigabit port.	
Syntax	show interface gigabit <portNo> qos	
Parameter		
	Name	Description
	<portNo>	Valid values: 1 ~ 28 Type: Mandatory

3.2.49 show policer

Description	Show ingress policer table.
Syntax	show policer
Parameter	None

3.2.50 show profile acl {<number>|all}

Description	Show ACL profile detail information.	
Syntax	show profile acl {<number> all}.	
Parameter		
	Name	Description
	<number>	Valid values: 1 ~ 20 Type: Mandatory
	all	Show all ACL profile.

3.2.51 show interface gigabit <portNo> acl

Description	Show ACL profile per gigabit port.	
Syntax	show interface gigabit <portNo> acl	
Parameter		
	Name	Description
	<portNo>	Valid values: 1 ~ 28 Type: Mandatory

3.2.52 show queue-scheduler profile

Description	Show scheduler profile table.
Syntax	show queue-scheduler profile
Parameter	None

3.2.53 show queue-shaper

Description	Show queue shaper information.
Syntax	show queue-shaper
Parameter	None

3.2.54 show port-shaper

Description	Show port shaper information.
Syntax	show port-shaper
Parameter	None

3.2.55 show port-isolation

Description	Show all port isolation information.
Syntax	show port-isolation
Parameter	None

3.2.56 show interface gigabit <portNo> port-isolation

Description	Show isolation information per gigabit port.	
Syntax	show interface gigabit <portNo> port-isolation	
Parameter		
	Name	Description
	<portNo>	Valid values: 1 ~ 28 Type: Mandatory

3.2.57 show interface gigabit <portNo> storm-control

Description	Show storm control information per gigabit port.	
Syntax	show interface gigabit <portNo> storm-control	
Parameter		
	Name	Description
	<portNo>	Valid values: 1~28 Type: Mandatory

3.2.58 show vlan {unknown-uc|unknown-mc|broadcast}

Description	Show storm control information by VLAN.	
Syntax	show vlan unknown-uc show vlan unknown-mc show vlan broadcast	
Parameter		
	Name	Description
	unknown-uc	Show unknown unicast storm control information by VLAN. Type: Mandatory
	unknown-mc	Show unknown multicast storm control information by VLAN. Type: Mandatory
	broadcast	Show broadcast storm control information by VLAN. Type: Mandatory

3.2.59 show port-mirror

Description	Show port mirror information.
Syntax	show port-mirror
Parameter	None

3.2.60 show interface gigabit <portNo> rmon-counter

Description	Show Ethernet counter per gigabit port.	
Syntax	show interface gigabit <portNo> rmon-counter	
Parameter		
	Name	Description
	<portNo>	Valid values: 1~28. Type: Mandatory

3.2.61 show interface vlan igmp

Description	Show IGMP VLAN information.	
Syntax	show interface vlan igmp show interface vlan <vlanid> igmp	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094. Type: Optional

3.2.62 show multicast-fdb

Description	Show IGMP VLAN multicast forwarding table.	
Syntax	show multicast-fdb show multicast-fdb vlan <vlanid> show multicast-fdb interface gigabit <portNo>	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094. Type: Optional
	<portNo>	Valid values: 1~28. Type: Optional

3.2.63 show multicast-fdb static

Description	Show IGMP VLAN static multicast forwarding table.	
Syntax	show multicast-fdb static show multicast-fdb static vlan <vlanid> show multicast-fdb static interface gigabit <portNo>	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094. Type: Optional
	<portNo>	Valid values: 1~28. Type: Optional

3.2.64 show ring

Description	Show ring protection configuration.
Syntax	show ring
Parameter	None

3.2.65 show ssl decrypted

Description	Show ssl certificate with decrypted format.
Syntax	show ssl decrypted
Parameter	None

3.2.66 show ssl encrypted

Description	Show ssl certificate with encrypted format.
Syntax	show ssl encrypted
Parameter	None

3.2.67 show interface gigabit <portNo>

Description	Show interface gigaport information
Syntax	show interface gigabit <portNo>

Parameter		
	Name	Description
	<portNo>	Gigabit port. Valid values: 1 ~ 28 Type: Mandatory

3.2.68 show ext-tpid

Description	Show TPID for the VLAN Tag
Syntax	show ext-tpid
Parameter	None

3.2.69 show interface vlan

Description	Show VLAN interface information of all VLANs.
Syntax	show interface vlan
Parameter	None

3.2.70 show interface vlan <vlanid>

Description	Show VLAN interface information of specify VLAN.	
Syntax	show interface vlan <vlanid>	
Parameter		
	Name	Description
	<vlanid>	VLAN ID. Valid values: 1 ~ 4094 Type: Mandatory

3.2.71 show protocol-vlan

Description	Show protocol based VLAN information for all entries.
Syntax	show protocol-vlan
Parameter	None

3.2.72 show interface gigabit <portNo> vlan

Description	Show vlan information per port	
Syntax	show interface gigabit <portNo> vlan	
Parameter		
	Name	Description
	<portNo>	Gigabit port. Valid values: 1 ~ 28 Type: Mandatory

3.2.73 show vlan-trans

Description	Show VLAN translation table for all
Syntax	show vlan-trans
Parameter	None

3.2.74 show igmp-mvr-profile {<number>|all}

Description	Show IGMP MVR profile	
Syntax	Show profile igmp-mvr-profile {<number> all}	
Parameter		
	Name	Description
	<number>	IGMP MVR profile number. Valid values: 1 ~ 15 Type: Mandatory

3.2.75 show igmp-acl-profile {<number>|all}

Description	Show IGMP ACL profile	
Syntax	Show profile igmp-acl-profile {<number> all}	
Parameter		
	Name	Description
	<number>	IGMP ACL profile number. Valid values: 1 ~ 15 Type: Mandatory

3.2.76 show interface gigabit <portNo> igmp

Description	Show IGMP information per port.	
Syntax	show interface gigabit <portNo> igmp	
Parameter		
	Name	Description
	<portNo>	Gigabit port. Valid values: 1 ~ 28 Type: Mandatory

3.2.77 show interface vlan igmp

Description	Show IGMP information.	
Syntax	show interface vlan igmp	
Parameter	None	

3.2.78 show interface vlan <vlanid> igmp

Description	Show IGMP information per vlan	
Syntax	show interface vlan <vlanid> igmp	
Parameter		
	Name	Description
	<vlanid>	VLAN ID. Valid values: 1 ~ 4094 Type: Mandatory

3.2.79 show multicast-fdb srclist

Description	Show multicast source list table.	
Syntax	show multicast-fdb srclist	
Parameter	None	

3.2.80 show multicast-fdb

Description	Show IGMP group membership table	
Syntax	show multicast-fdb	
Parameter	None	

3.2.81 show dot1x

Description	Show dot1x information.
Syntax	show dot1x
Parameter	None

3.2.82 show dot1x pae-info-status {<portNo>|all}

Description	Show dot1x PAE status.	
Syntax	show dot1x pae-info-status {<portNo> all}	
Parameter		
	Name	Description
	<portNo>	Gigabit port. Valid values: 1 ~ 28 Type: Mandatory

3.2.83 show dot1x eapol-stats {<portNo>|all}

Description	Show dot1x EAPOL stats.	
Syntax	show dot1x eapol-stats {<portNo> all}	
Parameter		
	Name	Description
	<portNo>	Gigabit port. Valid values: 1 ~ 28 Type: Mandatory

3.2.84 show dot1x radius-stats

Description	Show dot1x radius stats.
Syntax	show dot1x radius-stats
Parameter	None

3.2.85 show http

Description	show http and https information.
Syntax	show http
Parameter	None

3.2.86 show interface trunk-group

Description	show trunk group information.
Syntax	show interface trunk-group
Parameter	None

3.2.87 show fdb interface trunk-group <number>

Description	Show forwarding table per trunk group.	
Syntax	show fdb interface trunk-group <number>	
Parameter		
	Name	Description
	<number>	Trunk group. Valid values: 1 ~ 2 Type: Mandatory

3.2.88 show fdb

Description	Show forwarding table.
Syntax	show fdb
Parameter	None

3.2.89 show fdb vlan <vlanid>

Description	Show forwarding table per VLAN.	
Syntax	show fdb vlan <vlanid>	
Parameter		
	Name	Description
	<vlanid>	VLAN ID Valid values: 1 ~ 4094 Type: Mandatory

3.2.90 sleep

Description	Sleep for the specified number of milli-seconds	
Syntax	sleep <time>	
Parameter		
	Name	Description
	<time>	Valid values: 1 ~ 0xFFFFFFFF ms Type: Mandatory

3.2.91 system restart

Description	Restart System	
Syntax	system restart	
Parameter	None	

3.2.92 system stop

Description	Stop FTP transfer	
Syntax	system stop	
Parameter	None	

3.2.93 telnet <ip>

Description	Telnet to a remote host	
Syntax	telnet <ip>	
Parameter		
	Name	Description
	<ip>	Type: Mandatory

3.2.94 traceroute <ip>

Description	Print the route packets take to network host	
Syntax	traceroute <ip>	
Parameter		
	Name	Description
	<ip>	Type: Mandatory

3.3 Configure Mode Commands

Commands that can be executed under Configure Mode

3.3.1 bye

Description	Quit CLI.
Syntax	bye
Parameter	None

3.3.2 disable

Description	Enter init mode.
Syntax	disable
Parameter	None

3.3.3 !

Description	Execute the specific number of command in history	
Syntax	! <number>	
Parameter		
	Name	Description
	<number>	Valid values: 1 ~ 32 Type: Mandatory

3.3.4 interface gigabit <portNo>

Description	Gigabit Ethernet interface. (enter gigabit interface mode)	
Syntax	interface gigabit <portNo>	
Parameter		
	Name	Description
	<portNo>	Valid values: 1 ~ 28 Type: Mandatory

3.3.5 interface trunk-group <number>

Description	Trunk group interface	
Syntax	interface trunk-group <number>	
Parameter		
	Name	Description
	< number>	Valid values: 1 ~ 2 Type: Mandatory

3.3.6 interface vlan <vlanid>

Description	Vlan Ethernet interface (enter mode of interface vlan)	
Syntax	interface vlan <vlanid>	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1 ~ 4094 Type: Mandatory

3.3.7 profile acl

Description	Enter Acl Profile Config Mode
Syntax	profile acl
Parameter	None

3.3.8 profile alarm

Description	Alarm Profile Config Mode
Syntax	profile alarm
Parameter	None

3.3.9 profile igmp-acl

Description	Enter IGMP ACL profile config mode
Syntax	profile igmp-acl
Parameter	None

3.3.10 profile igmp-mvr

Description	Enter IGMP MVR profile config mode
Syntax	profile igmp-mvr
Parameter	None

3.3.11 profile sch

Description	Enter Scheduling Profile Config Mode
Syntax	profile sch
Parameter	None

3.3.12 promote <prompt>

Description	Prompt (1 ~ 31 characters)
Syntax	promote <prompt>
Parameter	None

3.3.13 promote default

Description	Set prompt to default
Syntax	promote default
Parameter	None

3.3.14 sntp polling-interval <interval>

Description	Set SNTP Polling interval.	
Syntax	sntp polling-interval <interval>	
Parameter		
	Name	Description
	<interval>	Valid values: 60 ~ 65535 seconds, 0: disable polling Type: Mandatory

3.3.15 sntp server address <ip>

Description	Set SNTP server address.	
Syntax	sntp server address <ip>	
Parameter		
	Name	Description
	<ip>	Type: Mandatory

3.3.16 sntp sync

Description	Manual SNTP synchronization.
Syntax	sntp sync
Parameter	None

3.3.17 time set timezone

Description	Set time zone.	
Syntax	time set timezone <timezone> time set timezone default	
Parameter		
	Name	Description
	<timezone>	Valid values: please see ' list timezone ' Type: Mandatory
	default	Set time zone to default (GMT/UTC). Type: Mandatory

3.3.18 time set {date|time}

Description	Set date/time.	
Syntax	time set date <month> <day> <year> time set time <hour> <minute> time set time <hour> <minute> <second>	
Parameter		
	Name	Description
	<month>	Valid values: 1 ~ 12 Type: Mandatory
	<day>	Valid values: 1 ~ 31 Type: Mandatory
	<year>	Valid values: 0 ~ 36 Type: Mandatory
	<hour>	Valid values: 0 ~ 23 Type: Mandatory
	<minute>	Valid values: 0 ~ 59 Type: Mandatory
	<second>	Valid values: 0 ~ 59 Type: Optional

3.3.19 account add <username>

Description	Add an account.	
Syntax	account add <username> account add <username> password <password> account add <username> password <password> comment <comment> account add <username> password <password> level <account_level> account add <username> password <password> level <account_level> comment <comment>	
Parameter		
	Name	Description
	<username>	Valid values: 1 ~ 31 characters Type: Mandatory
	<password>	Valid values: 0 ~ 31 characters Type: Mandatory
	<account_level>	Valid values: superuser engineer guest Type: Mandatory
	<comment>	Valid values: 0 ~ 31 characters Type: Mandatory

3.3.20 account delete <username>

Description	Delete an account.	
Syntax	account delete <username>	
Parameter		
	Name	Description
	<username>	Valid values: 1 ~ 31 characters Type: Mandatory

3.3.21 account modify <username>

Description	Modify an account	
Syntax	account modify <username> account modify <username> comment <comment> account modify <username> level <account_level> account modify <username> level <account_level> comment <comment> account modify <username> password <password> account modify <username> password <password> comment <comment> account modify <username> password <password> level <account_level> account modify <username> password <password> level <account_level> comment <comment>	
Parameter		
	Name	Description
	<username>	Valid values: 1 ~ 31 characters Type: Mandatory
	<password>	Valid values: 0 ~ 31 characters Type: Mandatory
	<account_level>	Valid values: dsuperuser engineer guest Type: Mandatory
	<comment>	Valid values: 0 ~ 31 characters Type: Mandatory

3.3.22 kick <index> { cli|console|web}

Description	Kick off a logged-in user.	
Syntax	kick <index> cli kick <index> console kick <index> web	
Parameter		
	Name	Description
	<index>	Valid values: 1 ~ 10 Type: Mandatory

3.3.23 syslog server <ip>

Description	Configure syslog server IP address.	
Syntax	syslog server <ip>	
Parameter		
	Name	Description
	<ip>	Syslog server IP address. Type: Mandatory

3.3.24 syslog {enable|disable}

Description	Disable or enable syslog service.
Syntax	syslog enable syslog disable
Parameter	None

3.3.25 setenv pagefilter <enabled>

Description	Configure Page Filter	
Syntax	setenv pagefilter	
Parameter		
	Name	Description
	<enabled>	Enable Page Filter Valid values: (0:disable, 1:enable) Type: Mandatory

3.3.26 setenv script-delay <delay>

Description	Configure script delay	
Syntax	setenv script-delay <delay>	
Parameter		
	Name	Description
	<delay>	Script Delay Valid values: 1 ~ 0xFFFFFFFF ms Type: Mandatory

3.3.27 setenv show-date-time-in-prompt <enabled>

Description	Show Date/Time in Prompt (0:disable, 1:enable)	
Syntax	setenv show-date-time-in-prompt <enabled>	
Parameter		
	Name	Description
	<enabled>	enabled Valid values: (0:disable, 1:enable) Type: Mandatory

3.3.28 clisettings <timeout>

Description	Configure CLI settings.	
Syntax	clisettings <timeout> clisettings <timeout> <flag> clisettings <timeout> <flag> <maxSessions>	
Parameter		
	Name	Description
	<timeout>	Valid values: 60 ~ 65535 seconds, 0: no timeout Type: Mandatory
	<flag>	Valid values: bitmap <input type="checkbox"/> showAlarm(0) <input type="checkbox"/> showEvent(1) <input type="checkbox"/> showReadWriteStatus(2) Type: Optional
	<maxSessions>	Valid values: 1 ~ 10 sessions Type: Mandatory

3.3.29 runningcfg clear

Description	Clear configuration.
Syntax	runningcfg clear all

	runningcfg clear all noreboot runningcfg clear general runningcfg clear general noreboot	
Parameter		
	Name	Description
	all	Clear all configuration. Type: Mandatory
	general	Clear general configuration. Type: Mandatory
	noreboot	Clear configuration without Reboot. Must reboot system manually for the changes to take effect! Type: Optional

3.3.30 runningcfg get <ip> <username> <password> {binary|cli} <string>

Description	Get exported configuration files from a FTP server.	
Syntax	runningcfg get <ip> <username> <password> binary <string> runningcfg get <ip> <username> <password> cli <string>	
Parameter		
	Name	Description
	<ip>	Type: Mandatory
	<username>	Valid values: 1 ~ 32 characters Type: Mandatory
	<password>	Valid values: 1 ~ 32 characters Type: Mandatory
	binary	Get two binary images. Type: Mandatory
	cli	Get two CLI scripts. Type: Mandatory
	<string>	Remote filename prefix. Valid values: 1 ~ 64 characters Type: Mandatory

3.3.31 runningcfg import download

Description	Import configuration from files retrieved via ' <u>runningcfg get</u> '.	
Syntax	runningcfg import download binary runningcfg import download binary noreboot runningcfg import download cli runningcfg import download cli noreboot	
Parameter		
	Name	Description
	binary	Import configuration from binary images retrieved via ' <u>runningcfg get</u> '. Type: Mandatory
	cli	Import configuration from the CLI scripts retrieved via ' <u>runningcfg get</u> '. Type: Mandatory
	Noreboot	Import configuration without Reboot. Must reboot system manually for the changes to take effect! Type: Optional

3.3.32 runningcfg put <ip> <username> <password> {binary|cli} <string>

Description	Put exported configuration files to a FTP server.	
Syntax	runningcfg put <ip> <username> <password> binary <string> runningcfg put <ip> <username> <password> cli <string>	
Parameter		
	Name	Description
	<ip>	Type: Mandatory
	<username>	Valid values: 1 ~ 32 characters Type: Mandatory
	<password>	Valid values: 1 ~ 32 characters Type: Mandatory
	binary	Put two binary images. Type: Mandatory
	cli	Put CLI scripts. Type: Mandatory
	<string>	Remote filename prefix. Valid values: 1 ~ 64 characters Type: Mandatory

3.3.33 runningcfg replace-save <inbandBackupIndex>

Description	Save running config to FLASH replacing existing the specified backup.	
Syntax	runningcfg replace-save <inbandBackupIndex> runningcfg replace-save <inbandBackupIndex> <inbandBackupName> runningcfg replace-save <inbandBackupIndex> <inbandBackupName> <generalBackupIndex> runningcfg replace-save <inbandBackupIndex> <inbandBackupName> <generalBackupIndex> <generalBackupName>	
Parameter		
	Name	Description
	<inbandBackupIndex>	Valid values: 1 ~ 16 Type: Mandatory
	<inbandBackupName>	Valid values: 1 ~ 31 characters Type: Optional
	<generalBackupIndex>	Valid values: 1 ~ 16 Type: Optional
	<generalBackupName>	Valid values: 1 ~ 31 characters Type: Optional

3.3.34 runningcfg restore index <inbandBackupIndex>

Description	Restore configuration.	
Syntax	runningcfg restore index <inbandBackupIndex> runningcfg restore index <inbandBackupIndex> <generalBackupIndex> runningcfg restore index <inbandBackupIndex> <generalBackupIndex> noreboot	
Parameter		
	Name	Description
	<inbandBackupIndex>	Valid values: 1 ~ 16 Type: Mandatory
	<generalBackupIndex>	Valid values: 1 ~ 16 Type: Optional (if omitted, use the same index as <inbandBackupIndex>)
	noreboot	Restore database without reboot. Must reboot system manually for the changes to take effect! Type: Optional

3.3.35 runningcfg restore name <inbandBackupName>

Description	Restore configuration.	
Syntax	runningcfg restore name <inbandBackupName> runningcfg restore name <inbandBackupName> <generalBackupName> runningcfg restore name <inbandBackupName> <generalBackupName> noreboot	
Parameter		
	Name	Description
	<inbandBackupName>	Valid values: 1 ~ 31 characters Type: Mandatory
	<generalBackupName>	Valid values: 1 ~ 31 characters Type: Optional (if omitted, use the same name as <inbandBackupName>)
	noreboot	Restore database without reboot. Must reboot system manually for the changes to take effect! Type: Optional

3.3.36 runningcfg save

Description	Save running config to FLASH.	
Syntax	runningcfg save runningcfg save <inbandBackupName> runningcfg save <inbandBackupName> <generalBackupName>	
Parameter		
	Name	Description
	<inbandBackupName>	Valid values: 1 ~ 31 characters Type: Optional
	<generalBackupName>	Valid values: 1 ~ 31 characters Type: Optional (if omitted, use the same name as <inbandBackupName>)

3.3.37 firmware partition <partition>

Description	Set boot partition.	
Syntax	firmware partition <partition>	
Parameter		
	Name	Description
	<partition>	Valid values: 0 ~ 1 Type: Mandatory

3.3.38 firmware write

Description	Perform Remote Download. Schedule a remote download (scheduled upgrade). Cancel a scheduled upgrade.	
Syntax	firmware write <ip> <username> <password> <string> {bootloader image} firmware write <ip> <username> <password> <string> {bootloader image} {noreboot <time>} firmware write <ip> <username> <password> <string> {bootloader image} noreboot <time> firmware write cancel	
Parameter		
	Name	Description
	<ip>	Type: Mandatory
	<username>	Valid values: 1 ~ 32 characters Type: Mandatory
	<password>	Valid values: 0 ~ 32 characters Type: Mandatory
	<string>	Image path and filename. Valid values: 1 ~ 64 characters Type: Mandatory
	image	Perform remote download for the software image. Type: Mandatory
	bootloader	Perform remote download for the boot loader. Type: Mandatory
	noreboot	Perform Remote Download without Reboot. Must reboot system manually for the changes to take effect! Type: Optional
	<noreboot>	Time for scheduled upgrade. (MM/DD/YYYY HH:MM:SS) Type: Optional
	cancel	Cancel scheduled upgrade. Type: Mandatory

3.3.39 system restart

Description	Restart system.	
Syntax	system restart system restart <time>	
Parameter	system restart	
	Name	Description
	<time>	Time for scheduled restart. (MM/DD/YYYY HH:MM:SS) Type: Optional

3.3.40 system restart cancel

Description	Cancel a previously-scheduled system restart.
Syntax	system restart cancel
Parameter	None

3.3.41 system dump <ip> <username> <password> <string>

Description	Dump system to a FTP server	
Syntax	system dump <ip> <username> <password> <string>	
Parameter		
	Name	Description
	<ip>	FTP server IP address Type: Mandatory
	<username>	Username Valid values: 1 ~ 32 characters Type: Mandatory
	<password>	Password Valid values: 0 ~ 32 characters Type: Mandatory
	<string>	Remote filename Valid values: 1 ~ 64 characters Type: Mandator

3.3.42 system stop ftp

Description	Stop FTP transfer
Syntax	system stop ftp
Parameter	None

3.3.43 route add <network> netmask <netmask> gateway <gateway>

Description	Add a route	
Syntax	route add <network> netmask <netmask> gateway <gateway>	
Parameter		
	Name	Description
	<network>	Destination network address. Type: Mandatory
	<netmask>	Type: Mandatory
	<gateway>	Type: Mandatory

3.3.44 route delete <network> netmask <netmask>

Description	Delete a route.	
Syntax	route delete <network> netmask <netmask>	
Parameter		
	Name	Description
	<network>	Destination network address. Type: Mandatory
	<netmask>	Type: Mandatory

3.3.45 default-gateway <default_gateway>

Description	Configure default gateway IP address.	
Syntax	default-gateway <default_gateway>	
Parameter		
	Name	Description
	<default_gateway>	Type: Mandatory

3.3.46 ip-address <ip>

Description	Configure IP address / netmask / gateway.	
Syntax	ip-address <ip> ip-address <ip> netmask <netmask> ip-address <ip> netmask <netmask> <default_gateway>	
Parameter		
	Name	Description
	<ip>	Type: Mandatory
	<netmask>	Type: Optional
	<default_gateway>	Type: Optional

3.3.47 default all

Description	Set all configurations to default.	
Syntax	default all default all except account	
Parameter		
	Name	Description
	except account	Set all configurations to default except user account. Type: Mandatory

3.3.48 list timezone

Description	List timezones.
Syntax	list timezone
Parameter	None

3.3.49 system-info contact <string>

Description	Modify system contact.	
Syntax	system-info contact <string>	
Parameter		
	Name	Description
	<string>	Valid values: 0 ~ 255 characters (ASCII code: 0x20 - 0x7E) Type: Mandatory

3.3.50 system-info location <string>

Description	Modify system location.	
Syntax	system-info location <string>	
Parameter		
	Name	Description
	<string>	Valid values: 0 ~ 255 characters (ASCII code: 0x20 - 0x7E) Type: Mandatory

3.3.51 system-info name <string>

Description	Modify system name.	
Syntax	system-info name <string>	
Parameter		
	Name	Description
	<string>	Valid values: 1 ~ 255 characters (ASCII code: 0x21 - 0x7E)

		Type: Mandatory
--	--	------------------------

3.3.52 http port {<portNo>|default}

Description	Set HTTP server port.	
Syntax	http port <portNo> http port default	
Parameter		
	Name	Description
	<portNo>	Valid values: 1 ~ 65535 Type: Mandatory
	default	Set http server port to default (80) Type: Mandatory

3.3.53 temperature shift down <time>

Description	Set downshift time.	
Syntax	temperature shift down <time>	
Parameter		
	Name	Description
	<timer>	Valid values: 1 ~ 255 seconds Type: Mandatory

3.3.54 temperature shift up <time>

Description	Set upshift time.	
Syntax	temperature shift up <time>	
Parameter		
	Name	Description
	<timer>	Valid values: 1 ~ 255 seconds Type: Mandatory

3.3.55 temperature threshold down <threshold>

Description	Set downshift temperature threshold.	
Syntax	temperature threshold down <threshold>	
Parameter		
	Name	Description
	<threshold>	Valid values: -55 ~ 85 degrees Centigrade Type: Mandatory

3.3.56 temperature threshold up <threshold>

Description	Set upshift temperature threshold.	
Syntax	temperature threshold up <threshold>	
Parameter		
	Name	Description
	<threshold>	Valid values: -55 ~ 85 degrees Centigrade Type: Mandatory

3.3.57 vlan <vlanid>

Description	Configure VLAN.	
Syntax	vlan <vlanid>	
Parameter		
	Name	Description
	<vlanid>	Create an empty VLAN index.

		Valid values: 1 ~ 4094 Type: Mandatory
--	--	---

3.3.58 vlan <vlanid> {<name> | broadcast | disable | unknown-mc | unknown-uc} {block | forward}

Description	Configure VLAN's name.	
Syntax	vlan <vlanid> {<name> broadcast disable unknown-mc unknown-uc} { block forward}	
Parameter		
	Name	Description
	<vlanid>	Create an empty VLAN index. Valid values: 1 ~ 4094 Type: Mandatory
	<name>	VLAN Name (0~31) String Size: 0~31 Type: Mandatory
	broadcast	Set storm control for broadcast packet per VLAN
	disable	Delete VLAN memberset/settting
	unknown-mc	Set storm control for unknown multicast packet per VLAN
	unknown-uc	Set storm control for unknown unicast packet per VLAN
	block	Block broadcast packet
	forward	Forward broadcast packet

3.3.59 vlan disable <vlanid>

Description	Delete VLAN memberset/setting.	
Syntax	vlan disable <vlanid>	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1 ~ 4094 Type: Mandatory

3.3.60 aging <time>

Description	Configure aging time for a bridge port.	
Syntax	aging <time>	
Parameter		
	Name	Description
	<time>	Valid values: 10 ~ 600 (seconds) Type: Mandatory

3.3.61 fdb-delete all

Description	Delete all dynamic entries from forwarding table.	
Syntax	fdb-delete all	
Parameter		
	Name	Description
	all	Delete all dynamic FDB entries. Type: Mandatory

3.3.62 fdb-delete interface gigabit <portNo>

Description	Delete Forwarding table entries per gigabit port.	
Syntax	fdb-delete interface gigabit <portNo>	
Parameter		
	Name	Description

	<portNo>	Valid values: 1~ 28 Type: Mandatory
--	----------	--

3.3.63 fdb-delete vlan <vlanid>

Description	Delete forwarding table entries per VLAN index.	
Syntax	fdb-delete vlan <vlanid>	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094 Type: Mandatory

3.3.64 fdbstatic <number> interface gigabit <portNo> <vlanid><mac>

Description	Create static MAC forwarding table entry.	
Syntax	fdbstatic <number> interface gigabit<portNo><vlanid><mac>	
Parameter		
	Name	Description
	<number>	Entry position. Valid values: 1~512 Type: Mandatory
	<portNo>	Valid values: 1~28 Type: Mandatory
	<vlanid>	Valid values: 1~4094 Type: Mandatory
	<mac>	Valid values: xx:xx:xx:xx:xx:xx Type: Mandatory

3.3.65 fdbstatic delete <number>

Description	Delete static MAC forwarding table entry.	
Syntax	fdbstatic delete <number>	
Parameter		
	Name	Description
	<number>	Valid values: 1~512 Type: Mandatory

3.3.66 fdbstatic delete all

Description	Delete all entries of static MAC forwarding table.
Syntax	fdbstatic delete all
Parameter	None

3.3.67 fdbstatic delete interface gigabit <portNo>

Description	Delete static MAC forwarding table entry per gigabit port.	
Syntax	fdbstatic delete interface gigabit <portNo>	
Parameter		
	Name	Description
	<portNo>	Valid values: 1~28 Type: Mandatory

3.3.68 fdbstatic delete vlan <vlanid>

Description	Delete static MAC forwarding table entry per VLAN index.	
Syntax	fdbstatic delete vlan <vlanid>	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094 Type: Mandatory

3.3.69 stp {disable|enable}

Description	Configure spanning tree protocol settings.	
Syntax	stp {disable enable}	
Parameter		
	Name	Description
	disable	Disable STP.
	enable	Enable STP.

3.3.70 stp bpdu {deny|flooding}

Description	Set BPDU packet filter (deny/flooding).	
Syntax	stp bpdu {deny flooding}	
Parameter		
	Name	Description
	deny	Deny BPDU packet.
	flooding	Flood BPDU packet.

3.3.71 stp forward-delay <number>

Description	Set STP forward delay time.	
Syntax	stp forward-delay <number>	
Parameter		
	Name	Description
	<number>	Valid values: 4 ~ 30 (seconds) Type: Mandatory

3.3.72 stp hello-time <number>

Description	Set STP hello time.	
Syntax	stp hello-time <number>	
Parameter		
	Name	Description
	<number>	Valid values: 1 ~ 10 (seconds) Type: Mandatory

3.3.73 stp max-age <number>

Description	Set STP max age value.	
Syntax	stp max-age <number>	
Parameter		
	Name	Description
	<number>	Valid values: 6 ~ 40 (seconds) Type: Mandatory

3.3.74 stp msti <index> { add | create | delete | set} { <vlan> | range}

Description	Set MSTP instance	
Syntax	stp msti <index> { add create delete set} { <vlan> range }	
Parameter		
	Name	Description
	<index>	MSTP instance Valid values: 1~10 Type: Mandatory
	add	Add VLAN ID to MSTP instance
	create	Create MSTP instance
	delete	Delete MSTP instance
	set	Set MSTP instance name
	<vlan>	VLAN ID Valid values: 1~4094
	range	Add multiple VLAN ID to MSTP instance

3.3.75 stp priority <number>

Description	Set STP priority.	
Syntax	stp priority <number>	
Parameter		
	Name	Description
	<number>	Valid values: 0 ~ 61440 step 4096 Type: Mandatory

3.3.76 stp region-name <name>

Description	Set STP Region Name	
Syntax	stp region-name <name>	
Parameter		
	Name	Description
	<name>	Region Name Valid values: Length 0..32 Type: Mandatory

3.3.77 stp revision <value>

Description	Set MST Revision Level	
Syntax	stp revision <value>	

Parameter		
	Name	Description
	<value>	Revision Level value Valid values: 0..65535 Type: Mandatory

3.3.78 stp version {stp|rstp|mstp}

Description	Set STP version.	
Syntax	stp version {stp rstp mstp}	
Parameter		
	Name	Description
	stp	Spanning tree protocol.
	rstp	Rapid spanning tree protocol.
	mstp	Multiple Spanning Tree Protocol

3.3.79 jumboframe {enable|disable}

Description	Set jumbo frame settings.	
Syntax	jumboframe {enable disable}	
Parameter		
	Name	Description
	enable	Enable jumbo frame.
	disable	Disable jumbo frame.

3.3.80 jumboframe mtu <value>

Description	MTU size.	
Syntax	jumboframe mtu <value>	
Parameter		
	Name	Description
	<value>	Range. Valid values: 1536~9000 (bytes) Type: Mandatory

3.3.81 cos-queue-mapping cos <priority> queue <number>

Description	Set CoS and queue mapping.	
Syntax	cos-queue-mapping cos <priority> queue < number>	
Parameter		
	Name	Description
	<priority>	Valid values: 0~7 Type: Mandatory
	<number>	Valid values: 0~7 Type: Mandatory

3.3.82 policer cos-mark green <green-number> yellow <yellow-number> red <red-number>

Description	Set ingress policer CoS remark mapping table.	
Syntax	policer cos-mark green <green-number> yellow <yellow-number> red <red-number>	
Parameter		
	Name	Description
	<green-number>	Color green and CoS number mapping. Valid values: 0~7 Type: Mandatory
	<yellow-number>	Color yellow and CoS number mapping. Valid values: 0~7 Type: Mandatory
	<red-number>	Color red and CoS number mapping. Valid values: 0~7 Type: Mandatory

3.3.83 policer dscp-mark green <green-number> yellow <yellow-number> red <red-number>

Description	Set ingress policer DSCP remark mapping table.	
Syntax	policer dscp-mark green <green-number> yellow <yellow-number> red <red-number>	
Parameter		
	Name	Description
	<green-number>	Color green and DSCP number mapping. Valid values: 0~63 Type: Mandatory
	<yellow-number>	Color yellow and DSCP number mapping. Valid values: 0~63 Type: Mandatory
	<red-number>	Color red and DSCP number mapping. Valid values: 0~63 Type: Mandatory

3.3.84 policer ingress-color {aware|blind}

Description	Enable/Disable ingress-color function.	
Syntax	policer ingress-color {aware blind}	
Parameter		
	Name	Description
	aware	Enable ingress color function.
	blind	Disable ingress color function.

3.3.85 policer ingress-color cos <number> {red|yellow|green}

Description	Set ingress-color mapping table.	
Syntax	policer ingress-color cos <number> {green yellow red}	
Parameter		
	Name	Description
	<number>	Valid values: 0~7 Type: Mandatory
	green yellow red	Green or yellow or red. Type: Mandatory

3.3.86 mirror analyzer-port {enable|disable}

Description	Enable/Disable analyzer port configuration.	
Syntax	mirror analyzer-port {enable disable}	
Parameter	None	
	Name	Description
	enable	Enable port mirror.
	disable	Disable port mirror.

3.3.87 mirror analyzer-port <portNo>

Description	Set analyzer port.	
Syntax	mirror analyzer-port <portNo>	
Parameter		
	Name	Description
	<portNo>	Valid values: 1~28 Type: Mandatory

3.3.88 vlan <vlanid> unknown-uc {block|forward}

Description	Block/ Forward unknown unicast packet per VLAN.	
Syntax	vlan <vlanid> unknown-uc block vlan <vlanid> unknown-uc forward	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094 Type: Mandatory

3.3.89 vlan <vlanid> unknown-mc {block|forward}

Description	Block/Forward unknown multicast packet per VLAN.	
Syntax	vlan <vlanid> unknown-mc block vlan <vlanid> unknown-mc forward	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094 Type: Mandatory

3.3.90 vlan <vlanid> broadcast {block|forward}

Description	Block/Forward broadcast packet per VLAN.	
Syntax	vlan <vlanid> broadcast block vlan <vlanid> broadcast forward	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094 Type: Mandatory

3.3.91 port-mirror monitor-port <portNo>

Description	Set the gigabit port to be monitored.	
Syntax	port-mirror monitor-port <portNo>	
Parameter		
	Name	Description
	<portNo>	Valid values: 1~28 Type: Mandatory

3.3.92 port-mirror {enable|disable}

Description	Enable/Disable port mirror.
Syntax	port-mirror enable port-mirror disable
Parameter	None

3.3.93 port-mirror {tx-analyzer-port|rx-analyzer-port} <portNo>

Description	Set Tx analyzer port (monitor 'out' packet of monitored port)/Rx analyzer port (monitor 'in' packet of monitored port).	
Syntax	port-mirror tx-analyzer-port <portNo> port-mirror rx-analyzer-port <portNo>	
Parameter		
	Name	Description
	<portNo>	Valid values: 1~28 Type: Mandatory

3.3.94 counter interface-counter clear <portNo>

Description	Clear interface counter per gigabit port.	
Syntax	counter interface-counter clear <portNo>	
Parameter		
	Name	Description
	<portNo>	Valid values: 1~28. Type: Mandatory

3.3.95 counter rmon-counter clear <portNo>

Description	Clear Ethernet counter per gigabit port.	
Syntax	counter rmon-counter clear <portNo>	
Parameter		
	Name	Description
	<portNo>	Valid values: 1~28. Type: Mandatory

3.3.96 multicast-fdb delete all

Description	Delete multicast forwarding table.	
Syntax	multicast-fdb delete all multicast-fdb delete vlan <vlanid> multicast-fdb delete interface gigabit <portNo>	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094. Type: Mandatory
	<portNo>	Valid values: 1~28. Type: Mandatory

3.3.97 multicast-fdb static delete

Description	Delete static multicast forwarding table.	
Syntax	multicast-fdb static delete <number> multicast-fdb static delete all multicast-fdb static delete vlan <vlanid> multicast-fdb static delete interface gigabit <portNo>	
Parameter		
	Name	Description
	<number>	Static multicast forwarding table entry index. Valid values: 1~128 Type: Mandatory
	<vlanid>	Valid values: 1~4094. Type: Mandatory
	<portNo>	Valid values: 1~28. Type: Mandatory

3.3.98 multicast-fdb static <number> interface gigabit <portNo> <vlan> <ipaddr>

Description	Create static IGMP VLAN forwarding table entry.	
Syntax	multicast-fdb static <number> interface gigabit <portNo> <vlan> <ipaddr>	
Parameter		
	Name	Description
	<number>	Static multicast forwarding table entry index. Valid values: 1~128 Type: Mandatory
	<portNo>	Valid values: 1~28. Type: Mandatory
	<vlanid>	Valid values: 1~4094. Type: Mandatory
	<ipaddr>	IGMP VLAN group IP address. Valid values: 224.0.0.0~239.255.255.255 Type: Mandatory

3.3.99 ring-group <number>

Description	Entry ring group interface	
Syntax	ring-group <number>	
Parameter		
	Name	Description
	<number>	Ring group index Valid values: 1~3 Type: Mandatory

3.3.100 ext-tpid <number>

Description	Set tpid.	
Syntax	ext-tpid <number>	
Parameter		
	Name	Description
	<number>	tpid Valid values: 0x0001~0xffff Type: Mandatory

3.3.101 profile igmp-mvr

Description	Entry IGMP MVR interface.
Syntax	profile igmp-mvr
Parameter	None

3.3.102 profile igmp-acl

Description	Entry IGMP ACL interface.
Syntax	profile igmp-acl
Parameter	None

3.3.103 dot1x {enable|disable}

Description	Enable / disable dot1x.
Syntax	dot1x {enable disable}
Parameter	None

3.3.104 dot1x radius set <ip> <auth_port> <secret>

Description	Set dot1x parameters.	
Syntax	dot1x radius set <ip> <auth_port> <secret>	
Parameter		
	Name	Description
	<ip>	IP address. Format : 0.0.0.0 ~ 255.255.255.255 Type : Mandatory
	<auth_port>	Authentication port. Valid values : 1 ~ 65535 Default values : 1812 Type : Mandatory
	<secret>	Authentication key. Length : 1 ~ 16 Type : Mandatory

3.3.105 dot1x clear eapol-stats {<portNo>|all}

Description	Clear dot1x EAPOL stats.	
Syntax	dot1x clear eapol-stats {<portNo> all}	
Parameter		
	Name	Description
	<portNo>	Gigabit port. Valid values : 1 ~ 28 Type : Mandatory

3.3.106 dot1x clear dot1x-radius-stats

Description	Clear dot1x radius-stats
Syntax	dot1x clear dot1x-radius-stats
Parameter	None

3.3.107 https {enable|disable}

Description	Enable/Disable https.
Syntax	https {enable disable}
Parameter	None

3.3.108 https port {<portNo>|default}

Description	Set https port by specific port or default port.	
Syntax	https port {<portNo> default}	
Parameter		
	<portNo>	https port number. Valid values : 1 ~ 65535 Type : Mandatory
	default	https default port number is 443. Type : Mandatory

3.3.109 interface trunk-group <number>

Description	Enter trunk group configure mode.	
Syntax	interface trunk-group <number>	
Parameter		
	<number>	Trunk group index. Valid values: 1 ~ 2 Type: Mandatory

3.3.110 fdb-delete interface trunk-group <number>

Description	Delete forwarding table per trunk group.	
Syntax	fdb-delete interface trunk-group <number>	
Parameter		
	<number>	Trunk group index. Valid values: 1 ~ 2 Type: Mandatory

3.3.111 ssl default-certificate

Description	Use system default SSL certificate	
Syntax	ssl default-certificate	
Parameter	None	

3.3.112 ssl upload

Description	Upload new SSL certificate	
Syntax	ssl upload	
Parameter	None	

3.4 Interface gigabit Mode Commands

3.4.1 accfrm

Description	Set acceptable frame type.	
Syntax	Accfrm{all tag untag}	
Parameter		
	Name	Description
	all	Accept all frames.
	tag	Accept tagged frame only.
	untag	Accept un-tagged frame only.

3.4.2 priority <priority>

Description	Set user priority for the gigabit port.	
Syntax	priority <priority>	
Parameter		
	Name	Description
	<priority>	Valid values: 0 ~ 7 Type: Mandatory

3.4.3 vlan <vlanid>

Description	Join VLAN with default setting (tagged).	
Syntax	vlan <vlanid>	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094 Type: Mandatory

3.4.4 vlan <vlanid> disable

Description	Leave joined VLAN.	
Syntax	vlan <vlanid> disable	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094 Type: Mandatory
	disable	Leave joined VLAN

3.4.5 vlan <vlanid> tag

Description	Join tagged VLAN.	
Syntax	vlan <vlanid> tag	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094 Type: Mandatory
	tag	Join Tagged VLAN

3.4.6 vlan <vlanid> untag

Description	Join untagged VLAN.	
Syntax	vlan <vlanid> untag	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1~4094

		Type: Mandatory
	untag	Join Untagged VLAN

3.4.7 stpport {disable|enable}

Description	Configure STP port.	
Syntax	stpport {disable enable}	
Parameter		
	Name	Description
	disable	Disable STP port.
	enable	Enable STP port.

3.4.8 stpport cost <number>

Description	Set STP port path cost.	
Syntax	stpport cost <number>	
Parameter		
	Name	Description
	<number>	Valid values: 1 ~ 200000000 Type: Mandatory

3.4.9 stpport edge-port {enable|disable}

Description	Set STP port edge-type.	
Syntax	stpport edge-port {enable disable}	
Parameter		
	Name	Description
	enable	Set as edge-type.
	disable	Set as none edge-type.

3.4.10 stpport priority <number>

Description	Set STP port priority.	
Syntax	stpport priority <number>	
Parameter		
	Name	Description
	<number>	Valid values: 0~240 step 16 Type: Mandatory

3.4.11 flow-control {enable|disable}

Description	Enable/Disable flow-control.	
Syntax	flow-control {enable disable}	
Parameter		
	Name	Description
	enable	Enable flow-control.
	disable	Disable flow-control.

3.4.12 speed

Description	Configure copper port Ethernet speed.	
Syntax	speed {auto full-1000mbps full-100mbps full-10mbps half-100mbps half-10mbps}	
Parameter		
	Name	Description
	auto	Auto negotiation.
	full-1000mbps	Set 1000Mbps full duplexing.
	full-100mbps	Set 100Mbps full duplexing.
	full-10mbps	Set 10Mbps full duplexing.
	half-100mbps	Set 100Mbps half duplexing.
	half-10mbps	Set 10Mbps half duplexing.

3.4.13 sfp-speed (for 10G ports)

Description	Configure 10G fiber port Ethernet speed.	
Syntax	speed {auto full-1000mbps full-10Gbps}	
Parameter		
	Name	Description
	auto	Auto negotiation.
	full-1000mbps	Set 1000Mbps full duplexing.
	full-10Gbps	Set 10Gbps full duplexing.

3.4.14 sfp-speed (for 1G ports)

Description	Configure fiber port Ethernet speed.	
Syntax	speed {auto full-1000mbps full-100mbps full-2500mbps}	
Parameter		
	Name	Description
	auto	Auto negotiation.
	full-1000mbps	Set 1000Mbps full duplexing.
	full-100mbps	Set 100Mbps full duplexing.

3.4.15 port {enable/disable}

Description	Set interface gigabit port enable or disable.	
Syntax	port {enable/disable}	
Parameter		
	Name	Description
	disable	Turn off gigabit port.
	enable	Turn off gigabit port.

3.4.16 default vlan

Description	Set default VLAN to gigabit port.	
Syntax	default vlan <vlanid>	
Parameter		
	Name	Description
	<vlanid>	Valid values: 1 ~ 4094 Type: Mandatory

3.4.17 policer pir <pir-rate> pbs <pbs-size> cir <cir-rate> cbs <cbs-size> {drop|cos|dscp}

Description	Set ingress policer parameters.	
Syntax	policer pir <pir-rate> pbs <pbs-size> cir <cir-rate> cbs <cbs-size> {drop cos dscp}	
Parameter		
	Name	Description
	<pir-rate>	Ingress total max rate setting. Valid values: 1~1000000 Type: Mandatory
	<pbs-size>	Ingress queue size setting. Valid values: 1~65535 Type: Mandatory
	<cir-rate>	Ingress max rate for first stage setting. Valid values: 1~1000000 Type: Mandatory
	<cbs-size>	Ingress max rate for second stage setting. Valid values: 1~65535 Type: Mandatory
	{drop cos dscp}	Policer type Type: Mandatory

3.4.18 policer disable

Description	Disable policer function.
Syntax	policer disable
Parameter	None

3.4.19 acl-profile-bind <number>

Description	Port ACL profile binding.	
Syntax	acl-profile-bind <number>	
Parameter		
	Name	Description
	<number>	Valid values: 1~10 Type: Mandatory

3.4.20 def-acl {permit|deny}

Description	Set port default ACL rule.
Syntax	def-acl permit def-acl deny
Parameter	None

3.4.21 queue-scheduler bind <number>

Description	Scheduler profile binding.	
Syntax	queue-scheduler bind <number>	
Parameter		
	Name	Description
	<number>	Scheduler profile index. Valid values: 1~8 Type: Mandatory

3.4.22 port-shaper {enable|disable}

Description	Enable/Disable port shaper.
Syntax	port-shaper {enable disable}
Parameter	None

3.4.23 port-shaper <rate>

Description	Set port shaper rate.	
Syntax	port-shaper <rate>	
Parameter		
	Name	Description
	<rate>	Valid values: 1~1000000 Type: Mandatory

3.4.24 queue-shaper {enable|disable}

Description	Enable/Disable queue shaper.
Syntax	queue-shaper {enable disable}
Parameter	None

3.4.25 queue-shaper queue <number> <rate>

Description	Set queue shaper parameters.	
Syntax	queue-shaper queue <number> <rate>	
Parameter		
	Name	Description
	<number>	Valid values: 0~7 Type: Mandatory
	<rate>	Valid values: 1~1000000 Type: Mandatory

3.4.26 port-isolation <portNo>

Description	Enable/Disabled port-isolation action.	
Syntax	port-isolation <portNo> port-isolation <portNo> disable	
Parameter		
	Name	Description
	<portNo>	Valid values: 1~28 Type: Mandatory

3.4.27 unknown-uc rate <rate>

Description	Set storm rate for unknown unicast packet.	
Syntax	unknown-uc rate <rate>	
Parameter		
	Name	Description
	<rate>	Valid values: 1~1000000 (Kbps) Type: Mandatory

3.4.28 unknown-uc {block|forward}

Description	Block/ Forward unknown unicast packet.
Syntax	unknown-uc block unknown-uc forward
Parameter	None

3.4.29 unknown-mc rate <rate>

Description	Set storm rate for unknown multicast packet.	
Syntax	unknown-mc rate <rate>	
Parameter		
	Name	Description
	<rate>	Valid values: 1~1000000 (Kbps) Type: Mandatory

3.4.30 unknown-mc {block|forward}

Description	Block/Forward unknown multicast packet.
Syntax	unknown-mc block unknown-mc forward
Parameter	None

3.4.31 broadcast rate <rate>

Description	Set storm rate for broadcast packet.	
Syntax	broadcast rate <rate>	
Parameter		
	Name	Description
	<rate>	Valid values: 1~1000000 (Kbps) Type: Mandatory

3.4.32 broadcast {block|forward}

Description	Block/Forward broadcast packet.
Syntax	broadcast block broadcast forward
Parameter	None

3.4.33 vlan-stack {enable|disable}

Description	Enable/disable vlan stack.
Syntax	vlan-stack {enable disable}
Parameter	None

3.4.34 protocol-vlan <number> create <ether-type> <svlan> <s-prio>

Description	Create protocol VLAN.	
Syntax	protocol-vlan <number> create <ether-type> <svlan> <s-prio>	
Parameter		
	Name	Description
	<number>	Protocol VLAN index. Valid values: 1 ~ 20 Type: Mandatory
	<ether-type>	Ether type. Valid values: 0 ~ FFFF,(hex) Type: Mandatory
	<svlan>	Service VLAN (SVALN). Valid values: 1 ~ 4094 Type: Mandatory
	<s-prio>	CoS of SVLAN. Valid values: 0 ~ 8 Type: Mandatory

3.4.35 protocol-vlan <number> delete

Description	Delete protocol VLAN.	
Syntax	protocol-vlan <number> delete	
Parameter		
	Name	Description
	<number>	Protocol VLAN index. Valid values: 1 ~ 20 Type: Mandatory

3.4.36 vlan-trans <number> create <cvlan> <c-prio> <svlan> <s-prio> many-to-

Description	Create VLAN translation.	
Syntax	vlan-trans <number> create <cvlan> <c-prio> <svlan> <s-prio> many-to-one-replaced	
Parameter		
	Name	Description
	<number>	VLAN translation index. Valid values: 1 ~ 20 Type: Mandatory
	<cvlan>	Customer VLAN (CVLAN). Valid values: 1 ~ 4094 Type: Mandatory
	<c-prio>	CoS of VLAN. Valid values: 0 ~ 8 Type: Mandatory
	<svlan>	Service VLAN (SVLAN). Valid values: 1 ~ 4094 Type: Mandatory
	<s-prio>	CoS of SVLAN. Valid values: 0 ~ 8 Type: Mandatory

3.4.37 vlan-trans <number> delete

Description	Delete VLAN translation.	
Syntax	vlan-trans <number> delete	
Parameter		
	Name	Description
	<number>	VLAN translation index. Valid values: 1 ~ 20 Type: Mandatory

3.4.38 igmp mvrprofile <index>

Description	Binding IGMP MVR profile to specified port.	
Syntax	igmp mvrprofile <index>	
Parameter		
	Name	Description
	<index>	IGMP MVR index. Valid values: 1 ~ 15 Type: Mandatory

3.4.39 igmp aclprofile <index>

Description	Binding IGMP ACL profile to specified port.	
Syntax	igmp aclprofile <index>	
Parameter		
	Name	Description
	<index>	IGMP ACL index. Valid values: 1 ~ 15 Type: Mandatory

3.4.40 igmp max-channel <number>

Description	Set max channel to specified port.	
Syntax	igmp max-channel <number>	
Parameter		
	Name	Description
	<number>	Max channel number. Valid values: 1 ~ 512 Type: Mandatory

3.4.41 dot1x {force-reinitialize| force-reauthenticate}

Description	Enable for force PAE port re-initialize / re-authenticate.
Syntax	dot1x {force-reinitialize force-reauthenticate}
Parameter	None

3.4.42 dot1x auth-port-control {auto| force-authorized| force-unauthorized}

Description	Set dot1x authentication type of PAE port.
Syntax	dot1x auth-port-control {auto force-authorized force-unauthorized}
Parameter	None

3.4.43 dot1x auth-quiet-period <period>

Description	Set quiet period of PAE port	
Syntax	dot1x auth-quiet-period <period>	
Parameter		
	Name	Description
	<period>	The quiet period of PAE port Valid values: 1 ~ 255 seconds. Default values: 60 seconds Type: Mandatory

3.4.44 dot1x auth-tx-period <period>

Description	Set timeout of authenticator waiting for EAP-Response / Identity from supplication of PAE port	
Syntax	dot1x auth-tx-period <period>	
Parameter		
	Name	Description
	<period>	The quiet period of PAE port Valid values: 1 ~ 255 seconds. Default values: 30 seconds Type: Mandatory

3.4.45 dot1x max-req <number>

Description	Set max times of backend Authenticator send EAP-Request to supplicant before restarting the authentication process.	
Syntax	dot1x max-req <number>	
Parameter		
	Name	Description
	<number>	Max request number. Valid values: 1 ~ 10. Default values: 2 Type: Mandatory

3.4.46 dot1x auth-supp-timeout <timeout>

Description	Set timeout of authenticator wait for EAP-Response(exclude EAP-Request / Identify) after sending EAP-Request.	
Syntax	dot1x auth-supp-timeout <timeout>	
Parameter		
	Name	Description
	<timeout>	Authenticator timeout. Valid values: 1 ~ 255 seconds. Default values: 30 seconds Type: Mandatory

3.4.47 dot1x auth-server-timeout <timeout>

Description	Set timeout of Authenticator wait Access-Challenge / Access-Accept / Access-Reject after sending Access-Request	
Syntax	dot1x auth-server-timeout <timeout>	
Parameter		
	Name	Description
	<timeout>	Authenticator timeout. Valid values: 1 ~ 255 seconds. Default values: 30 seconds Type: Mandatory

3.4.48 dot1x reauth {enable|disable}

Description	Enable/Disable re-authentication of APE port
Syntax	dot1x reauth {enable disable}
Parameter	None

3.4.49 dot1x reauth-period <period>

Description	period of re-authentication of PAE port	
Syntax	dot1x reauth-period <period>	
Parameter		
	Name	Description
	<period>	Period of re-authentication. Valid values: 1 ~ 3600 seconds. Default values: 3600 seconds Type: Mandatory

3.5 Acl-profile Configure Mode Commands

3.5.1 acl-profile <number> {create|delete}

Description	Create/Delete ACL profile.	
Syntax	acl-profile <number> {create delete}	
Parameter		
	Name	Description
	<number>	Valid values: 2~10 Type: Mandatory
	create delete	Type: Mandatory

3.5.2 acl-profile <prof-number> {create|delete} entry <entry-number>

Description	Create/Delete ACL profile entry.	
Syntax	acl-profile <prof-number> create entry <entry-number> acl-profile <prof-number> delete entry <entry-number>	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory

3.5.3 acl-profile <prof-number> set name <name>

Description	Set ACL profile name.	
Syntax	acl-profile <prof-number> set name <name>	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<name>	Valid Length: 1~31 Type: Mandatory

3.5.4 acl-profile <prof-number> set entry <entry-number> mac-type set vlan <vlanid>

Description	Set VLAN index for ACL MAC type entry.	
Syntax	acl-profile <prof-number> set entry <entry-number> mac-type set vlan <vlanid>	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory
	<vlanid>	Valid values: 1~4094 Type: Mandatory

3.5.5 acl-profile <prof-number> set entry <enrty-number> mac-type set vlan any

Description	Set VLAN index for ACL MAC type entry.	
Syntax	acl-profile <prof-number> set entry <enrty-number> mac-type set vlan any	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory

3.5.6 acl-profile <prof-number> set entry <entry-number> mac-type set {srcmac|dstmac} <mac> <mask>

Description	Set MAC for ACL MAC type entry.	
Syntax	acl-profile <prof-number> set entry <entry-number> mac-type set {srcmac dstmac} <mac> <mask>	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory
	srcmac dstmac	Source / Destination MAC Address Type: Mandatory
	<mac>	Valid values: 00:00:00:00:00:00 ~ FF:FF:FF:FF:FF:FF Type: Mandatory
	<mask>	Valid values: 00:00:00:00:00:00 ~ FF:FF:FF:FF:FF:FF Type: Mandatory

3.5.7 acl-profile <prof-number> set entry <entry-number> mac-type set ethertype <ethertype>

Description	Set ether type for ACL MAC type entry.	
Syntax	acl-profile <prof-number> set entry <entry-number> mac-type set ethertype <ethertype>	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory
	<ethertype>	Valid values: 0x0001~0xFFFF Type: Mandatory

3.5.8 acl-profile <prof-number> set entry <entry-number> mac-type set ethertype any

Description	Set ether type for ACL MAC type entry.	
Syntax	acl-profile <prof-number> set entry <entry-number> mac-type set ethertype any	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory

3.5.9 acl-profile <prof-number> set entry <entry-number> ipv4-type set {srcip|dstip} <ipaddr> <mask>

Description	Set IP for ACL IPv4 type entry.	
Syntax	acl-profile <prof-number> set entry <entry-number> ipv4-type set {srcip dstip} <ipaddr> <mask>	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory
	srcip dstip	Source / Destination IP Address Type: Mandatory
	<ipaddr>	Valid values: 0.0.0.0 ~ 255.255.255.255 Type: Mandatory
	<mask>	Valid values: 0.0.0.0 ~ 255.255.255.255 Type: Mandatory

3.5.10 acl-profile <prof-number> set entry <entry-number> ipv4-type set ip-protocol <protocol-id>

Description	Set protocol for ACL IPv4 type entry.	
Syntax	acl-profile <prof-number> set entry <entry-number> ipv4-type set ip-protocol <protocol-id>	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory
	<protocol-id>	Valid values: 1~255 Type: Mandatory

3.5.11 acl-profile <prof-number> set entry <entry-number> ipv4-type set ip-protocol any

Description	Set protocol for ACL IPv4 type entry.	
Syntax	acl-profile <prof-number> set entry <entry-number> ipv4-type set ip-protocol any	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory

3.5.12 acl-profile <prof-number> set entry <entry-number> l4port-type set protocol {tcp|udp}

Description	Set protocol for ACL L4Port type entry.	
Syntax	acl-profile <prof-number> set entry <entry-number> l4port-type set protocol {tcp udp}	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory
	tcp udp	TCP or UDP packet. Type: Mandatory

3.5.13 acl-profile <prof-number> set entry <entry-number> l4port-type set {srcip|dstip} <ipaddr> <mask>

Description	Set IP for ACL L4Port type entry.	
Syntax	acl-profile <prof-number> set entry <entry-number> l4port-type set {srcip dstip} <ipaddr> <mask>	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory
	srcip dstip	Source / Destination IP Address Type: Mandatory
	<ipaddr>	Valid values: 0.0.0.0 ~ 255.255.255.255 Type: Mandatory
	<mask>	Valid values: 0.0.0.0 ~ 255.255.255.255 Type: Mandatory

3.5.14 acl-profile <prof-number> set entry <entry-number> l4port-type set {srcport|dstport} <number>

Description	Set port for ACL L4Port type entry.	
Syntax	acl-profile <prof-number> set entry <entry-number> l4port-type set {srcport dstport} <number>	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory
	srcport dstport	Source / Destination port Type: Mandatory
	<number>	Valid values: 1~65535 Type: Mandatory

3.5.15 acl-profile <prof-number> set entry <entry-number> l4port-type set {srcport|dstport} any

Description	Set port for ACL L4Port type entry.	
Syntax	acl-profile <prof-number> set entry <entry-number> l4port-type set {srcport dstport} any	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory
	srcport dstport	Source / Destination port. Type: Mandatory

3.5.16 acl-profile <prof-number> set entry <entry-number> tos-type set {srcip|dstip} <ipaddr> <mask>

Description	Set IP for ACL ToS type entry.	
Syntax	acl-profile <prof-number> set entry <entry-number> tos-type set {srcip dstip} <ipaddr> <mask>	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory
	srcip dstip	Source / Destination IP Address Type: Mandatory
	<ipaddr>	Valid values: 0.0.0.0 ~ 255.255.255.255 Type: Mandatory
	<mask>	Valid values: 0.0.0.0 ~ 255.255.255.255 Type: Mandatory

3.5.17 acl-profile <prof-number> set entry <entry -number> tos-type set type {precedence|tos|dscp } <number>

Description	Set type for ACL ToS type entry.	
Syntax	acl-profile <prof-number> set entry <entry -number> tos-type set type {precedence tos dscp } <number>	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory
	precedence tos dscp	Precedence or ToS or DSCP Type. Type: Mandatory
	<number>	Precedence type. Valid values: 0~7 Tos type. Valid values: 0~15 DSCP type. Valid values: 0~63 Type: Mandatory

3.5.18 acl-profile <prof-number> set entry <entry-number> tos-type set type any

Description	Set type for ACL ToS type entry.	
Syntax	acl-profile <prof-number> set entry <entry-number> tos-type set type any	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory

3.5.19 acl-profile <prof-number> set entry <entry-number> action forwarding {deny|permit}

Description	Set ACL entry action is forwarding.	
Syntax	acl-profile <prof-number> set entry <entry-number> action forwarding {deny permit}	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory
	deny permit	Deny or Permit forwarding. Type: Mandatory

3.5.20 acl-profile <prof-number> set entry <entry-number> action queue <number>

Description	Set ACL entry action to specific queue number.	
Syntax	acl-profile <prof-number> set entry <entry-number> action queue <number>	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory
	<number>	Valid values: 0~7 Type: Mandatory

3.5.21 acl-profile <prof-number> set entry <entry-number> action cos <number>

Description	Set ACL entry action is mark CoS number.	
Syntax	acl-profile <prof-number> set entry <entry-number> action cos <number>	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory
	<number>	Valid values: 0~7 Type: Mandatory

3.5.22 acl-profile <prof-number> set entry <entry-number> action copyframe

Description	Set ACL entry action is copy frame.	
Syntax	acl-profile <prof-number> set entry <entry-number> action copyframe	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~10 Type: Mandatory
	<entry-number>	Valid values: 1~16 Type: Mandatory

3.6 Sch-profile Configure Mode Commands

3.6.1 scheduler-profile <number> method {spq|spq-wrr|wrr}

Description	Set scheduler profile method.	
Syntax	scheduler-profile <number> method {spq spq-wrr wrr}	
Parameter		
	Name	Description
	<number>	Scheduler profile index. Valid values: 2~8 Type: Mandatory
	sp sp-wrr wrr	sp: strict priority sp-wrr: strict priority + weighted round robin wrr: weighted round robin Type: Mandatory

3.6.2 scheduler-profile <prof-number> queue <queue-number> weight <number>

Description	Set scheduler profile queue weight.	
Syntax	scheduler-profile <prof-number> queue <queue-number> weight <number>	
Parameter		
	Name	Description
	<prof-number>	Valid values: 2~8 Type: Mandatory
	<queue-number>	Valid values: 0~7 Type: Mandatory
	<number>	Valid values: 1~255 Type: Mandatory

3.7 SNMP Configure Mode Commands

3.7.1 snmp <index> notify <name>

Description	Configure snmp notify	
Syntax	snmp <index> notify <name>	
Parameter		
	Name	Description
	<index>	Index. Valid values: 1~32 Type: Mandatory
	notify	Configure snmp notify Type: Mandatory
	<name>	Notify name Valid values: 1 ~ 31 characters Type: Mandatory

3.7.2 snmp <index> notify delete

Description	Configure snmp notify	
Syntax	snmp <index> notify <name>	
Parameter		
	Name	Description
	<index>	Index. Valid values: 1~32 Type: Mandatory
	notify	Configure snmp notify Type: Mandatory
	delete	Delete a snmp target Type: Mandatory

3.7.3 snmp <index> target <ip>

Description	Configure snmp target	
Syntax	snmp <index> target	
Parameter		
	Name	Description
	<index>	Scheduler profile index. Valid values: 1~32 Type: Mandatory
	target	Configure snmp target Type: Mandatory
	<ip>	Target IP address Type: Mandatory

3.7.4 snmp <index> target delete

Description	Delete a snmp target	
Syntax	snmp <index> target	
Parameter		
	Name	Description
	<index>	Scheduler profile index. Valid values: 1~32 Type: Mandatory
	target	Configure snmp target Type: Mandatory
	delete	Delete a snmp target

	Type: Mandatory
--	------------------------

3.7.5 snmp community <name> group <name>

Description	Config snmp community	
Syntax	snmp community <name> group <name>	
Parameter		
	Name	Description
	<name>	Community name. Valid values: 1 ~ 31 characters Type: Mandatory
	group	Config a community to bind with a group Type: Mandatory
	<name>	Group name Valid values: (1 ~ 15 characters) (input 'none' to unbind) Type: Mandatory

3.7.6 snmp community <name> ro

Description	Config snmp community	
Syntax	snmp community <name> ro	
Parameter		
	Name	Description
	<name>	Community name. Valid values: 1 ~ 31 characters Type: Mandatory
	ro	Config a community access right as read-only Type: Mandatory

3.7.7 snmp community <name> rw

Description	Config snmp community	
Syntax	snmp community <name> rw	
Parameter		
	Name	Description
	<name>	Community name. Valid values: 1 ~ 31 characters Type: Mandatory
	rw	Config a community access right as read-write Type: Mandatory

3.7.8 snmp community <name> view <name>

Description	Config snmp community	
Syntax	snmp community <name> view <name>	
Parameter		
	Name	Description
	<name>	Community name. Valid values: 1 ~ 31 characters Type: Mandatory
	view	Config a community to bind with a group Type: Mandatory
	<name>	Group name Valid values: (1 ~ 15 characters) (input 'none' to unbind) Type: Mandatory

3.7.9 snmp create-community {ro | rw} <name> {view | group} <name>

Description	Create snmp community	
Syntax	snmp create-community {ro rw} <name> {view group} <name>	
Parameter		
	Name	Description
	ro	Create a snmp community (read only) Type: Mandatory
	rw	Create a snmp community (read,write) Type: Mandatory
	<name>	Community name Valid values: 1 ~ 31 characters Type: Mandatory
	view	Create a snmp community (read only) and bind it with a view Type: Mandatory
	group	Create a snmp community (read only) and bind it with a group Type: Mandatory
	<name>	Group name Valid values: 1 ~ 15 characters Type: Mandatory

3.7.10 snmp create-group <name> model {v1 | v2 | v3sum} level {auth | noauth | priv} read <name> write <name>

Description	Create snmp v3 access group	
Syntax	snmp create-group <name> model {v1 v2 v3sum} level {auth noauth priv} read <name> write <name>	
Parameter		
	Name	Description
	<name>	Group name Valid values: 1 ~ 15 characters Type: Mandatory
	model	Security model of the group (v1/v2c/v3) Type: Mandatory
	v1	SNMP v1 security model
	v2c	SNMP v2c security model
	v3usm	SNMP v3 security model
	level	Security level of the group (noauth/auth/priv) Type: Mandatory
	auth	Authentication, but no privacy
	noauth	No authentication, no privacy
	priv	Both authentication and privacy
	read	Specify a read view to this group
	<name>	View name Valid values: 1 ~ 15 characters Type: Mandatory
	write	Specify a write view to this group
	<name>	View name Valid values: 1 ~ 15 characters Type: Mandatory

3.7.11 snmp create-user {access | group} {ro | rw} {md5 | sha} <passPhrase> des <passPhrase>

Description	Create snmp v3 user
--------------------	---------------------

Syntax	snmp create-user <name> {access group} {ro rw} {md5 sha} <passPhrase> des <passPhrase>	
Parameter		
	Name	Description
	<name>	User name Valid values: 1 ~ 31 characters Type: Mandatory
	access	Access right of user (ro/rw) Type: Mandatory
	group	Bind user to a group Type: Mandatory
	ro	Read-only user
	rw	Read-write user
	md5	Use MD5 as authentication protocol
	sha	Use SHA as authentication protocol
	<passPhrase>	Authentication pass phrase Valid values: 8 ~ 15 characters Type: Mandatory
	des	Use DES as encryption protocol
	<passPhrase>	Encryption pass phrase Valid values: 8 ~ 15 characters Type: Mandatory

3.7.12 snmp create-view <name> type { exclude | include} subtree <subtree>

Description	Create snmp v3 access view	
Syntax	snmp create-view <name> type { exclude include} subtree <subtree>	
Parameter		
	Name	Description
	<name>	View name Valid values: 1 ~ 15 characters Type: Mandatory
	type	View type of the subtree Type: Mandatory
	exclude	Exclude the subtree
	include	Include the subtree
	subtree	Set subtree(oid or name) of a view Type: Mandatory
	<subtree>	Subtree, oid or name Valid values: 1 ~ 31 characters Type: Mandatory

3.7.13 snmp delete-community <name>

Description	Delete snmp community	
Syntax	snmp delete-community name	
Parameter		
	Name	Description
	name	Delete snmp community Type: Mandatory

3.7.14 snmp delete-group <name>

Description	Delete snmp v3 group	
Syntax	snmp delete-group name	
Parameter		
	Name	Description

	name	Delete snmp v3 group Type: Mandatory
--	------	--

3.7.15 snmp delete-user name

Description	Delete snmp v3 user	
Syntax	snmp delete-user name	
Parameter		
	Name	Description
	name	Delete snmp v3 user Type: Mandatory

3.7.16 snmp delete-view { index | name }

Description	Delete snmp v3 access view	
Syntax	snmp delete-view { index name }	
Parameter		
	Name	Description
	index	Delete snmp v3 view Type: Mandatory
	name	Delete snmp v3 view Type: Mandatory

3.7.17 snmp version { v2c | v3 }

Description	Config snmp version (v2c/v3)	
Syntax	snmp version { v2c v3 }	
Parameter		
	Name	Description
	v2c	Set snmp version to v2c
	v3	Set snmp version to v3

3.8 Interface VLAN Mode Commands

3.8.1 igmp vlan {create|delete}

Description	Create / Delete IGMP.
Syntax	igmp vlan create igmp vlan delete
Parameter	None

3.8.2 igmp router-port <portNo>

Description	Set IGMP VLAN source port.	
Syntax	igmp router-port <portNo>	
Parameter		
	Name	Description
	<portNo>	Valid values: 1~28. Type: Mandatory

3.8.3 igmp access-mode {snooping|proxy}

Description	Set IGMP VLAN access mode.
Syntax	igmp access-mode snooping igmp access-mode proxy
Parameter	None

3.8.4 igmp leave-mode {normal|fast}

Description	Set IGMP VLAN leave mode.
Syntax	igmp leave-mode normal igmp leave-mode fast
Parameter	None

3.8.5 igmp version {v2|v3|v3compatible}

Description	Set IGMP VLAN version.
Syntax	igmp version v2 igmp version v3 igmp version v3compatible
Parameter	None

3.8.6 igmp robustness <number>

Description	Set IGMP VLAN robustness.	
Syntax	igmp robustness <number>	
Parameter		
	Name	Description
	<number>	Valid values: 1~3. Type: Mandatory

3.8.7 igmp query-interval <number>

Description	Set IGMP VLAN query interval.	
Syntax	igmp query-interval <number>	
Parameter		
	Name	Description
	<number>	Valid values: 1~1800 (unit: sec). Type: Mandatory

3.8.8 igmp max-response-time <number>

Description	Set IGMP VLAN max response time.	
Syntax	igmp max-response-time <number>	
Parameter		
	Name	Description
	<number>	Valid values: 1~255 (unit: 100ms). Type: Mandatory

3.8.9 igmp last-member-query-count <number>

Description	Set IGMP VLAN last member query count.	
Syntax	igmp last-member-query-count <number>	
Parameter		
	Name	Description
	<number>	Valid values: 1~3. Type: Mandatory

3.8.10 igmp last-member-query-interval <number>

Description	Set IGMP VLAN last member query interval.	
Syntax	igmp last-member-query-interval <number>	
Parameter		
	Name	Description
	<number>	Valid values: 1~255 (unit: 100ms). Type: Mandatory

3.8.11 igmp vlan interface address <ipaddr>

Description	Set IP address of IGMP VLAN interface.	
Syntax	igmp vlan interface address <ipaddr>	
Parameter		
	Name	Description
	<ipaddr>	Valid values: 0.0.0.0~223.255.255.255. Type: Mandatory

3.8.12 ip-address <ip>

Description	Set layer3 IP address for specified VLAN.	
Syntax	ip-address <ip>	
Parameter		
	Name	Description
	<ip>	IP address. Valid values: 0.0.0.0~255.255.255.255 Type: Mandatory

3.8.13 ip-address <ip> netmask <netmask>

Description	Set layer3 IP address and netmask for specified VLAN.	
Syntax	ip-address <ip> netmask <netmask>	
Parameter		
	Name	Description
	<ip>	IP address. Valid values: 0.0.0.0~255.255.255.255 Type: Mandatory
	<netmask>	IP address. Valid values: 0.0.0.0~255.255.255.255 Type: Mandatory

3.8.14 igmp version {v2|v3| v3compatible}

Description	Set IGMP version.
Syntax	igmp version {v2 v3 v3compatible}
Parameter	None

3.9 Ring Group Mode Commands

3.9.1 ringv2-group <number>

Description	Ringv2 group interface	
Syntax	ringv2-group <number>	
Parameter		
	Name	Description
	<number>	Ring group index Valid values: 1 ~ 3 Type: Mandatory

3.9.2 guardtimer <time>

Description	Set guardtimer	
Syntax	guardtimer <time>	
Parameter		
	Name	Description
	<time>	Second. Range: Default is 10 seconds Valid values: 10~3600 Type: Mandatory

3.9.3 mode enable

Description	Enable ring protect on specific ring group
Syntax	mode enable
Parameter	None

3.9.4 mode disable

Description	Disable ring protect on specific ring group
Syntax	mode disable
Parameter	None

3.9.5 node1 <portNo>

Description	Ring node1 setting	
Syntax	node1 <portNo>	
Parameter		
	Name	Description
		Port number Valid values: 1 ~ 28 Type: Mandatory

3.9.6 node2 <portNo>

Description	Ring node2 setting	
Syntax	node2 <portNo>	
Parameter		
	Name	Description
		Port number Valid values: 1 ~ 28 Type: Mandatory

3.9.7 role ring-master

Description	Configure the role of ring group as Master of the Ring
Syntax	role ring-master
Parameter	None

3.9.8 role ring-slave

Description	Configure the role of ring group as Slave of the Ring
Syntax	role ring-slave
Parameter	None

3.9.9 role coupling-primary

Description	Configure the role of ring group as Primary of the Coupling
Syntax	role coupling-primary
Parameter	None

3.9.10 role coupling-backup

Description	Configure the role of ring group as Backup of the Coupling
Syntax	role coupling-backup
Parameter	None

3.9.11 role dual-homing

Description	Configure the role of ring group as Dual Homing
Syntax	role dual-homing
Parameter	None

3.9.12 role chain-head

Description	Configure the role of ring group as Head of the Chain
Syntax	role chain-head
Parameter	None

3.9.13 role chain-tail

Description	Configure the role of ring group as Tail of the Chain
Syntax	role chain-tail
Parameter	None

3.9.14 role chain-member

Description	Configure the role of ring group as Member of the Chain
Syntax	role chain-member
Parameter	None

3.9.15 role balancing-chain-terminal-1

Description	Configure the role of ring group as Terminal 1 of the Balancing Chain
Syntax	role balancing-chain-terminal-1
Parameter	None

3.9.16 role balancing-chain-terminal-2

Description	Configure the role of ring group as Terminal 2 of the Balancing Chain
Syntax	role balancing-chain-terminal-2
Parameter	None

3.9.17 role balancing-chain-member

Description	Configure the role of ring group as Member of the Balancing Chain
Syntax	role balancing-chain-member
Parameter	None

3.9.18 role balancing-chain-central-block

Description	Configure the role of ring group as Central Block of the Balancing Chain
Syntax	role balancing-chain-central-block
Parameter	None

3.10 IGMP MVR Mode Commands

3.10.1 igmp-mvr <number,2..15> {create|delete}

Description	Create / delete IGMP MVR profile.	
Syntax	igmp-mvr <number,2..15> {create delete}	
Parameter		
	Name	Description
	<number>	IGMP MVR profile index. Valid values: 2~15 Type: Mandatory

3.10.2 igmp-mvr <p-number> entry <e-number> <startIP> <endIP> <vid>

Description	Create IGMP MVR entry.	
Syntax	igmp-mvr <p-number> entry <e-number> <startIP> <endIP> <vid>	
Parameter		
	Name	Description
	<p-number>	IGMP MVR profile index. Valid values: 2~15 Type: Mandatory
	<e-number>	IGMP MVR entry index. Valid values: 1~32 Type: Mandatory
	<startIP> <endIP>	IP address. Valid values: 224.0.1.0~239.255.255.255 Type: Mandatory
	<vid>	VLAN ID. Valid values: 1~4094 Type: Mandatory

3.10.3 igmp-mvr <p-number> entry <e-number> delete

Description	Delete IGMP MVR entry.	
Syntax	igmp-mvr <p-number> entry <e-number> delete	
Parameter		
	Name	Description
	<p-number>	IGMP MVR profile index. Valid values: 2~15 Type: Mandatory
	<e-number>	IGMP MVR entry index. Valid values: 1~32 Type: Mandatory

3.11 IGMP ACL Mode Commands

3.11.1 igmp-acl <number> {create|delete}

Description	Create / delete IGMP ACL profile.	
Syntax	igmp-acl <number> {create delete}	
Parameter		
	Name	Description
	<number>	IGMP ACL profile index. Valid values: 2~15 Type: Mandatory

3.11.2 igmp-acl <number> {default-deny| default-permit}

Description	Set IGMP ACL default rule.	
Syntax	igmp-acl <number> {default-deny default-permit}	
Parameter		
	Name	Description
	<number>	IGMP ACL profile index. Valid values: 2~15 Type: Mandatory

3.11.3 igmp-acl <p-number> entry <e-number> <startIP> <endIP> {<vid>|all} {permit|deny}

Description	Create IGMP ACL entry.	
Syntax	igmp-acl <p-number> entry <e-number> <startIP> <endIP> {<vid> all} {permit deny}	
Parameter		
	Name	Description
	<p-number>	IGMP ACL profile index. Valid values: 2~15 Type: Mandatory
	<e-number>	IGMP MVR entry index. Valid values: 1~32 Type: Mandatory
	<startIP> <endIP>	IP address. Valid values: 224.0.1.0~239.255.255.255 Type: Mandatory
	<vid>	VLAN ID. Valid values: 1~4094 Type: Mandatory

3.11.4 igmp-acl <p-number> entry <e-number> delete

Description	Delete IGMP ACL entry	
Syntax	igmp-acl <p-number> entry <e-number> delete	
Parameter		
	Name	Description
	<p-number>	IGMP ACL profile index. Valid values: 2~15 Type: Mandatory
	<e-number>	IGMP MVR entry index. Valid values: 1~32 Type: Mandatory

3.12 Trunk Group Mode Commands

3.12.1 trunk enable static

Description	Enable link aggregation group and its mode is static.
Syntax	trunk enable static
Parameter	None

3.12.2 trunk disable

Description	Disable link aggregation group and all member port will be remove on specific port.
Syntax	trunk disable
Parameter	None

3.12.3 port-trunk add <portNo>

Description	Add member port to specific trunk group, the max member ports is 4.	
Syntax	port-trunk add <portNo>	
Parameter		
	<portNo>	Port number. Valid values: 1~28 Type: Mandatory

3.12.4 port-trunk remove {<portNo>|all}

Description	Remove member port from specific trunk group.	
Syntax	port-trunk remove <portNo>	
Parameter		
	<portNo>	Port number. Valid values: 1~28 Type: Mandatory
	all	All member port. Type: Mandatory

3.13 Alarm Related Commands

3.13.1 show profile alarm

Description	Show alarm profile list
Syntax	show profile alarm
Parameter	None

3.13.2 show alarm current

Description	Show current alarm list
Syntax	show alarm current
Parameter	None

3.13.3 show event

Description	Show event list
Syntax	show event (Refer to. event Table)
Parameter	None

3.13.4 show alarm history

Description	Show alarm history
Syntax	show alarm history
Parameter	None

3.13.5 event clear

Description	Clear event.
Syntax	event clear
Parameter	None

3.13.6 alarm history clear

Description	Clear alarm history.
Syntax	alarm history clear.
Parameter	None

3.13.7 profile alarm

Description	Enter Alarm Profile Configuration Mode.
Syntax	profile alarm
Parameter	None

3.13.8 alarm <alarmid> {mask|unmask|major|minor}

Description	Configure an alarm profile entry (default setting for each alarm is unmask and minor)	
Syntax	alarm <alarmid> mask alarm <alarmid> unmask alarm <alarmid> major alarm <alarmid> minor	
Parameter		
	Name	Description
	<alarmid>	Alarm ID Valid values: Refer to. Alarm Table Type: Mandatory
	mask	Mask this alarm Type: Mandatory
	unmask	Unmask this alarm Type: Mandatory
	major	Set alarm level to major Type: Mandatory
	minor	Set alarm level to minor Type: Mandatory