## Einrichtung eines Printservers unter MAC OS X ( hier MAC OS 10.3 )

Klicken Sie in der Systemverwaltung auf Drucker und Fax Geräte Klicken Sie auf hinzufügen

	TCP/IP-Druci			
Druckert	yp: LPD/LPR			÷.
uckeradres	se: 192.168.192	2.163		•
	Adresse ist vo	ollständig und	zulässig.	
Name o Wartelis	te:	17555 14755	A.S	¢
	Für Stand ard	warteliste bitte	leer lassen	
Druckermo	dell: Lexmark			\$
Name				
Lexmark E2	32			0
Lexmark E3	20			
Lexmark E3	22			1
	- 5 m + 2	Abbrach	A LIIS	STIFICE S
7.0				
Home	Configuration	Network	Tools	He
Home	Configuration	Network	Tools	Hel
Home	Configuration	Network	Tools	He
Home	Configuration	Network	Tools	He
Home System Status Server Name	Configuration	Network	Tools	Hel
Home System Status Server Name Model	Configuration	Network	Tools	Hel
Home System Status Server Name Model Firmware Versio	Configuration : PS-560D5A : DP-300U n : 1.21 (2004-10-22)	Network	Tools	He
Home System Status Server Name Model Firmware Versio MAC Address	Configuration : PS-560D5A : DP-300U n : 1.21 (2004-10-22) : 00 0E 3D 56 0D 56	Network	Tools	He
Home System Status Server Name Model Firmware Versio MAC Address	Configuration : PS-560D5A : DP-300U n : 1.21 (2004-10-22) : 00 0F 3D 56 0D 58 192 168 192 163 (M	Network	Tools	Hel
Home System Status Server Name Model Firmware Versio MAC Address IP Address	Configuration : PS-560D5A : DP-300U n : 1.21 (2004-10-22) 00.0F 3D 56 0D 5A 192.168.192.163 (M : 0 days, 02:54:30	Network	Tools	He
Home System Status Server Name Model Firmware Versio MAC Address IP Address Up Time	Configuration : PS-560D5A : DP-300U n : 1.21 (2004-10-22) : 00 0F 3D 56 0D 5A 192.168.192.163 (M : 0 days, 02:54:30	Network	Tools	He
Home System Status Server Name Model Firmware Versio MAC Address IP Address Up Time Printer Status	Configuration : PS-560D5A : DP-300U n: 1.21 (2004-10-22) 00.0E 3D 56 0D 5A 192.168.192.163 (M : 0 days, 02:54:30	Network	Tools	He
Home System Status Server Name Model Firmware Versio MAC Address IP Address Up Time Printer Status USB	Configuration : PS-560D5A : DP-300U n: 1.21 (2004-10-22) 00 0E 3D 56 0D 5A 192.168.192.163 (M : 0 days, 02:54:30	Network	Tools	He
Home System Status Server Name Model Firmware Versio MAC Address IP Address Up Time Printer Status USB Printer Name	Configuration : PS-560D5A : DP-300U n : 1.21 (2004-10-22) : 00 0F 3D 56 0D 5A 192.168.192.163 (M : 0 days, 02:54:30 a : USB1	Network	Tools	He
Home System Status Server Name Model Firmware Versio MAC Address IP Address Up Time Printer Status USB Printer Name Printer Status	Configuration : PS-560D5A : DP-300U n : 1.21 (2004-10-22) : 00.0E 3D 56 0D 5A 192.168.192.163 (M : 0 days, 02:54:30 : USB1 s : Offline	Network		He
Home System Status Server Name Model Firmware Versio MAC Address IP Address Up Time Printer Status USB Printer Name Printer Status	Configuration : PS-560D5A : DP-300U n: 1.21 (2004-10-22) : 00 0E 3D 56 0D 5A 192.168.192.163 (M : 0 days, 02:54:30 : USB1 : : Off line	Network		He
Home System Status Server Name Model Firmware Versio MAC Address IP Address Up Time Printer Status USB Printer Name Printer Status	Configuration : PS-560D5A : DP-300U n : 1.21 (2004-10-22) : 00 0F 3D 56 0D 5A 192.168.192.163 (M : 0 days, 02:54:30 : USB1 : : Off line	Network	Tools	He
Home System Status Server Name Model Firmware Versio MAC Address Up Time Printer Status USB Printer Status LPT1 Printer Name Printer Status	Configuration : PS-560D5A : DP-300U n: 1.21 (2004-10-22) : 00 0E 3D 56 0D 5A 192.168.192.163 (M : 0 days, 02:54:30 : USB1 : Off line : Port1 : On line	anual)		He
Home System Status Server Name Model Firmware Versio MAC Address IP Address Up Time Printer Status USB Printer Status LPT1 Printer Name Printer Status	Configuration : PS-560D5A : DP-300U n : 1.21 (2004-10-22) : 00.0E 3D 56 0D 5A 192.168.192.163 (M : 0 days, 02:54:30 : USB1 : Offline : Port1 : On line	anual)		He
Home System Status Server Name Model Firmware Versio MAC Address IP Address Up Time Printer Status USB Printer Status LPT1 Printer Name Printer Status	Configuration : PS-560D5A : DP-300U n: 1.21 (2004-10-22) : 00 0F 3D 56 0D 5A 192.168.192.163 (M : 0 days, 02:54:30 : USB1 : Off line : Port1 : On line	anual)		He
Home System Status Server Name Model Firmware Versio MAC Address Up Time Printer Status USB Printer Status LPT1 Printer Name Printer Status LPT2 Printer Name Printer Status	Configuration : PS-560D5A : DP-300U n: 1.21 (2004-10-22) : 00 0F 3D 56 0D 5A 192.168.192.163 (M : 0 days, 02:54:30 : USB1 : Off line : Port1 : On line : Port2 : Off line	anual)		He

Geben Sie unter Druckeradresse die IP Adresse des Printservers an (hier im Beispiel 192.168.192.163)

Unter Name der Warteliste geben Sie den im Printserver vergebenen Portnamen an Wählen Sie unter Druckermodell Ihren Drucker aus Klicken Sie auf hinzufügen.

Hinweis : Sollte der Printserver MAC Rendezvous ( z.B. DP-301P+ Rev C1 ) können Sie statt TCP/IP Drucker auch Rendezvous auswählen. Sollte dies nicht der Fall sein, so ist immer TCP/IP Drucker auszuwählen.