D-Link®

10000mAh Power Bank



Key Features

- A portable powerhouse with high 10,000mAh power supply capability
- Built-in intelligent digital display shows the remaining power in digital format
- Compatible with PD 3.0 and QC 3.0 for fast power supply
- Supports various power outputs with a maximum of 18W power supply
- Designed with advanced protection features: overcurrent, overvoltage, overcharge, overtemperature, and short circuit protection











User Benefits



Universal Support

Supports multiple USB ports (USB Type-C and USB Type-A) to accommodate a variety of mobile devices and gadgets



Overcurrent/Overvoltage Protection

Power supply is disabled in the event of errors caused by overcurrent, overvoltage, overcharge, or short circuit



Energy Efficiency

Standardised fast charge technologies promote efficient charge, saving time while reducing energy waste



Large Capacity

Peace of mind with sufficient capacity – top up iPhone 2.5 times, iPad mini 1.5 times, or Nintendo Switch 1.5 times*



Sleek and Slim

Lightweight design that easily slips into your pocket, allowing you to carry it anywhere



Best On-the-go Partner

Charge all your smart and portable accessories safely and efficiently, anytime and anywhere, so you can stay ahead of your schedule

Technical Specifications

Functionality	
Power Supply Capability*	10000mAH
Output Interfaces (power-out)	When only one charging port is used USB Type-C: 18W Output protocol: Power Delivery 3.0 (PD 3.0) USB Type-A: 18W Output protocol: Quick Charge 3.0 (QC 3.0) When more than one charging port is used USB Type-C & USB Type-A: Total 15W
Input Interfaces (power-in)	USB Type-C: 18W
Digital LED Display	Intelligent digital display shows the remaining power in digital format
Protection	Overcurrent Protection Overvoltage Protection Overcharge Protection Short Circuit Protection Overtemperature Protection
Quick Charge/Fast Charge	Quick Charge QC 2.0/QC 3.0 , USB Power Delivery USB PD 2.0/3.0 for fast charge
Physical	
Dimensions	105 x 72 x 23 mm
Power Input	USB Type-C
Weight	205 g
Ripple And Noise	≤240mVp-p
Operating Temperature	0 to 40 °C
Storage Temperature	-20 to 35 °C for storage period less than 3 months 23 °C ± 2 °C for storage period of 6 months or longer
Operating Humidity	20% to 90% non-condensing
Storage Humidity	5% to 45% non-condensing
Certifications	CE FCC UN38.3
Package Contents	
DPP-101	10000mAh Power Bank USB-C to USB-C Cable (100 cm) Quick Installation Guide Warranty Card

 $[*] Results \ based \ on \ lab \ tests. \ Capacity \ loss \ may \ occur \ due \ to \ circuit \ heat \ and \ voltage \ conversion.$

