

Product announcement



Product:	DSL-G604T
Product name:	ADSL Ethernet Router (Annex A), 4 Ports Switch; WLAN AP
Key features:	<ul style="list-style-type: none"> • Meets T-DSL (U-R2) performance requirements <p>ADSL</p> <ul style="list-style-type: none"> • ADSL Router with four 10/100M switching LAN ports • Data rates up to 8 Mbps for downstream and 1 MBit for upstream • Friendly Web/GUI configuration and management Interface • Supports T1.413 issue 2, G.dmt and G.lite standards • Multiple PVC supported • Supports bridged Ethernet over ATM, classical IP over ATM and PPP over ATM • Embedded PPP over Ethernet function • NAT, DHCP client/server support • Built-in MIBs for SNMP management • PAP/CHAP authentication, administrative passwords through Telnet, SNMP • Upgradeable firmware through TFTP and Web • Support UPnP feature • VPN passthrough <p>Wireless</p> <ul style="list-style-type: none"> • Support 802.11g Standard, 54Mbps • Support Data Transfer Rates of 1,2,5.5,11,22,54 Mbps at 2.4 GHz • Wireless Range of up to 900 Feet¹ • Fully 802.11b Compatible • Support up to 256-bit WEP Encryption at 2.4 GHz • Utilizes Direct Sequence Spread Spectrum (DSSS) and Packet Binary Convolutional Code (PBCC) at 2.4 GHz <ul style="list-style-type: none"> • Rate adaptive ADSL technology • DMZ and Virtual Server Mapping support • Virtual Private Network (VPN) pass-through support • Ethernet über ATM, IP über ATM, PPPoE • PAP/CHAP Authentication • Supports up to 8 virtual circuits simultaneously (PVC) • LAN port supports 10/100 MBit Fast Ethernet connection
Bid text:	DSL-G604T D-Link ADSL Ethernet Router (Annex A), 4 Port Switch 10/100 TX, Wireless Access Point, 8 MBit Down- and 1 MBit Upstream, T-DSL (UR2), 10/100 MBit LAN Port, Web based management, built-in highspeed 802.11g, 54Mbps
Why to Buy D-Link	<ul style="list-style-type: none"> • Easy to connect • Web based management • No driver for installation needed • Fast 8 MBit download speed • Built-in high speed 802.11g, 54 Mbps • Works with all ISP's (AOL, Telekom, Arcor, etc.) • For ANALOG Telephone lines • DSL Gateway ready
Technical Details:	<p>STANDARDS: ITU G.992.1 (G.dmt) ITU G.992.2 (G.lite) ITU G.994.1 (G.hs) ANSI T1.413 Issue # 2</p> <p>DATA TRANSFER RATE:</p>

	<p>G.dmt full rate: Downstream up to 8 MBit Upstream up to 1Mbit G.lite: Downstream up to 1.5 MBit Upstream up to 512 KBit MEDIA INTERFACE EXCHANGE: RJ-11 port ADSL telephone line connection RJ-45 port for 10/100 BASE-T Ethernet connection DC Inputs: 9 VAC 1A external power adapter Power Adapter: 12 V DC 1.2A Safety: TÜV/GS Power Consumption: 9 Watts Max. Operating Temperature: 5 ° to 40 ° Humidity: 5 to 95% (non-condensing) Dimensions: 180 mm x 117 mm x 30 mm Weight: 380 g EMI: CE</p>
Package Contents:	QIG, Manual CD, RJ-45 Cable, Telephone Cable, Power Supply
Retail:	Yes
UPC Code:	7.90069.265648
Units per Carton:	10
Dimensions and Weight:	530 x 365 x 385mm, 15,55 Kg (Carton) 250 x 288 x 65 mm, 1,634 Kg (Box)
Revision:	DSL-604T H/W: A1
Available:	Now
End User Price (Gross):	€

D-Link GmbH, Product Marketing Management, 28. April 2004