

Product Highlights

Easy expansion

Quickly add seven USB 2.0 ports to any PC, allowing you to connect more peripherals with ease

Sync and charge your mobile devices

Easily charge and sync your mobile devices at the same time on any of the USB ports

Compact and portable

Fits easily into any bag for travel and can still function as a USB hub when without a power adapter



DUB-H7

7-Port USB 2.0 Hub

Features

Connectivity

- Seven USB 2.0 ports
- Backwards compatible with USB 1.1

Fast Charge Mode¹

- Seven Fast Charge USB ports for high-power mobile devices such as an iPad
- Does not require a PC to charge devices
- Battery Charging 1.2
- Charging current of up to 5 V / 2.4 A for iPads and iPhones

Easy To Use

- Plug and play
- · Sleek, compact design
- Works on Windows and Mac OS PCs

The DUB-H7 7-Port USB 2.0 Hub provides an easy way to add Seven USB 2.0 ports to your notebook or desktop computer. In Fast Charge Mode, each of the USB ports can provide a maximum charging current of 2.4 A for mobile devices¹. This means you can charge devices like sync and charge iPads/tablets, while connecting additional USB devices like cameras, card readers, hard drives, mice, keyboards, and other peripherals.

Add Seven USB 2.0 Ports to Your Computer

With the DUB-H7 7-Port USB 2.0 Hub, you can conveniently add more USB ports to a notebook or desktop computer and connect up to Seven more USB peripherals. USB 2.0 technology supports data rates of up to 480 Mbps, which means that you can enjoy faster transfer speeds compared to previous USB standards.

Fast Charge Your Devices

The DUB-H7 features Seven Fast Charge USB ports that are designed to provide an increased maximum charging current of 2.4 A to connected devices¹. This makes it perfect for charging power-hungry mobile devices like the iPad quickly, as these devices have high-capacity batteries. The DUB-H7 does not require a PC to charge your devices, so you can take it with you on the road and leave your mobile device chargers at home.

DUB-H7 7-Port USB 2.0 Hub

Hardware Version		• G1
Standards		
Standards	• OHCI / UHCI / EHCI / USB 2.0 / USB 1.1	Transfer data rates of up to 480 Mbps
Interfaces	Downstream Port: 7 USB 2.0 Type-A (Female)	Upstream Port: 1 USB 2.0 Type-C (Female)
System Requirements	• Windows 10 / 8 / 7 / Vista / XP	• Mac OS X 10.4 or above
Supplied Charging Current ¹	Standard Charge Mode: 500 mA total for all seven front ports	 Fast Charge Mode¹: Max. 5 V / 1.5 A each for Battery Charging 1.2 compliant devices Max. 5 V / 2.4 A each for iPad / iPhone
Power Input	External power adapter: 5 V / 3 A DC	• Bus-powered from USB port: 5 V / 1.5 A DC
General Specifications		
Temperature	• Operating: 0 to 45 °C	• Storage: -10 to 70 ℃
Humidity	Operating: 10% to 85% non-condensing	Storage: 5% to 90% non-condensing
Dimensions (L x W x H)	• 99 x 57 x 25 mm	
Weight	• 79 g	
Certifications	• FCC • CE • RCM	• IC • RoHS

 $^{^{\}scriptscriptstyle 1}$ The total combined power draw must be under 2.4 A or 12 W with the power adapter.





