

AQUILA PRO AI BE3600 Wi-Fi 7 Smart Mesh Router

M36

Key Features

- Wi-Fi 7 technology provides ultra-high-speed performance, greater capacity, and less network congestion
- Dual-band (2.4 GHz/5 GHz) Wi-Fi with speeds up to 3.6 Gbps for seamless video streaming, gaming and video calls^{1,2}
- 4096-QAM significantly increases data throughput and capacity to more than double that of Wi-Fi 6
- OFDMA, MU-MIMO and beamforming reduce latency, improve Wi-Fi efficiency, and transmit to more devices simultaneously
- Latest WPA3™ data encryption provides the most robust network protection with enhanced privacy and security
- Multi-Link Operation (MLO) technology improves latency for real-time applications, enhances network reliability, and mitigates interference
- 2.5 Gigabit Ethernet ports enable ultra-fast connectivity
- Eco-friendly design and elegant aesthetics blend perfectly into any modern home
- Free AQUILA PRO AI app for hassle-free installation and management



User Benefits



Ultra-Fast Connections

The latest Wi-Fi 7 technology enables real-time applications with high bandwidth and data rates



AI-Optimised Connectivity

Improved Wi-Fi channel tuning, beamforming, and QoS ensure a consistent, efficient Wi-Fi experience



Reliable Connectivity

Mesh capability eliminates dead spots and weak signals for homes of any size



Multi-Link Operation MLO

Multi-Link Operation (MLO) significantly enhances wireless resiliency, throughput, and latency reduction



2.5-Gigabit Ports

2.5GbE WAN/LAN ports deliver ultra-fast Internet and local network speeds, complementing Wi-Fi 7's exceptional performance



Easy Setup and Management

Set up your mesh Wi-Fi in minutes with the AQUILA PRO AI app to effortlessly manage your network



Enhanced Security

Safer connections with separate Wi-Fi zones, advanced parental controls, WPA3™ encryption, and EN 18031/IEC 62443-4-1 certificates



Aesthetic Design

Eagle-inspired design and feather-patterned ventilation blends beauty and performance

Technical Specifications

General		
Device Interfaces	<ul style="list-style-type: none"> 3 x 2.5 Gigabit Ethernet LAN ports 1 x 2.5 Gigabit Ethernet WAN port 1 x WPS button 	<ul style="list-style-type: none"> 1 x Reset button 1 x Power connector 1 x LED on/off button
LED	Power/Status/WPS	
Antenna Type	2 x 2.4 GHz internal antennas	2 x 5 GHz internal antennas
Wi-Fi Data Rate ^{1,2}	<ul style="list-style-type: none"> 2.4 GHz up to 688 Mbps 5 GHz up to 2882 Mbps 	
IEEE Standard	<ul style="list-style-type: none"> IEEE 802.11be/ax/ac/n/g/b/k/v/a/h IEEE 802.3u/ab/bz 	
WAN Type	<ul style="list-style-type: none"> IPv4: <ul style="list-style-type: none"> Static IP Dynamic IP PPPoE PPTP L2TP IPv4 as a Service 802.1p & 802.1q VLAN tagging and priority bit 	<ul style="list-style-type: none"> IPv6: <ul style="list-style-type: none"> Auto Detection Static IPv6 Auto Configuration (SLAAC/DHCPv6) PPPoE 6RD Local Connectivity Only
Functionality		
Security Protocol	WPA2- personal	WPA3 - personal
Firewall	<ul style="list-style-type: none"> DoS Stateful Packet Inspection Anti-spoofing checking 	<ul style="list-style-type: none"> IP address filtering 1 x DMZ
Mesh	D-Link Wi-Fi Mesh (mesh system support available on select models) ³	
QoS	D-Link Intelligent QoS Technology	
Power Saving	AI ECO Mode	
Access Control	<ul style="list-style-type: none"> Advanced Parental Controls Guest zone 	<ul style="list-style-type: none"> IoT zone MLO zone
Dynamic DNS	No-IP DDNS	Dyn DDNS
Protocols	IPv4	IPv6
Operation Modes	<ul style="list-style-type: none"> Router mode Extender mode 	Bridge mode
VPN Pass-Through	<ul style="list-style-type: none"> L2TP PPTP 	IPSec
Software		
Device Management	AQUILA PRO AI app (iOS and Android™)	Web UI
Voice Assistants	Amazon Alexa	Google Assistant
Physical		
Hardware version	B1	
Dimensions	192.65 x 171.42 x 92.96 mm	
Weight	557 g (19.65 oz)	
Power Input	12 V/1.5 A	
Max Power Consumption	11.45 W	
Operating Temperature	0 to 40 °C	
Storage Temperature	-20 to 65 °C	
Operating Humidity	10% to 90% non-condensing	
Storage Humidity	5% to 95% non-condensing	
Certifications	<ul style="list-style-type: none"> CE FCC IC 	<ul style="list-style-type: none"> BSMI EN 18031 IEC 62443-4-1
Package Content		
M36	<ul style="list-style-type: none"> BE3600 Wi-Fi 7 Smart Mesh Router (M36) Power Adapter 	<ul style="list-style-type: none"> Quick Installation Guide Ethernet Cable

- Maximum wireless signal rate derived from IEEE Standard 802.11be specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, may lower actual data throughput rate. Environmental factors will adversely affect wireless signal range.
- Supported frequency bands are dependent on regional variants and may not be available in all markets.
- Please visit the product page to see which models are compatible with mesh systems.
- Google, Android and Google Home are trademarks of Google LLC.

D-Link (Deutschland) GmbH, Schwalbacher Strasse 74, 65760 Eschborn, Germany
D-Link (Europe) Ltd, 3rd Floor, 166 College Road, Harrow HA1 1BH, United Kingdom

Specifications are subject to change without notice. ©2025 D-Link. All Rights Reserved. D-Link and the D-Link logo are trademarks or registered trademarks of D-Link. All other third-party marks mentioned herein may be trademarks of their respective owners.

v1.00 EU

